



- 01 **Rugged:** Automatic arc return and non-strippable drive prevent damage from vandalism
- 02 **Versatile:** Part-and full-circle in one model, from 50° to 360°
- 03 **Efficient:** Built-in check valve saves water and reduces liability

I-25 PERFORMANCE ROTOR

This Rugged Rotor Can Stand Up to Any Commercial Job

The I-25 gets the job done with power, efficiency, and commercial-grade reliability. With a robust watering radius of 37' to 71', this rotor can be used in a variety of applications and environments. The compact, highly durable design is available in a plastic model or stainless steel for tough-as-nails strength. With a 5-year warranty, the I-25 also has options for reclaimed water ID and high-speed. A standard check valve is built in, and a wide selection of high performance nozzles are available. Efficient, tough, and built-to-last, Hunter's I-25 rotors work hard day in and day out so you don't have to.

I-25 FEATURES & SPECIFICATIONS

Features

- Models plastic/stainless steel riser: 4", 6"
- Arc settings: 50° to 360°
- Factory installed rubber cover
- Through-the-top arc adjustment
- Quick check arc mechanism
- Water lubricated gear-drive
- Nozzle choices: 12
- Nozzle range: #4 to #28
- Warranty period: 5 years

Specifications

- Radius: 37' to 71'
- Flow rate: 3.8 to 31.5 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approx.
- Nozzle trajectory: 25°

Models

I-25-04

Overall Height: 7 $\frac{7}{8}$ "
Pop-up Height: 4"
Exposed Diameter: 1 $\frac{1}{8}$ "
Inlet Size: 1" female NPT



I-25-06

Overall Height: 10 $\frac{1}{4}$ "
Pop-up Height: 6"
Exposed Diameter: 1 $\frac{1}{8}$ "
Inlet Size: 1" female NPT



I-25 (PLASTIC) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04 = 4" Pop-up I-25-06 = 6" Pop-up	Adjustable arc, plastic riser, check valve, and 5 nozzles	(blank) = No option R = Reclaimed water ID	#4 to #28 = Factory installed nozzle number

I-25 (STAINLESS STEEL) - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-25-04-SS = 4" Pop-up I-25-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve, and 5 nozzles	(blank) = No option R = Reclaimed water ID HS = High speed HS-R = High speed and reclaimed water ID	#4 to #28 = Factory installed nozzle number

Examples:

I-25-04 = 4" Pop-up, adjustable arc

I-25-04-SS - R - 18 = 4" Pop-up, adjustable arc, stainless steel riser, reclaimed water ID, and #18 nozzle

I-25-06-SS = 6" Pop-up, adjustable arc, stainless steel riser

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.


Gregory R. Hunter, President of Hunter Industries