

# QUICK COUPLERS

Size:  $\frac{3}{4}$ ", 1"  
Pressure Rating: 150 PSI

## FEATURES

- 100% interchangeable with major brands\*
- Red brass and stainless steel construction
- Heavy-duty thermoplastic locking and non-locking covers
- Optional winged stabilization and ACME key connection
- Stainless steel lug on 1" and 1½" keys
- Spring-loaded covers with stainless steel springs for positive closing and protection of valve's sealing components
- Warranty period: 5 years

\* See compatibility chart on page 163



Quick Couplers



### Reclaimed Water Option

All locking models have an optional purple TuffTop™ cover for sites using reclaimed water.

## HQ PRESSURE LOSS IN PSI

Flow (GPM)	HQ-3	HQ-33	HQ-44	HQ-5
5	0.8	1.0		
10	1.8	2.0		
15	4.1	4.3	2.2	
20	7.2	7.6	4.4	1.0
30			11.5	3.0
40				6.3
50				9.2
60				13.0
70				19.8

## QUICK COUPLER, KEY AND HOSE SWIVEL CHARTS

Model	Inlet Threads	Slots	Body	Color*	Locking	Key	Swivels
HQ-3RC	$\frac{3}{4}$ "	2	1 - Piece	Yellow	No	HK-33	HS-0
HQ-33DRC	$\frac{3}{4}$ "	2	2 - Piece	Yellow	No	HK-33	HS-0
HQ-33DLRC	$\frac{3}{4}$ "	2	2 - Piece	Yellow	Yes	HK-33	HS-0
HQ-44RC	1" NPT	1	2 - Piece	Yellow	No	HK-44	HS-1 or HS-2
HQ-44LRC	1" NPT	1	2 - Piece	Yellow	Yes	HK-44	HS-1 or HS-2
HQ-44RC-AW	1" NPT	ACME	2 - Piece Wing**	Yellow	No	HK-44A	HS-1 or HS-2
HQ-44LRC-AW	1" NPT	ACME	2 - Piece Wing**	Yellow	Yes	HK-44A	HS-1 or HS-2
HQ-5RC	1" NPT	2	1 - Piece	Yellow	No	HK-55	HS-1 or HS-2
HQ-5LRC	1" NPT	2	1 - Piece	Yellow	Yes	HK-55	HS-1 or HS-2

### Notes:

\* All locking cover models are available with purple covers for reclaimed water applications.

\*\* Anti-rotation stabilization wings.

**QUICK COUPLER - SPECIFICATION BUILDER:** ORDER 1 + 2 + 3

1 Model	2 Cover Options	3 Additional Options
<b>HQ3</b> = ¾" Inlet, 1-piece body, 2 slots <b>HQ5</b> = 1" Inlet, 1-piece body, 2 slots <b>HQ33D</b> = ¾" Inlet, 2-piece body, 2 slots <b>HQ44</b> = 1" Inlet, 2-piece body, 1 slot or ACME key socket	<b>RC</b> = Yellow rubber cover <b>LRC</b> = Yellow locking rubber cover <i>(Not available for HQ3 body)</i>	<b>(blank)</b> = No option <b>AW</b> = ACME key with anti-rotation wings <i>(Only available for HQ44 body)</i> <b>R</b> = Purple locking cover <i>(reclaimed water ID; only available for LRC models)</i>

**Examples:**

HQ3 - RC = HQ3 valve with rubber cover

HQ44 - LRC = HQ44 valve with locking rubber cover

HQ44 - LRC - R = HQ44 valve with locking rubber cover and reclaimed water ID

HQ44 - LRC - AW - R = HQ44 valve, with locking rubber cover, ACME key socket with anti-rotation wings and reclaimed water ID

**KEYS**

Model	Compatible Valve	Compatible Swivel
HK33 = ¾" valve, ¾" key inlet	HQ3, HQ33	HS0
HK44 = 1" valve, 1" key inlet	HQ44	HS1, HS2, HS1B, HS2B
HK44A = 1" valve, ACME key inlet	HQ44AW	HS1, HS2, HS1B, HS2B
HK55 = 1" valve, 1¼" key inlet	HQ5	HS1, HS2, HS1B, HS2B

**HS HOSE SWIVELS**

Model	Compatible Key
HS0 = ¾" inlet, ¾" hose outlet	HK33
HS1 = 1" inlet, ¾" hose outlet	HK44, HK44A, HK55
HS2 = 1" inlet, 1" hose outlet	HK44, HK44A, HK55



① HQ5LRC Quick Coupler with SnapLok™ equipped HSJ-1 swing joint

Introducing Hunter's new full line of HSJ heavy-duty swing joints with configurations for every need and every project. There is even a version specifically designed for quick coupler applications. The SnapLok outlet on HSJ-1 models is equipped with accommodations for both rebar and pipe stabilization, as well as heavy-duty brass outlet threads with a unique anti-rotation locking feature.

[See the HSJ swing joints on page 47](#)