

MINI-CLIK®

Sensor: **Rain**

FEATURES

- Easily installs on any automatic irrigation system
- Debris tolerant for reliable operation without unnecessary shutdowns
- Can be set to shut system off from 1/8" to 3/4" of rainfall
- Includes 25' of 20 AWG sheathed, two-conductor, UL-approved wire
- Optional user-installed metal gutter mount for Mini-Clik (order SGM)
- Optional user-installed stainless steel sensor guard enclosure for Mini-Clik (order SG-MC, Includes Mini-Clik)
- Warranty period: 5 years

SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: 20 AWG, UL listed, typically interrupts the common ground wire between the solenoid valves and controller



MINI-CLIK
Height: 2"
Length: 6"



SG-MC
Stainless steel sensor guard enclosure for Mini-Clik. Includes Mini-Clik.



SGM
Optional gutter mount

MINI-CLIK®	
Model	Description
MINI-CLIK	Rain Sensor
MINI-CLIK-NO	Rain Sensor with "normally-open" switch
MINI-CLIK-C	Rain Sensor with conduit mount
MINI-CLIK-HV	Rain Sensor for high voltage application (120/230 VAC)

FREEZE-CLIK®

Sensor: **Freeze**

FEATURES

- Installs easily with no adjustment needed
- Accurate temperature sensing shuts system off when air temperature reaches 37°F
- Used with other sensors to enhance overall efficiency of irrigation systems
- Warranty period: 5 years

Note: Not intended for agricultural applications

SPECIFICATIONS

- Switch rating: 24 VAC, 5 A
- Wiring: Typically interrupts the common ground wire between the solenoid valves and the controller
- UL listed



FREEZE-CLIK
Height: 2"
Length: 6"

FREEZE-CLIK®	
Model	Description
FREEZE-CLIK	Freeze sensor interrupts irrigation when temperatures drop below 37° F
FREEZE-CLIK REV	Freeze sensor interrupts irrigation below 37°F for non-Hunter controllers with normally open sensor inputs

SENSORS