

I-20

Radius: **17' to 46'**
Flow: **0.36 to 14.8 GPM**
Inlet: **¾"**

FEATURES

- Models plastic riser: Shrub, 4", 6", 12"
- Models stainless steel riser: 4", 6"
- Arc setting: 50° to 360°
- Factory installed rubber cover
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water lubricated gear-drive
- Nozzle choices: 34
- Nozzle racks: 1.5 to 8.0 Blue, 2.0 to 4.5 Low Angle Gray, 0.50 to 3.0 Short Radius Black, 6.0 to 13.0 Green, MPR-25, MPR-30, MPR-35
- Warranty period: 5 years
- ▶ Automatic arc return
- ▶ Non-strippable drive
- ▶ Part- and full-circle in one model
- ▶ Headed and slotted set screw
- ▶ FloStop® control
- ▶ Reclaimed water ID
- ▶ Stainless steel riser
- ▶ Drain check valve (up to 10' of elevation)

OPERATING SPECIFICATIONS

- Radius: 17' to 46'
- Flow: 0.36 to 14.8 GPM
- Recommended pressure range: 25 to 70 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.4 in/hr approximately
- Nozzle trajectory: Std = 25°, Low Angle = 13°

▶ = *Advanced Feature descriptions on page 30*



I-20 Reclaimed

Available as a factory installed option on all models

I-20 (PLASTIC) – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-20-00 = Shrub I-20-04 = 4" Pop-up I-20-06 = 6" Pop-up I-20-12 = 12" Pop-up	Adjustable arc, plastic riser, check valve, 8 standard nozzles, and 4 low-angle nozzles	(blank) = No option NCV = Without check valve (only available on 4" model) R = Drain check valve and reclaimed water ID	Blue 1.5 - 8.0 Gray Low Angle Black Short Radius Green High Flow MPR-25-Q, T, H, F MPR-30-Q, T, H, F MPR-35-Q, T, H, F 1.5 to 4.0 = only nozzles 1.5 - 4.0 can be factory-installed

I-20 (STAINLESS STEEL) – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-20-04-SS = 4" Pop-up I-20-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve, 8 standard nozzles, and 4 low-angle nozzles	(blank) = No option NCV = Without check valve (only available on 4" model) R = Drain check valve and reclaimed water ID	Blue 1.5 - 8.0 Gray Low Angle Black Short Radius Green High Flow MPR-25-Q, T, H, F MPR-30-Q, T, H, F MPR-35-Q, T, H, F 1.5 to 4.0 = only nozzles 1.5 - 4.0 can be factory-installed

Examples:

I-20-12 - **R** - **4.0** = 12" Pop-up, adjustable arc, with reclaimed water ID, and 4.0 nozzle



I-20-00

Overall height: 7¾"
Exposed diameter: 1¾"
Inlet size: ¾"



I-20-04

Overall height: 7½"
Pop-up height: 4"
Exposed diameter: 1¾"
Inlet size: ¾"



I-20-06

Overall height: 9½"
Pop-up height: 6"
Exposed diameter: 1¾"
Inlet size: ¾"



I-20-12

Overall height: 17"
Pop-up height: 12"
Exposed diameter: 1¾"
Inlet size: ¾"