

RESIDENTIAL & COMMERCIAL IRRIGATION

Built on Innovation®



- 01 **Durable:** Stainless steel riser built to withstand tough conditions
- 02 **Accurate:** Triple nozzle system provides uniform, wind-resistant distribution
- 03 **Reliable:** Automatic arc return and non-strippable drive ensures dependability

I-40 ROTOR

For Sports Fields and Parks, the I-40 Delivers Professional Results

The I-40 is a tough commercial rotor that delivers water with accuracy and efficiency at distances up to 70 feet. Featuring diverse three-port nozzle options, a non-strippable drive, and a thick rubber cover built to prevent injury, it's no wonder this rotor is found most often in stadiums worldwide. With the strength of stainless steel, the I-40 is built to last in the harshest sports, public park, and commercial environments. If efficiency, effective irrigation, and beautiful results are the goal, the I-40 is the irrigation professional's best solution.

I-40 FEATURES & SPECIFICATIONS

Features

- Stainless riser models: 4", 6"
- Arc setting: 50 to 360 degrees
- Factory installed rubber cover
- Nozzle choices: 12
- Nozzle ranges I-40: #8 to #25
- Nozzle ranges I-40-ON: #15 to #28
- Through-the-top arc adjustment
- Quick check arc mechanism
- Water lubricated gear drive
- Warranty period: 5 years

Specifications

- Radius I-40: 44' to 69'
- Radius I-40-ON: 52' to 76'
- Flow rate I-40: 7.6 to 29.5 GPM
- Flow rate I-40-ON: 13.0 to 33.7 GPM
- Recommended pressure range: 40 to 100 PSI
- Operating pressure range: 40 to 100 PSI
- Precipitation rates: 0.4 in/hr approx.
- Nozzle trajectory: 25 degrees

Models



I-40-04

Overall Height: 7 $\frac{7}{8}$ "
Pop-up Height: 4"
Exposed Diameter: 2"
Inlet Size: 1"



I-40-06

Overall Height: 10 $\frac{1}{4}$ "
Pop-up Height: 6"
Exposed Diameter: 2"
Inlet Size: 1"



I-40 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-06-SS = 6" Pop-up	Adjustable arc, stainless steel riser, check valve and 6 nozzles	(blank) = No option HS = High speed HS-R = High speed and reclaimed water ID R = Reclaimed water ID	#8 to #25 = Factory installed nozzle number

I-40-ON - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-40-04-SS-ON = 4" Pop-up I-40-06-SS-ON = 6" Pop-up	Full-circle, opposing nozzle, stainless steel riser, check valve and 6 nozzles	(blank) = No option ON = Full-circle opposing nozzle ON-R = Full-circle opposing nozzles, reclaimed water ID HS = High speed HS-R = High speed and reclaimed water ID R = Reclaimed water ID	#15 to #28 = Factory-installed nozzle number

Website hunterindustries.com | **Customer Support** 1-800-383-4747 | **Technical Service** 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.


Gregory R. Hunter, President of Hunter Industries

