

I-90

Radius: **66' to 103'**
Flow: **29.5 to 83.8 GPM**
Inlet: **1½"**

FEATURES

- Model: 3"
- Arc setting: 40° to 360°
- Dual trajectory nozzle choices:
 - 8 standard trajectory 22.5°
 - 8 low angle trajectory 15°
- Nozzle range: #25 to #73
- Exclusive PressurePort™ nozzle technology
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water lubricated gear-drive
- Standard factory installed nozzle: #53
- Factory installed rubber logo cap
- Warranty period: 5 years
- ▶ Opposing nozzle 360° model
- ▶ Dual trajectory color-coded nozzles
- ▶ Optional reclaimed water ID
- ▶ Drain check valve (up to 9' of elevation)



I-90

Overall height: ADV/36V: 11"
Pop-up height: 3"
Exposed diameter: 3½"
Inlet size: 1½"

OPERATING SPECIFICATIONS

- Radius: 66' to 103'
- Flow: 29.5 to 83.8 GPM
- Recommended pressure range: 80 to 120 PSI
- Operating pressure range: 80 to 120 PSI
- Precipitation rates: 0.75 in/hr approximately

USER-INSTALLED OPTION

- Turf Cup Kit
 - I-90 all: P/N 467955
- Rubber Cover Kit
 - I-90-ADV: P/N 234200 (all)
 - I-90-36V: P/N 234200 (0711 date code and after)
 - I-90-36V: P/N 234201 (0611 date code and prior only)
- Low-Angle Nozzles - #25 to #73

▶ = [Advanced Feature descriptions on page 30](#)



Turf cup kit
P/N 467955



Rubber cover kits
P/N 234200; P/N 234201



I-90 Reclaimed

Available as a factory installed option on all models

I-90 - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1 Model	2 Standard Features	3 Feature Options	4 Nozzle Options
I-90 = 3" Pop-up	Plastic riser, check valve, and 8 nozzles	ADV = Adjustable arc ARV = Adjustable arc and reclaimed water ID 36V = Full-circle, opposing nozzles 3RV = Full-circle, opposing nozzles and reclaimed water ID	#25 to #73 = Factory installed nozzle number

Examples:

I-90 - ADV = 3" Pop-up, adjustable arc

I-90 - 36V - 43 = 3" Pop-up, full-circle, opposing nozzles, and #43 nozzle

I-90 - 3RV - 63 = 3" Pop-up, full-circle, opposing nozzles, reclaimed water ID, and #63 nozzle

I-90-ADV NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr ■ ▲	
25 ● Lt. Blue	80	66	29.5	1.30	1.51
	90	67	31.5	1.35	1.56
	100	68	33.2	1.38	1.60
	110	69	35.6	1.44	1.66
33 ● Gray	80	68	36.2	1.51	1.74
	90	69	38.2	1.54	1.78
	100	70	40.4	1.59	1.83
	110	71	42.6	1.63	1.88
38 ● Red	80	72	40.6	1.51	1.74
	90	73	43.0	1.55	1.79
	100	75	45.4	1.55	1.79
	110	76	47.6	1.59	1.83
43 ● Dk. Brown	80	74	46.1	1.62	1.87
	90	74	48.5	1.70	1.97
	100	75	50.7	1.74	2.00
	110	77	53.4	1.73	2.00
48 ● Dk. Green	80	77	50.2	1.63	1.88
	90	79	52.6	1.62	1.87
	100	81	55.1	1.62	1.87
	110	82	57.5	1.65	1.90
53 ● Dk. Blue*	80	81	54.9	1.61	1.86
	90	84	57.2	1.56	1.80
	100	86	59.5	1.55	1.79
	110	87	62.1	1.58	1.82
	120	88	64.4	1.60	1.85
63 ● Black	80	86	62.3	1.62	1.87
	90	88	65.5	1.63	1.88
	100	90	69.0	1.64	1.89
	110	91	71.9	1.67	1.93
	120	92	74.7	1.70	1.96
73 ● Orange	80	89	72.7	1.77	2.04
	90	91	75.4	1.75	2.02
	100	93	78.1	1.74	2.01
	110	95	80.9	1.73	1.99
	120	97	83.8	1.71	1.98

* Factory installed nozzle

Notes:

Precipitation rates for ADV models are calculated for 180° operation. Precipitation rates for 36V models are calculated for 360° operation. All triangular rates are equilateral. Complies to ASAE standard.

I-90-36V NOZZLE PERFORMANCE DATA

Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr ■ ▲	
25 ● Lt. Blue	80	73	30.5	0.55	0.64
	90	75	32.4	0.55	0.64
	100	76	34.3	0.57	0.66
	110	78	36.5	0.58	0.67
33 ● Gray	80	77	36.3	0.59	0.68
	90	78	38.4	0.61	0.70
	100	80	40.6	0.61	0.71
	110	81	42.7	0.63	0.72
38 ● Red	80	80	40.6	0.61	0.71
	90	82	42.9	0.61	0.71
	100	83	45.3	0.63	0.73
	110	85	47.7	0.64	0.73
43 ● Dk. Brown	80	83	46.2	0.65	0.75
	90	84	48.6	0.66	0.77
	100	85	50.9	0.68	0.78
	110	86	53.4	0.69	0.80
48 ● Dk. Green	80	86	49.6	0.65	0.75
	90	89	52.5	0.64	0.74
	100	90	54.8	0.65	0.75
	110	91	57.3	0.67	0.77
53 ● Dk. Blue*	80	89	54.2	0.66	0.76
	90	90	56.7	0.67	0.78
	100	92	59.2	0.67	0.78
	110	93	61.7	0.69	0.79
	120	94	64.2	0.70	0.81
63 ● Black	80	92	63.2	0.72	0.83
	90	94	65.9	0.72	0.83
	100	96	69.4	0.72	0.84
	110	97	72.0	0.74	0.85
	120	98	74.9	0.75	0.87
73 ● Orange	80	96	72.1	0.75	0.87
	90	98	75.0	0.75	0.87
	100	99	77.8	0.76	0.88
	110	102	80.5	0.74	0.86
	120	103	83.3	0.76	0.87

I-90 NOZZLES

ADV & 36V



Low-Angle ADV & 36V**

** Low angle nozzles reduce radius by 15%

I-90