

PRS30

PRESSURE REGULATED

Models: **Shrub, 4", 6", 12"**
Pressure Regulation: **30 PSI**

FEATURES

- Models: Shrub, 4", 6", 12"
- Side inlet (SI) version available in 6" and 12"
- Identification cap is brown for easy field ID
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve
- ▶ Pressure regulated to 30 PSI
- ▶ FloGuard™ technology

OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

FACTORY INSTALLED OPTIONS

- Drain check valve (up to 14' of elevation)
- Check valve available on 4", 6", 12"
- Reclaimed water ID cap
- FloGuard technology available for check valve models

USER INSTALLED OPTIONS

- Vandal-proof cap (P/N PROS-PRS30-VPC)
- Drain check valve (up to 14' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458560)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)

▶ = *Advanced Feature descriptions on page 52*



PROS-00-PRS30
Retracted height: 4½"
Inlet size: ½"



PROS-04-PRS30
Retracted height: 5⅞"
Pop-up height: 4"
Exposed diameter: 2¼"
Inlet size: ½"



[A] **PROS-06-SI-PRS30**
[B] **PROS-06-PRS30**
Retracted height: 8¾"
Pop-up height: 6"
Exposed diameter: 2¼"
Inlet size: ½"



[A] **PROS-12-SI-PRS30**
[B] **PROS-12-PRS30**
Retracted height: 16⅞"
Pop-up height: 12"
Exposed diameter: 2¼"
Inlet size: ½"

PRS30 – SPECIFICATION BUILDER: ORDER 1 + 2 + 3

1 Model	2 Feature Options	3 Specialty Options
PROS-00-PRS30 = 30 PSI regulated shrub adapter	(blank) = No option	(blank) = No option
PROS-04-PRS30 = 30 PSI regulated 4" pop-up	CV = Factory-installed drain check valve (Pop-up models only 6" and 12" models ordered as CV will come as no side inlet)	R = Factory-installed reclaimed body cap
PROS-06-PRS30 = 30 PSI regulated 6" pop-up		F = FloGuard technology
PROS-12-PRS30 = 30 PSI regulated 12" pop-up		F-R = FloGuard technology with reclaimed body cap

PRS30 (SIDE INLET) MODELS

Model

PROS-06-SI-PRS30 = 30 PSI regulated 6" pop-up with side inlet

PROS-12-SI-PRS30 = 30 PSI regulated 12" pop-up with side inlet

Examples:

PROS-06-SI-PRS30 = 6" Pop-up with side inlet regulated at 30 PSI

PROS-06-PRS30-CV = 6" Pop-up regulated at 30 PSI, drain check valve

PROS-12-PRS30-CV-F-R = 12" Pop-up regulated at 30 PSI, drain check valve, and FloGuard technology with reclaimed body cap



PRS30 Reclaimed

PRS30 models include optional factory-installed purple reclaimed caps



Related Solutions: Works Best With

Pro-Spray® Fixed Arc Nozzles and Pro Adjustable Nozzles work best with PRS30