

# PRO-SPRAY®

Models: **Shrub, 2", 3", 4", 6", 12"**  
Inlet: **½"**

## FEATURES

- Models: Shrub, 2", 3", 4", 6", 12"
- Compatible with all female threaded nozzles
- Side inlet (SI) version available in 6" and 12"
- Innovative directional flush plug design
- Warranty period: 5 years
- ▶ Co-molded wiper seal
- ▶ Heavy-duty spring
- ▶ Industry's strongest spray body
- ▶ Innovative seal design
- ▶ Pro-Spray check valve

## OPERATING SPECIFICATIONS

- Operational pressure range: 15 to 100 PSI

## FACTORY INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation)
- Check valve available on 4", 6", 12"
- Reclaimed water ID cap

## USER INSTALLED OPTIONS

- Drain check valve (up to 10' of elevation; P/N 437400SP)
- Reclaimed water ID cap (P/N 458520SP)
- Snap-on reclaimed cover (P/N PROS-RC-CAP)
- ▶ = *Advanced Feature descriptions on page 52*



### Pro-Spray Reclaimed

Pro-Spray models include optional factory-installed purple reclaimed caps

## PRO-SPRAY® - SPECIFICATION BUILDER: ORDER 1 + 2

| 1 Models                                       | 2 Options                                                                                                                              |
|------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------|
| <b>PROS-00</b> = Shrub Adapter                 | <b>(blank)</b> = No option                                                                                                             |
| <b>PROS-02</b> = 2" Pop-up                     | <b>CV</b> = Factory-installed drain check valve<br>(Pop-up models only, 6" and 12" models<br>ordered as CV will come as no side inlet) |
| <b>PROS-03</b> = 3" Pop-up                     | <b>CV-R</b> = Factory-installed reclaimed body cap<br>(Shrub molded in purple)                                                         |
| <b>PROS-04</b> = 4" Pop-up                     |                                                                                                                                        |
| <b>PROS-06-SI</b> = 6" Pop-up with side inlet  |                                                                                                                                        |
| <b>PROS-06</b> = 6" Pop-up (no side inlet)     |                                                                                                                                        |
| <b>PROS-12-SI</b> = 12" Pop-up with side inlet |                                                                                                                                        |
| <b>PROS-12</b> = 12" Pop-up (no side inlet)    |                                                                                                                                        |

### Examples:

**PROS-04** = 4" pop-up

**PROS-06 - CV** = 6" pop-up, drain check valve

**PROS-12 - CV-R** = 12" pop-up, drain check valve, reclaimed body cap



### PROS-00

Retracted height: 1½"  
Inlet size: ½"



### PROS-02

Retracted height: 4"  
Pop-up height: 2"  
Exposed diameter: 2¼"  
Inlet size: ½"



### PROS-03

Retracted height: 5"  
Pop-up height: 3"  
Exposed diameter: 2¼"  
Inlet size: ½"  
Shut-Off



### PROS-04

Retracted height: 5⅞"  
Pop-up height: 4"  
Exposed diameter: 2¼"  
Inlet size: ½"  
Shut-Off



### [A] PROS-06-SI

### [B] PROS-06

Retracted height: 8¾"  
Pop-up height: 6"  
Exposed diameter: 2¼"  
Inlet size: ½"



### [A] PROS-12-SI

### [B] PROS-12

Retracted height: 16⅞"  
Pop-up height: 12"  
Exposed diameter: 2¼"  
Inlet size: ½"