

SRM

Radius: **15' to 30'**
Flow: **0.42 to 3.4 GPM**
Inlet: **½"**

FEATURES

- Model: 4"
- Arc setting: 40° to 360°
- Nozzle choices: 6
- Nozzle range: 0.50 to 3.0
- Standard factory installed nozzle: 3.0 only
- Through-the-top arc adjustment
- QuickCheck™ arc mechanism
- Water lubricated gear-drive
- Warranty period: 1 year

OPERATING SPECIFICATIONS

- Radius: 15' to 30'
- Flow: 0.42 to 3.4 GPM
- Recommended pressure range: 30 to 50 PSI
- Operating pressure range: 20 to 100 PSI
- Precipitation rates: 0.45 in/hr approximately
- Nozzle trajectory: 18° approximately



SRM-04

Overall height: 6⅝"
Pop-up height: 4"
Exposed diameter: 1⅝"
Inlet size: ½"

ROTORS

SRM		SRM NOZZLES
Model	Description	
SRM-04	4" Pop-up, adjustable arc, 6 standard nozzles	

SRM



SRM GREEN NOZZLE PERFORMANCE DATA					
Nozzle	Pressure PSI	Radius ft.	Flow GPM	Precip in/hr ■ ▲	
.50 ● Dk. Green	30	15	0.42	0.36	0.41
	40	16	0.50	0.38	0.43
	50	17	0.58	0.39	0.45
.75 ● Dk. Green	30	15	0.42	0.36	0.41
	40	16	0.50	0.38	0.43
	50	17	0.58	0.39	0.45
1.0 ● Dk. Green	30	19	0.85	0.45	0.52
	40	20	1.0	0.48	0.56
	50	20	1.1	0.53	0.61
1.5 ● Dk. Green	30	23	1.3	0.47	0.55
	40	24	1.5	0.50	0.58
	50	25	1.7	0.52	0.60
2.0 ● Dk. Green	30	25	1.7	0.52	0.60
	40	26	2.0	0.57	0.66
	50	27	2.3	0.61	0.70
3.0 ● Dk. Green	30	28	2.5	0.61	0.71
	40	30	3.0	0.64	0.74
	50	30	3.4	0.73	0.84

Bold = Recommended pressure

Note:

All precipitation rates calculated for 180° operation. For the precipitation rate for a 360° sprinkler, divide by 2.