# **FITTINGS**

Fittings: **16-18 mm Dripline** 

**Uses: Barbed and Premium Fittings** 

## **BARBED FITTINGS**

- Acetal material
- Dual barb provides stronger hold than single barb
- Ideal for use with Eco-Mat®, Eco-Wrap™, PLD
- · Fits 17 mm dripline and tubing
- · Brown color to match PLD dripline
- No clamps necessary
- Warranty period: 1 year

#### **OPERATING SPECIFICATIONS**

• Maximum pressure: 60 PSI

## **FITTINGS**



**PLD-075** 34" MPT x 17 mm Barb



**PLD-050** ½" MPT x 17 mm Barb



**PLD-ELB** 17 mm Barb Elbow



**PLD-CPL** 17 mm Barb Coupling



PLD-CAP 17 mm Barb x ½" MPT with Cap



**PLD-TEE** 17 mm Barb Tee



PLD-075-TBTEE 17 mm Barb Tee x ¾" Thread



**PLD-BV** 17 mm Barb Shut-off Valve



PLD-AVR ½" Air/Vacuum Relief Valve

#### **PLD-LOC**

- · High quality glass-filled polypropylene
- Easy push-on installation, threads lock it into place
- Easier and faster than other fittings
- Fits multiple sizes of dripline and tubing (Inside diameter range from 0.520" to 0.620")
- Brown color blends in with dripline and landscape
- · Reusable and ideal for drip irrigation maintenance
- Warranty period: 2 years

#### **OPERATING SPECIFICATIONS**

· Maximum pressure: 60 PSI

## **FITTINGS**



**PLD-LOC 075**34" Male Pipe Thread x Loc



PLD-LOC 050 ½" Male Pipe Thread x Loc



PLD-LOC ELB Locking Elbow



**PLD-LOC CPL**Locking Coupler



PLD-LOC CAP End Cap x Loc



PLD-LOC TEE Locking Tee



PLD-LOC FHS 34" Female Hose Swivel x Loc