

RESIDENTIAL & COMMERCIAL IRRIGATION Built on Innovation®



- O1 Convenient: Visible bright yellow or reclaimed purple riser stem and cap confirm system operation.
- **Reliable:** Stem pops up when pressure exceeds the threshold, indicating low pressures if not raised.
- **O3 Flexible:** Connects via bottom or side inlet ports for easy installation; side inlet port is available on 12" version.

ECO-INDICATOR

Visually Confirm Irrigation System Operation and Adequate Pressure with This Convenient Device

The Eco-Indicator provides a visual confirmation that an irrigation system is operating properly. Whether you are using landscape dripline, online emitter products, or subsurface products such as the Eco-Mat® or Eco-Wrap® Systems, the Eco-Indicator will verify the system is pressurized.

It has a simple design and is easy to install. Depending on the model, the bright yellow or reclaimed purple indicator stem will extend to a height of 6" or 12" when the system is running. When the system shuts off, the Eco-Indicator will retract to a protected position out of sight.



ECO-INDICATOR FEATURES & SPECIFICATIONS

Key Benefits

- Visible bright yellow or reclaimed purple riser stem and cap indicate when system is in operation
- Stem pops up when pressure exceeds the threshold and assists in confirming low pressures if not raised
- Connects via bottom or side inlet ports for easy installation; side inlet port is available on 12" version only

Operating Specifications

ECO-ID

• Operating pressure: up to 70 PSI

• Indication of system operation: above 12 PSI

• Warranty period: 2 years

ECO-ID-12, ECO-ID-12-R

• Operating pressure: up to 100 PSI

• Indication of system operation: above 15 PSI

• Warranty period: 5 years

USER-INSTALLED OPTIONS FOR 12" ECO-INDICATOR

• Drain check valve (up to 10' of elevation; P/N 437400SP)

• SJ Swing Joint: SJ-512 (1/2" threaded x 12" length)

ECO-INDICATOR	
Model	Description
ECO-ID	6" Eco-Indicator
ECO-ID-12	12" Eco-Indicator
ECO-ID-12-R	12" Eco-Indicator, Reclaimed



The Eco-Indicator is compatible with rigid PVC systems and any PE tubing or dripline (both traditional and subsurface) with the appropriate connections.

Website hunterindustries.com | Customer Support 1-800-383-4747 | Technical Service 1-800-733-2823

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.