

B SERIES

Models: **G80B**
Radius: **20.4 to 26.8 m**
Flow: **5.11 to 13.15 m³/hr; 85.2 to 219.2 l/min**

FEATURES

- Full circle opposing nozzles
- Colour-coded nozzles: 7 standard trajectory (25°)
- Nozzle range: #23 to #53
- Exclusive PressurePort™ nozzle technology
- Water lubricated gear-drives
- Check height up to 3 m in elevation change

OPERATING SPECIFICATIONS

- Radius: 20.4 to 26.8 m
- Flow: 5.11 to 13.15 m³/hr; 85.2 to 219.2 l/min
- Pressure range: 4.5 to 6.9 bar; 450 to 690 kPa
- All B Series rotors are pressure rated at 10 bar; 1,000 kPa



G80B
Pop-up height: 8 cm
Overall height: 24.5 cm
Flange diameter: 13.7 cm
Female Inlet: 1¼" ACME

G80B – SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

1	Model	2	Valve Options	3	Nozzle	4	Options*
G80 = Full Circle		B = Block rotor with check valve		23 to 53 = Installed G80 Nozzle* * SSU = #23, #25 or #48		S = SSU* * Standard Stocking Unit	

Example:
G80 - B - 25 - S = G80 full circle block rotor, installed #25 nozzle, standard stocking unit model

G80B NOZZLE PERFORMANCE DATA*

Nozzle	Pressure		Radius m	Flow		Precip mm/hr	
	bar	kPa		m ³ /hr	l/min	■	▲
23 ● Green	4.5	450	20.4	5.11	85.2	12.3	14.1
	4.8	480	21.0	5.43	90.5	12.3	14.2
	5.5	550	21.6	5.91	98.4	12.6	14.6
	6.2	620	21.9	6.34	105.6	13.2	15.2
	6.9	690	22.3	6.77	112.8	13.7	15.8
25 ● Blue	4.5	450	21.6	6.54	109.0	14.0	16.1
	4.8	480	22.3	6.79	113.2	13.7	15.8
	5.5	550	22.6	7.29	121.5	14.3	16.5
	6.2	620	22.9	7.79	129.8	14.9	17.2
	6.9	690	23.2	8.18	136.3	15.2	17.6
33 ● Grey	4.5	450	22.3	7.04	117.3	14.2	16.4
	4.8	480	22.6	7.31	121.9	14.4	16.6
	5.5	550	23.2	7.88	131.4	14.7	17.0
	6.2	620	23.5	8.40	140.1	15.3	17.6
	6.9	690	23.8	8.81	146.9	15.6	18.0
38 ● Red	4.5	450	23.2	7.97	132.9	14.9	17.2
	4.8	480	23.5	8.25	137.4	15.0	17.3
	5.5	550	24.1	8.75	145.7	15.1	17.4
	6.2	620	24.4	9.20	153.3	15.5	17.9
	6.9	690	24.7	9.75	162.4	16.0	18.5
43 ● Dk. Brown	4.5	450	23.8	8.90	148.4	15.8	18.2
	4.8	480	24.1	9.27	154.4	16.0	18.5
	5.5	550	25.0	9.93	165.4	15.9	18.3
	6.2	620	25.3	10.56	176.0	16.5	19.1
	6.9	690	25.6	11.09	184.7	16.9	19.5
48 ● Dk. Green	4.5	450	25.0	9.95	165.8	15.9	18.4
	4.8	480	25.3	10.52	175.3	16.4	19.0
	5.5	550	25.9	11.13	185.5	16.6	19.1
	6.2	620	26.2	11.79	196.5	17.2	19.8
	6.9	690	26.5	12.36	205.9	17.6	20.3
53 ● Dk. Blue	4.5	450	25.3	10.65	177.5	16.6	19.2
	4.8	480	25.6	11.15	185.9	17.0	19.6
	5.5	550	26.5	11.95	199.1	17.0	19.6
	6.2	620	26.8	12.45	207.4	17.3	20.0
	6.9	690	26.8	13.15	219.2	18.3	21.1

G80B NOZZLES

* Complies to ASAE standard. All precipitation rates calculated for 360° operation. All triangular rates are equilateral.

G80B