

# HDL

HUNTER DRIPLINE HDL-CV, HDL-PC, HDL-R

Flow: **0.4, 0.6, 0.9 GPH**  
Surface or Subsurface Irrigation: **Gardens, Turf, Tree Rings, Green Walls, Irregular Spaces**

## FEATURES

- Pressure-compensating emitters
- Color-coded stripes to identify flow
- Flow rates of 0.4, 0.6, 0.9 GPH
- Emitter spacing at 12", 18", and 24"
- Tubing diameter: 0.660" (OD) x .560" (ID)
- Wall thickness 0.05"
- Strong UV resistance
- Stretch-wrapped 100', 250', and 500' coils make handling easy and efficient
- Available without emitters (blank)
- Emitter inlet filtration to prevent clogging
- Extra-wide flow labyrinth prevents clogging
- Full-size outlet pool and raised wall inhibit debris and roots from entering the emitter
- Warranty period: 5 years (plus 2 additional years for environmental stress cracking)
- Check valves keep the line charged up to 6' and prevent low-point drainage (HDL-CV only)

## OPERATING SPECIFICATIONS

- HDL-CV:
  - Pressure-compensating, non-draining emitters
  - Operating pressure range: 15 to 60 PSI
  - Minimum filtration: 120 mesh; 125 microns
- HDL-PC and HDL-R:
  - Pressure-compensating
  - Operating pressure range: 10 to 60 PSI
  - Minimum filtration: 120 mesh; 125 microns

► = *Application Rate charts on page 171*



HDL-CV



HDL-PC



HDL-R (Reclaimed)



Coil with Stretch Wrap

### HDL - SPECIFICATION BUILDER: ORDER 1 + 2 + 3 + 4

| 1 | Model                  | 2        | Spacing | 3           | Length | 4                                                                                                                                     | Options |
|---|------------------------|----------|---------|-------------|--------|---------------------------------------------------------------------------------------------------------------------------------------|---------|
|   | HDL-04 = 0.4 GPH Flow  | 12 = 12" |         | 100 = 100'  |        | PC=Pressure-compensating<br>CV=Pressure-compensating with check valve<br><br>R = Reclaimed (available in 0.6 and 0.9 GPH models only) |         |
|   | HDL-06 = 0.6 GPH Flow  | 18 = 18" |         | 250 = 250'  |        |                                                                                                                                       |         |
|   | HDL-09 = 0.9 GPH Flow  | 24 = 24" |         | 500 = 500'  |        |                                                                                                                                       |         |
|   | HDL-BLNK = No Emitters |          |         | 1K = 1,000' |        |                                                                                                                                       |         |

#### Example:

HDL-09-12-250-CV = 0.9 GPH check valve dripline with 12" spacing in a 250' coil

Notes: \* 100' coils available in the following HDL models only: HDL-06-12-100-CV, HDL-09-12-100-CV, HDL-09-18-100-CV, HDL-06-12-100-PC, and HDL-09-12-10-PC

### HDL Installed

