

ICC2

This flexible control system can run any combination of conventional, EZDS two-wire, or Wireless Valve Link outputs with built-in flow monitoring and convenient, online control with Centralus™ Software.

KEY BENEFITS

- 4 independent irrigation programs (8 start times each) allow for customized scheduling
- 2 sensor inputs available for dedicated flow sensor (HFS or HC Flow) and weather sensor (Clik or Solar Sync) connections
- Backward compatibility to original ICC Controllers allows for quick updates to older systems
- Forward compatibility with HCC Controllers and Hydrowise® Software using convenient upgrade kit
- 12-hour maximum station run times provide flexibility for low-flow zones
- Any 2 programs can operate simultaneously, providing more efficient watering
- 1 P/MV output for pump start relay and master valve activation
- Compatible with EZ Decoder System two-wire and Wireless Valve Link outputs in the same installation



ELECTRICAL SPECIFICATIONS

- Transformer input: 120/230 VAC
- Transformer output (24 VAC): 1.4 A
- Station output (24 VAC): 0.56 A
- P/MV output (24 VAC): 0.56 A
- Approvals: Wall Mounts IP55, Plastic Pedestal IP24, UL, cUL, FCC, CE, UKCA, RCM, ISED
- Warranty period: 5 years

USER-INSTALLED OPTIONS

- Compatible with Hunter Flow-Sync® Sensor and HC Flow Meter for standalone flow monitoring connections

Copyright © 2025 Hunter Industries Inc. Hunter, the Hunter logo, and other marks are trademarks of Hunter Industries Inc., registered in the U.S. and certain other countries.

<https://www.hunterirrigation.com/irrigation-product/controllers/icc2>
021025