



Simple: Installs faster with optional factory-installed Pro High-Efficiency Nozzles

Efficient: Waters more efficiently with a high-uniformity spray pattern for consistent coverage

Compact: Built tough for tight spaces with a durable slim-line spray body

PS ULTRA SPRINKLER BODY WITH PRO HIGH-EFFICIENCY NOZZLE

Smarter spray performance in a slim profile

PS Ultra combines a compact, durable spray body with factory-installed Pro High-Efficiency Nozzles for high-uniformity performance, improved efficiency, and simple installation. Matched precipitation across the 8' to 17' nozzle range allows mixing and matching within the same zone.

Available in 2", 4", and 6" models, this slim sprinkler features a reliable two-piece ratcheting riser that allows spray direction adjustment without resetting the body or arc.

The male-threaded riser accepts all female nozzles for maximum field flexibility, while an optional extra-large filter screen on 4" and 6" models provides double filtration to reduce clogging in dirty or reclaimed water.

A flush plug version is available without a nozzle or filter screen. Multiple compatible nozzle options make it easy to match the sprinkler to the application.

Learn more. Visit hunterirrigation.com or contact your local Sales Manager.



hunter.info/psultra

PS ULTRA FEATURES & SPECIFICATIONS

Features

- Models: 2", 4", 6"
- Available with flush plug to clear debris quickly
- Two-piece ratcheting riser lets you fine-tune spray direction by hand without resetting the body or arc
- Male-threaded riser accepts all female nozzles for maximum flexibility in the field
- Optional extra-large filter screen reduces clogging in dirty or reclaimed water

Specifications

- Operating pressure: 20 to 70 PSI
- Recommended pressure: 30 PSI
- Radius: 8' to 17' or 5'x30' with SS-530
- Matched precipitation rate of 1.6 in/hr
- Flow rate: 0.2 to 5.3 GPM
- Warranty period: 2 years

PS ULTRA - SPECIFICATION BUILDER: ORDER 1 + 2

1 Model	2 Nozzles
PSU-02 = 2" pop-up PSU-04 = 4" pop-up PSU-06 = 6" pop-up	(blank) = Flush plug, no large filter screen 8A-HE = 8' adjustable nozzle 10A-HE = 10' adjustable nozzle 12A-HE = 12' adjustable nozzle 15A-HE = 15' adjustable nozzle 17A-HE = 17' adjustable nozzle 5SS = 5' x 30' side strip (2" and 4" only)

Examples:

PSU-02-5SS = 2" pop-up with a 5' x 30' side strip
PSU-04 = 4" pop-up with flush plug; large filter screen not included
PSU-06-10A-HE = 6" pop-up with a 10' adjustable, high-efficiency nozzle

Models



[A] PSU-02

Overall height: 5"
 Pop-up height: 2"
 Exposed diameter: 1¼"
 Inlet size: ½"

[B] PSU-04

Overall height: 7¼"
 Pop-up height: 4"
 Exposed diameter: 1¼"
 Inlet size: ½"

[C] PSU-06

Overall height: 9½"
 Pop-up height: 6"
 Exposed diameter: 1¼"
 Inlet size: ½"

DIRECTIONAL FLUSH PLUG

When ordered without a nozzle, the PS Ultra comes with a directional flush plug to prevent flooding of the head area.



Website hunterirrigation.com | Customer Support +1-800-383-4747

Helping our customers succeed is what drives us. While our passion for innovation and engineering is built into everything we do, it is our commitment to exceptional support that we hope will keep you in the Hunter family of customers for years to come.

Denise Mullikin, President, Landscape Division