

Total Prep Efflorescence/Stain Remover

720-1G, 720-55G

DESCRIPTION:

ICT Total Prep is a professional grade efflorescence and stain remover. **Total Prep** is formulated to dissolve efflorescence and remove surface stains such as ground in dirt, traffic marks, iron stains etc. It can be used on, but not limited to, concrete/brick pavers, slabs, concrete retaining walls and many other concrete surfaces. **Total Prep** is environmentally and user friendly. It contains no hydrochloric acid and works without discoloring or damaging the surface. **Total Prep cleans** and **primes** the surface evenly and enables sealers/protectors to penetrate and cover more efficiently.

FEATURES & BENEFITS:

| | |
|---|------------------------|
| Removes efflorescence and ground in dirt | Neutralizes with water |
| Prepares the surface for sealer application | Low V.O.C. |
| Easy to use and rinse | |

USE/MIXING INSTRUCTIONS:

Total Prep is highly concentrated and must be diluted based on the recommendations below. When diluting **Total Prep** **always** add product to water. **Never** add water to product. Do not mix with hot water. Used plastic containers only. It is always recommended to do a small test area to check strength and compatibility. For use on vertical surfaces, the use of a foam sprayer is recommended.

- Pavers:** 1part **Total Prep** : 4-5 parts water
- Broom Finished Concrete:** 1 part **Total Prep** : 2 parts water
- Concrete Block:** 1 part **Total Prep** : 4 parts water
- Smooth Finished Concrete:** 1 part **Total Prep** : 7 parts water

- Always pre-wet surface with fresh water. Make sure when using on vertical surfaces to work from the bottom up keeping the lower level wet to avoid streaks.
- Apply diluted **Total Prep** to surface with a masonry brush or plastic watering can.
- Allow **Total Prep** to remain on the surface for 3-5 minutes. **Do not allow to dry.**
 Rinse thoroughly with fresh water making sure all residue has been removed from the surface. Repeat as necessary.
- Pressure wash thoroughly after final use.

Safety:

Read MSDS Sheet prior to use. Protect people, vehicles, metal, paints surfaces, plants and other non-masonry material from product. Avoid breathing spray mist. All caulking and sealant materials should be in place and thoroughly cured before cleaning. Keep off of glass and anodized aluminum. As with any industrial cleaner practice safe handling and wear Personal Protective Equipment such as safety goggles, chemical proof gloves and foot wear. Keep container closed when not in use. **Keep Out of Reach of Children**

| <u>CHARACTERISTICS AND TECHNICAL DATA</u> | |
|---|---|
| <u>Liquid Properties</u> | <u>Test Results</u> |
| Weight/Gallon..... | 10.02 lbs./gal. |
| Freezing Point..... | 30°F |
| Appearance Wet..... | Green liquid |
| Coverage/Gallon..... | Up to 200 sq. ft. per gal. (depending on dilution ratio) |
| Clean Up..... | Water |
| Shelf Life..... | 1 yr min. (closed container) |



ICT Corporation
 2410 McJunkin Road * Lakeland, FL 33803
 (Nationwide): 888-296-5236 * (Local): 863-665-8787 *(Fax): 863-666-2768
 (Email): info@innovativeconcrete.com
www.innovativeconcrete.com