

# Color Seal H<sub>2</sub>O Pro

## Sealer & Protector

### USE:

*ICT Color Seal H<sub>2</sub>O Pro* is used to enhance and protect new or existing concrete surfaces. *Color Seal H<sub>2</sub>O Pro* is designed to be used over *ICT Texture Krete 2000* Surfacing System as well as keystone, cool deck and all concrete surfaces. *Color Seal H<sub>2</sub>O Pro* protects interior and exterior concrete and properly prepared asphalt. *Color Seal H<sub>2</sub>O Pro* is ideal for commercial and residential patios, pool decks, walkways, driveways, and garage floors.

### DESCRIPTION:

*ICT Color Seal H<sub>2</sub>O Pro* is a unique blend of 100% non blushing, deep penetrating, self cross linking acrylic resin. *Color Seal H<sub>2</sub>O Pro* is easy to apply, quick drying, durable, easily cleaned and environmentally friendly. *Color Seal H<sub>2</sub>O Pro* resists water and UV light damage. This makes *Color Seal H<sub>2</sub>O Pro* the professional's choice in water-based color sealers.

### FEATURES & BENEFITS:

QUICK DRYING  
DURABLE  
ENVIRONMENTALLY FRIENDLY  
SUPER ADHESION  
EXCELLENT WEATHERABILITY  
COLOR STABILITY: Resistant to UV light  
CHLORINE & SALT RESISTANT

### SURFACE PREPARATION:

To successfully install *ICT Color Seal H<sub>2</sub>O Pro*, the surface must be dry, clean, free of all algae, grease, oil, dirt and all other foreign matter. Make certain any previously applied coatings or deck systems are secure or removed prior to installation. Stripping or Sand blasting may be required. New concrete surfaces should be allowed to cure a minimum of 30 days and should be pressure washed prior to application of sealer.

**Step 1:** Removal of algae, mildew and other foreign matter may be achieved with a solution of either bleach or chlorine, (diluted 1-3 parts water). *ICT Total Klean*, all purpose cleaner and degreaser, scrub surface well, pressure clean and rinse thoroughly. Allow to dry thoroughly before applying *Color Seal H<sub>2</sub>O Pro*.

**Step 2: Etching Surface (Only when necessary):** Smooth concrete must be etched with a solution of muriatic acid (diluted with a minimum 4 parts water, 1 part acid). Never allow acid solution to dry; rinse thoroughly. It is recommended after etching to neutralize with sodium bicarbonate and to pressure wash with a minimum of 2,500 P.S.I. to insure the complete removal of chemicals and residue. *NOTE: WHILE ACID WASHING, IF BUBBLING DOES NOT OCCUR IN ALL AREAS, THEN CONTAMINANTS REMAIN ON THE CONCRETE.*

### APPLICATION:

Allow surface to dry for a minimum of 24 hours after cleaning and prior to application of *Color Seal H<sub>2</sub>O Pro*. It is important to always stir *Color Seal H<sub>2</sub>O Pro* thoroughly prior to use. *Color Seal H<sub>2</sub>O Pro* may be applied with a brush, roller (3/4" - 1" nap is recommended), or airless sprayer (.0015-.0017 tip recommended). *NOTE:* Using a roller nap greater than 1" may result in bubbling of *Color Seal H<sub>2</sub>O Pro*.

(cont'd on reverse)

### CHARACTERISTICS AND TECHNICAL DATA

<u>Liquid Properties</u>	<u>Test Results</u>
Weight/Gallon.....	10.80 lbs./gal.
% Solids.....	53% (+/-1)
Gloss @ 60°F.....	20
Freezing Point.....	30°F
Coverage/Gallon.....	Approx. 200 sq. ft. per gal.
Installation Surface Temp...	min. 50°F
Clean Up.....	Warm Soapy Water
Dry to touch.....	*30 min.
Dry to Recoat.....	*3-4 hours
Cured...	*72 hours
Shelf Life.....	1 yr min. (closed container)
V.O.C.....	less than 100 grams/liter
Liters/gallon.....	3.785 liters

\*Thickness of material, low temperature & high humidity will significantly lengthen drying time.

### ICT Corporation

2410 McJunkin Road \* Lakeland, FL 33803  
(Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768  
(Email): [info@innovativeconcrete.com](mailto:info@innovativeconcrete.com)  
[www.innovativeconcrete.com](http://www.innovativeconcrete.com)

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 12-18 months from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.