

# Stone Show H<sub>2</sub>O

## Enhancer & Protector

### USE:

**ICT Stone Show H<sub>2</sub>O** is a breathable, water-based, penetrating, water repellent designed to be used on natural stones, concrete, and other properly prepared masonry surfaces. While providing a unique and beautiful enhancement to the existing color(s) of the substrate, **Stone Show H<sub>2</sub>O** also acts as a protective shield against staining, simplifies maintenance & cleaning, and disallows deterioration of the substrate caused by water presence & contaminants carried by water.

### DESCRIPTION:

**ICT Stone Show H<sub>2</sub>O** is a clear drying water-proofer with immaculate color enhancing properties. **Stone Show H<sub>2</sub>O** has been specially formulated to be the ideal option for natural stones that must allow moisture to escape without allowing moisture the reenter through the non-film-forming barrier created by the proper installation of **Stone Show H<sub>2</sub>O**. By disallowing the penetration of moisture, **Stone Show H<sub>2</sub>O** will also help against other complications cause by the presence of water such as efflorescence, staining, spalling, and some cracking. **Stone Show H<sub>2</sub>O** does not create a film over the surface and will not make the surface any more slippery than before application of **Stone Show H<sub>2</sub>O**. **Stone Show H<sub>2</sub>O** will keep surfaces beautiful and protected through years of use.

### FEATURES & BENEFITS:

COLOR ENHANCEMENT	ONE-WAY WATER PROOFING
STAIN RESISTANCE	EASY MAINTENANCE
LOW V.O.C.	INHIBITS BIO GROWTH
EFFLORESCENCE RESISTANCE	PENETRATING
BREATHABLE	DOES NOT CREATE A FILM ON THE SURFACE

### CHARACTERISTICS AND TECHNICAL DATA

<u>Liquid Properties</u>	<u>Test Results</u>
Weight/Gallon.....	8.38 lbs./gal.
% Solids.....	15%
Gloss.....	No Gloss
Flash Point.....	212°F
Appearance Wet.....	Milky White
Appearance Dry.....	Clear/Enhanced Wet Look
Coverage/Gallon.....	60—300 sq. ft. per gal.
Clean Up.....	Warm Soapy Water
Dry to touch.....	6 hours
Return to Service.....	12 hours
Vehicular Traffic...	24—48 hours
Shelf Life.....	1 year (closed container)
V.O.C.....	< 50 grams/liter

### SURFACE PREPARATION:

1. Clean surface thoroughly with **ICT Total Klean** all purpose degreaser and cleaner to remove dirt and oils. It is recommended that you also use a bleach/liquid chlorine solution to remove any visible or microscopic algae or mildew. Rinse thoroughly.
2. If efflorescence is present, it is recommended that you use **ICT Total Prep** according to product directions. This will remove any efflorescence and condition / prepare the surface to receive **Stone Show H<sub>2</sub>O**.
3. Pressure wash the entire area thoroughly to remove any residual chemicals.
4. Allow surface to dry.

### ICT Corporation

2410 McJunkin Road \* Lakeland, FL 33803  
 (Nationwide): 888-296-5236 \* (Local): 863-665-8787 \*(Fax): 863-666-2768  
 (Email): [info@innovativeconcrete.com](mailto:info@innovativeconcrete.com)  
[www.innovativeconcrete.com](http://www.innovativeconcrete.com)

All Innovative Concrete Technology Corp. products are manufactured with the finest raw materials. Shelf life is 2 years from the date of manufacturing when maintained in protected storage of 50°F to 90°F. It is the applicator's responsibility to determine the appropriate use of the product. All recommendations and suggestions are made without warranty, express or implied, since conditions of use are beyond ICT's control. ICT Corp. disclaims any liability incurred in connection with the use of these data or suggestions.