



1K URETHANE

1 PART COLOR ENHANCING PAVER SEALER

INSECO's 1K URETHANE is a water based, single component, protective finish designed to seal and enhance the color of concrete pavers. 1K URETHANE penetrates into the surface and produces a tough, durable, clear film that will enhance the pavers color similar to its solvent based counterparts, bind the joint sand and protect against water damage, staining and UV ray damage. 1K URETHANE also provides mildew protection and tremendous resistance against wear from both foot and vehicular traffic. 1K URETHANE may be applied to damp pavers which allows for same day cleaning and sealing.

Wet Look & High Gloss

May Apply to Damp Surfaces

Seals & Protects

Enhances Color

Repels Water

RECOMMENDED USES: For properly prepared concrete and brick pavers, slate, Saltillo tiles and clay roof tiles.

SURFACE PREPARATION: Dirt, grease, grime and any foreign material must be removed before application of new coating. Treat surface for mildew. Oil and grease should be scrubbed with a solution of Oxiclean and water. Contact an INSECO representative for detailed surface preparation specifications.

DO NOT APPLY TO PAINTED SURFACES.

APPLICATION: Mix product thoroughly and apply with brush, roller or airless sprayer. When spraying, use a tip designed for gloss coatings. Apply when surface and air temperatures are above 50 Deg. F. Do not apply if the threat of rain exists or if moisture or dew may condense on the surface prior to 1K URETHANE curing. Cover and protect all vegetation and surrounding areas not being sealed. Do not over apply, soak the substrate or allow product to puddle. Two coats are recommended for best performance.

DRY TIME: Touch: 30 to 60 minutes. Recoat: 2 hours. Foot traffic: 24 hours. Vehicular traffic: 72 hours.

CLEAN UP: Clean up drips and spills immediately using a damp cloth. Clean tools and equipment with soap and fresh water.

COVERAGE (THEORETICAL): Coverage will depend on porosity and contour of the surface being coated. Coverage typically averages 200-300 square feet per gallon.

CAUTION: KEEP OUT OF REACH OF CHILDREN!

WARNING! If you scrape, sand or remove old paint, you may release lead dust. **LEAD IS TOXIC. EXPOSURE CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE.** Wear an NIOSH-approved respirator to control lead exposure. Carefully clean up with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.



HAGA CLIC AQUÍ PARA ESPAÑOL

Finish:	High-Gloss
Pigment Type:	None
Vehicle Type:	Acrylic Urethane
Solvent Type:	Water
% Solids By Weight:	50 % +/- 2%
% Solids By Volume:	48 % +/- 2%
Density:	8.55 lbs. per gallon
Viscosity @ 75 deg. F (24 deg. C):	Waterlike
Coating VOC:	<50 g/l
Flash Point, Minimum:	Not Flammable
Flame Spread:	Class A rating on non combustible substratum
Estimated Dry Time:	Touch: 30-60 Minutes Recoat: 2 Hours Foot Traffic: 24 Hours Vehicular Traffic: 72 Hours

1K URETHANE is water based. Do not Freeze.

Technical data contained here in is true and accurate at the date of issue, but is subject to change without notice. An Inseco representative should be contacted with any questions concerning product information or application procedures. Our products conform to Inseco quality standards, but no other warranty is expressed or implied. Liability, if any, is limited to the replacement of product or purchase price.



INSECO

INSECO, Inc.
2897 South Street
Fort Myers, FL 33916

insecoproducts.com
(800) 883-5150
info@insecoproducts.com