



FM1D14 Series

Electronic Time Switch

The New Face of Convenience

Grässlin by Intermatic, the undisputed leader in modular panel mount time switches, is adding the new compact FM1D14 timer to its vaunted product line. The one channel 24-hour, 7-Day timer delivers the best environmental ratings and most versatile voltage settings in its category. Add in a competitive price to the unmatched features and you have the best solution for heavy-duty commercial or industrial applications.



GRÄSSLINTM
by **INTERMATIC**[®]

Compact. Simple. Smart.

The FM1D14 timer gives you everything you need in one compact timer. Its small footprint allows you to install the panel mount timer in the most convenient spots in your facility.

Features

- 24-Hour or 7-Day applications
- 14 setpoint programs
- Easy-to-follow menu driven programming
- Manual override with status indication
- Rechargeable battery with backup protection up to 2500 hours
- 5 selectable block programs



Ideal for

- Pumps • Fans • Heaters • HVAC Control Circuits
- Lighting • Machinery • OEM Applications
- Commercial and Industrial Equipment

Ratings



Size: 2.36" x 2.36" (60 mm x 60 mm)

Power Consumption: 1.4 W

Supply Voltage: 12 VDC, 24 VAC/VDC, 120-277 VAC, 50/60 Hz

Switch Rating: SPDT relay

N.O. Contact: 15A, 277 VAC, General Use
10 FLA, 60 LRA, 250 VAC
½ HP 120 VAC
1 HP 250 VAC
1000 W, 120 VAC, Tungsten
8 A, 277 VAC, Ballast
B300 Pilot Duty
4.9 A, 120 VAC, Electronic Ballast

N.C. Contact: 15 A, 277 VAC, General Use
10 FLA, 60 LRA, 250 VAC
½ HP 120/240 VAC
12 A, 24 VDC, Resistive
8 A, 120 VAC, Ballast

Wiring Connections: ¼" quick connect terminals

Operating Temperature: -40°F to 131°F (-40°C to 55°C)
(limited display function at -13°F)

Shipping Weight: 10 lbs.

Warranty: Limited 1 year

Model Number	Voltage	Programs	Mounting
FM1D14-12	12 VDC	14	Panel
FM1D14-24*	24 VAC/VDC	14	Panel
FM1D14-AV	120-277 VAC	14	Panel

*24V model will operate on AC or DC

www.intermatic.com

© 2013 Intermatic Incorporated 7777 Winn Road Spring Grove, IL 60081
300GR10099