

# ECO™ SERIES

The strength you trust, now with ultra low voc.

- Superior joint strength
- Fast setting
- 30% lower solvent emissions
- Less odorous fumes
- Improved working environment



Breathe easier

[www.weldon.com](http://www.weldon.com)





# ECO™ SERIES

|  | Max Pipe Size                         | Set Time | Available Color  | Performance Specification   |
|--|---------------------------------------|----------|--|---|
|  | 4" (110 mm)<br>Not for Sch. 80        | Fast     | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block;">CLEAR</div>   | <br>PW-G/DWV/SW<br>U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61  |
|  | 6" (160 mm)<br>4" (110 mm)<br>Sch. 80 | Fast     | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block;">CLEAR</div><br><div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #555; color: white;">GRAY</div>      | <br>C US PW-G/DWV/SW U.P. CODE (GRAY ONLY) PW-G/DWV/SW U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61<br>CSA B137.3 CSA B181.2 |
|  | 6" (160 mm)<br>4" (110 mm)<br>Sch. 80 | Fast     | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #007bff; color: white;">BLUE</div>   | <br>PW-G/DWV/SW<br>U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61  |
|  | 6" (160 mm)<br>4" (110 mm)<br>Sch. 80 | Fast     | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #007bff; color: white;">BLUE</div>   | <br>PW-G/DWV/SW<br>U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61  |
|  | 12" (315 mm)                          | Medium   | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #555; color: white;">GRAY</div>  | <br>C US PW-G/DWV/SW U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61  |
|  | 12" (315 mm)                          | Medium   | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block;">CLEAR</div><br><div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #555; color: white;">GRAY</div>      | <br>C US PW-G/DWV/SW U.P. CODE (GRAY ONLY) PW-G/DWV/SW U.P. CODE<br>ASTM D2564<br>NSF/ANSI 14 & 61<br>CSA B137.3 CSA B181.2 |
|  | —                                     | —        | <div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block;">CLEAR</div><br><div style="border: 1px solid gray; border-radius: 5px; padding: 2px 10px; display: inline-block; background-color: #6f42c1; color: white;">PURPLE</div> | <br>C US U.P. CODE (PURPLE ONLY)<br>ASTM F656<br>NSF/ANSI 14 & 61   |