

Contractors' **CHOICE**[®]

Wire Connectors - For Conventional Dry Splices

Product Specifications

Hi-Temperature Black Nut Connector

- Max Voltage: 300V
- Wire Range: Min #22/Max #18
- Max Temp Rating: 150°C (302°F)
- Wire Type: Copper/Copper

Gray Nut Connector

- Max Voltage: 300V
- Wire Range: Min #22/Max #14
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Blue Nut Connector

- Max Voltage: 300V
- Wire Range: Min #22/Max #14
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Orange Nut Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #22/Max #14
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Yellow Nut Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #22/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Red Nut Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #22/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Not suitable for wet applications.

See reverse side for a listing
of wire combinations.

Hi-Temperature Black Nut Connector

Catalog #	Selling Unit
67061	Bag of 1,000
67065	Box of 100



Gray Nut Connector

Catalog #	Selling Unit
67011	Bag of 1,000
67015	Box of 100



Blue Nut Connector

Catalog #	Selling Unit
67021	Bag of 1,000
67025	Box of 100



Orange Nut Connector

Catalog #	Selling Unit
67031	Bag of 500
67033	Bucket of 5,000
67035	Box of 100
67039	Drum of 20,000



Yellow Nut Connector

Catalog #	Selling Unit
67041	Bag of 500
67045	Box of 100



Red Nut Connector

Catalog #	Selling Unit
67051	Bag of 500
67055	Box of 100



- UL 486C and CSA 22.2 No. 188 Certified
- Tough ThermoPlastic, UL 94 V-2
Flame Retardant Shell

KING
INNOVATION[®]

www.kinginnovation.com

(P) 800.633.0232
(F) 636.519.5410

Contractors' Choice™ Wire Connectors

Wire Connectors - For Conventional Dry Splices

Hi-Temperature Black Nut Connector - 300V Wire Combinations

Max. 2 #18
Min. 1 #18 w/1 #22

Gray Nut Connector - 300V Wire Combinations

Max. 1 #16 w/1 #18 w/1 #20
Min. 2 #22

Blue Nut Connector - 300V Wire Combinations

Max. 3 #16
Min. 2 #22

Orange Nut Connector - 300V Wire Combinations

Max. 4 #16 w/1 #20
Min. 1 #18 w/1 #20

Orange Nut Connector - 600V Wire Combinations

Max. 1 #14 w/1 #16 w/1 #18
Min. 2 #18

Yellow Nut Connector- 300V Wire Combinations

Max. 2 #12 w/2 #14
Min. 2 #14

Yellow Nut Connector- 600V Wire Combinations

Max. 3 #14
Min. 3 #20 Solid

Red Nut Connector- 300V Wire Combinations

Max. 1 #10 w/1 #12 w/4 #18
Min. 3 #16 w/1 #20 w/1 #22

Red Nut Connector- 600V Wire Combinations

Max. 2 #10 Solid w/2 #12
Min. 3 #18

Please contact factory for a complete list of wire combinations.