

Contractors' CHOICE™

Wire Connectors - For Conventional Dry Splices

Product Specifications

Yellow Wing Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #18/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Tan Wing Connector

- Max Voltage: 600V
- Wire Range: Min #22/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Red Wing Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #18/Max #8
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Green Wing Connector

- For Grounding Terminals Only
- Wire Range: Min #14/Max #10
- Wire Type: Copper/Copper

Gray Wing Connector

- Max Voltage: 600V
- Wire Range: Min #18/Max #8
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

continued on back

Not suitable for wet applications.

See reverse side for a listing
of wire combinations.

Yellow Wing Connector

Catalog #	Selling Unit
67075	Box of 100
67071	Bag of 500
67073	Bucket of 4000
67079	Drum of 35000



Tan Wing Connector

Catalog #	Selling Unit
67085	Box of 100
67081	Bag of 500
67083	Bucket of 3000
67089	Drum of 30000



Red Wing Connector

Catalog #	Selling Unit
67095	Box of 100
67091	Bag of 500
67093	Bucket of 2000
67099	Drum of 20000



Green Wing Connector

Catalog #	Selling Unit
27120	Bag of 25
27145	Box of 500
27143	Bucket of 2500
27190	Drum of 25000



Gray Wing Connector

Catalog #	Selling Unit
67105	Box of 50
67101	Bag of 250



- UL 486C and CSA 22.2 No. 188 Certified
- Tough ThermoPlastic, UL 94 V-2
Flame Retardant Shell

KING
INNOVATION®

www.kinginnovation.com
(P) 800.633.0232
(F) 636.519.5410

Product Specifications

Blue Wing Connector

- Max Voltage: 600V
- Wire Range: Min #14/Max #6
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Blue Wing Connector

Catalog #	Selling Unit
67115	Box of 50
67111	Bag of 100



Contractors' Choice™ Wire Connectors

Wire Connectors - For Conventional Dry Splices

Yellow Wing Connector - 300V Wire Combinations

Max. 3 #12

Min. 2 #16

Yellow Wing Connector - 600V Wire Combinations

Max. 3 #14

Min. 2 #18

Tan Wing Connector - 600V Wire Combinations

Max. 3 #10

Min. 3 #22

Red Wing Connector - 300V Wire Combinations

Max. 5 #12 Solid

Min. 2 #14

Red Wing Connector - 600V Wire Combinations

Max. 5 #14

Min. 3 #16

GroundGuard Green Wing Connector - Wire Combinations

Max. 2 #12

Min. 3 #14

Gray Wing Connector - 600V Wire Combinations

Max. 3 #10

Min. 3 #14 w/1 #18

Blue Wing Connector - 600V Wire Combinations

Max. 3 #8 w/1 #12

Min. 2 #10 w/1 #12

Please contact factory for a complete list of wire combinations.