



RPS™ 75 Rotors

Sets the standard for
3/4" gear-driven rotors

- ▶ Right Position Start
- ▶ Patented Reversing Mechanism – Continuous reverse and return
- ▶ Full and Part Circle Rotation – Provides a full range of adjustment from 40° to 360°
- ▶ Non-flushing Wiper Seal – Reduces leaks caused by debris trapped under seal
- ▶ 3/4" (1,9 cm) Inlet – Replaces all standard rotors
- ▶ Rubber Cover – Seals out dirt and increases durability
- ▶ Wide Selection of Nozzles – Including standard and low angle for flexibility in system design
- ▶ Includes 5 Free Check Valve Assemblies Per Box
- ▶ Universal Riser Assembly – Fits into existing Hunter® PGP® and PGP® Ultra cans
- ▶ Pressure Regulated – 45 PSI available (6" only)



EASY ARC SETTING

- Arc Selection: 40° to 360°
- Adjust from right start

INLET SIZE
3/4"

RADIUS
22' – 51'

FLOW RATE
.07 – 8.3 GPM

BEST IN THE INDUSTRY
WARRANTY
7 YEARS



RPS™ 75 Rotor Series

Real innovation is a catalyst for growth in any field. Decades ago, K-Rain® developed and patented the original reversing mechanism for continuous reverse and return still in use today. You'll find it here in the RPS75 and sprinkled across the industry, too.

Here's a benefit that will save you time on the job: The RPS™75 riser assembly fits into a PGP® and PGP® Ultra can already in the ground. How's that for optimal efficiency?

And with a wide selection of standard and low angle nozzles, the RPS™ 75 provides matched precipitation and flexibility in design.



Scan this code to learn more about free customization.

Specifications

Radius	22' – 51' (6,7 – 15,5 m)
Flow Rate	0.7 – 8.3 GPM (2,6 – 31 LPM)
Pressure Range	20 – 70 PSI (1,4 – 4,8 bar)
Precipitation Rate	.16 – 1.0 in/hr (4 – 25,4 mm/hr)
Arc Setting Range	40° – 360°
Nozzle Trajectory	26°
Low Angle Nozzle Trajectory	11°
Nozzles Included	8 Standard – 4 Low Angle
4 inch	Riser height: 4 1/4" (10,81 cm) Retracted height: 7 3/8" (18,7 cm)
6 inch	Riser height: 6 1/4" (15,9 cm) Retracted height: 9 1/2" (24,1 cm)
Shrub	Height: 7 1/2" (19,1 cm)
Inlet size	3/4" (1,9 cm) Female Thread NPT
Warranty	7 years

Includes

5 Check Valve Assemblies
8 Standard/4 Low Angle Nozzles



Watch the video. Scan this code with your smartphone camera.

Models

RPS75	RPS™ 75 Rotor
RPS75-360	RPS™ 75 Rotor, 360°
RPS75-SH	RPS™ 75 Rotor, Shrub
RPS75-360-SH	RPS™ 75 Rotor, 360°, Shrub
RPS75-6INCH	RPS™ 75 Rotor 6" (15,2 cm)

How to Specify

MODELS	OPTIONS
RPS75	-SS ▶ Stainless Steel
RPS75-360	-CV ▶ Check valve
RPS75-SH	-NN ▶ No nozzle
RPS75-360-SH	-RCW ▶ Reclaimed water use
RPS75-6inch	-PR ▶ Pressure Regulation

Examples: RPS75-SS, RPS75-360-RCW