

1. PRODUCT & COMPANY IDENTIFICATION

1.1	Product Name:	Hand Sanitizer Antiseptic Foam
1.2	Chemical Name:	Aerosol Foam Hand Sanitizer 62% v/v Alcohol
1.3	Synonyms:	PAYA® Hand Sanitizer Antiseptic Foam
1.4	Trade Names:	Aerosol Foam Hand Sanitizer
1.5	Product Uses/ Restrictions:	Professional and Cosmetic Use
1.6	Manufacturer's Name:	Piedmont LLC
1.7	- Manufacturer's Address:	2030 Old Candler Rd, Gainesville, GA 30507
1.8	Emergency Phone:	CHEMTEL: +1 (800) 424-9300 / +1 (703) 527-3887
1.9	Business Phone / Fax:	+1 (574) 295-0000 / +1 (574) 296-1709

2. HAZARDS IDENTIFICATION

2.1	Hazard Identification:	<p>This product is classified as a HAZARDOUS SUBSTANCE and as DANGEROUS GOODS according to the classification criteria of NOHSC: 1088 (2004) and ADG Code (Australia)</p> <p>WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED. HIGHLY FLAMMABLE LIQUID AND VAPOR. CAUSES EYE IRRITATION.</p> <p><u>Classification:</u> Level 1 Aerosol; Category 2 Flammable Aerosol</p> <p><u>Hazard Statements (H):</u> H-223– Flammable Aerosol. H229–Pressurized container: may burst if heated. H320 – Causes eye irritation.</p> <p><u>Precautionary Statement (P):</u></p> <p>P210 – Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No Smoking.</p> <p>P211 – Do not spray on an open flame or other ignition source.</p> <p>P251 – Do not pierce or burn, even after use.</p> <p>P261 – avoid breathing vapors/spray.</p> <p>P271 – Use only in well-ventilated area.</p> <p>P304+P340 – IF INHALED; Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+338 – IF INEYES; Rinse cautiously with water for several minutes. Remove contact lenses, if present, continue rinsing.</p> <p>P337+P313 – If eye irritation persists: Get medical advice/attention.</p> <p>P410+P412 – Protect from sunlight. Do no expose to temperature exceeding 48°C (120 °F).</p> <p>P501 – Dispose of contents/container to licensed and permitted disposal or recycling facility.</p>	
-----	------------------------	--	---

3. COMPOSITION & INGREDIENT INFORMATION

Substance / Chemical Name(s)	CAS No.	EINECS No.	%	Other
DIFLUOROETHANE (R-152a)	75-37-6	200-866-1	0.1 – 5%	Flam. Gas 1; H220
Isobutane	75-28-5	200-857-2	0.1 – 5 %	Flam. Gas 1; H220
Ethanol (SD Alcohol 40B)	64-17-5	200-578-6	50 – 70 %	Flam. Liq. 2; H225

4. FIRST AID MEASURES

4.1	First Aid:	<u>Ingestion:</u>	If ingested, do not induce vomiting! If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give water or milk to an unconscious person. Contact the nearest Poison Control Center or local emergency number. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed.
		<u>Skin:</u>	If irritation occurs & product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with plenty of soap and water. Remove contaminated clothing and wash thoroughly before reuse. If irritation, redness or swelling persists, consult a physician immediately.
		<u>Eyes:</u>	If product get in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. Raise and lower eyelid(s) while flushing to ensure thorough irrigation. If problems persist seek immediate medical attention.
		<u>Inhalation:</u>	Remove victim to fresh air and keep comfortable for breathing.
4.2	Effects of Exposure:	<u>Ingestion:</u>	If product is swallowed, may cause nausea, vomiting and/or diarrhea and central nervous system depression.
		<u>Skin:</u>	May be irritating to skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals upon prolonged or repeated exposure.
		<u>Eyes:</u>	Moderately irritating to the eyes.

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-1-2020

		<u>Inhalation:</u>	Vapors of this product may be moderately irritating to the nose, throat and other tissues of the respiratory system. Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing. Inhalation of concentrated vapors can cause nervous system depression (e.g., drowsiness, dizziness, headaches, nausea).		
4.3	Symptoms of Overexposure	<u>Ingestion:</u>	May cause nausea, vomiting and/or diarrhea and central nervous system depression.		
		<u>Skin:</u>	Prolonged contact with skin may result in bleaching and irritation of skin. The product can cause allergic skin reactions (e.g., rashes, welts, dermatitis) in some sensitive individuals. Symptoms of skin overexposure may include redness, itching, and irritation of affected areas.		
		<u>Eyes:</u>	Overexposure in eyes, may cause redness, itching and watering (risk of serious damage to eyes) Contact may cause mild eye irritation including stinging, watering and redness.		
		<u>Inhalation:</u>	Symptoms of overexposure can include coughing, wheezing, nasal congestion, and difficulty breathing.		
4.4	Acute Health Effects:	Moderate irritation to eyes and skin near affected areas. Additionally, high concentrations of vapors can cause drowsiness, dizziness, headaches and nausea.			
4.5	Chronic Health Effects:	No harmful or chronic health effects are expected to occur from a single accidental ingestion. These ingredients may be irritating to skin and mucous membrane of the eye and respiratory system. Overexposure may trigger asthma-like symptoms in some sensitive individuals. May also induce skin sensitization and respiratory hypersensitivity. Possible allergic dermatitis.			
4.6	Target Organs:	Eyes, skin, respiratory system.			
4.7	Medical Conditions Aggravated by Exposure	Acute health hazards may be delayed. Most common symptoms include irritating properties to eyes, respiratory system and skin. Existing dermatological conditions (such as eczema) and respiratory conditions (such as bronchial asthma and/or bronchitis) may be exacerbated.	HEALTH	1	
			FLAMMABILITY	3	
			PHYSICAL HAZARDS	0	
			PROTECTIVE EQUIPMENT		B
			EYES	SK IN	

5. FIREFIGHTING MEASURES

5.1	Fire and Explosion Hazards:	Level 1 Aerosol (NFPA 30B). Aerosols may burst at temperatures above 120° F (48°C). Cool uninvolved containers to prevent possible bursting. Aerosols may be projectile hazards when bursting. If aerosols are bursting, stay clear until bursting is complete. Containers may rupture and release flammable liquids and/or exposed gases if exposed to the heat of fire. Keep containers cool by spraying them with water until the fire has been extinguished.	
5.2	Extinguishing Methods:	Water Fog, Foam, CO ₂ , Dry Chemical	
5.3	Firefighting Procedures:	As in any fire, wear MSHA/NIOSH approved self-contained breathing apparatus (pressure-demand_ and full protective gear. Keep containers cool until well after the fire is out. Use water spray to cool fire-exposed surfaces and to protect personnel. Fight fire upwind. Prevent runoff from fire control or dilution from entering sewers, drains, drinking water supply, or any natural waterway. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.	

6. ACCIDENTAL RELEASE MEASURES

6.1	Spills:	<p>Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate Personal Protective Equipment (PPE).</p> <p><u>Small spills</u> Wear appropriate personal protective equipment including gloves and protective eyewear. Use a non-combustible material such as vermiculite or sand to soak up the product and place into a container for later disposal. Do not use water or a material such as "speedy dry" to soak up material. Sweep up material using non-sparking materials (e.g., plastic brooms, shovels, dustpans) and place into a plastic container or plastic liner within another container.</p> <p><u>Large spills:</u> Keep incompatible materials (e.g., organics such as oil) away from spill. Stay upwind and away from spill or release. Isolate immediate hazard area and keep unauthorized personnel out of area. Stop spill or release if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant.</p>
-----	---------	--

7. HANDLING AND STORAGE INFORMATION

7.1	Work & Hygiene Practices	Do not eat, drink, or smoke while handling this product. Contents under pressure. Handle as to avoid puncturing container(s). When used as intended, no additional protective equipment is necessary. Use chemical goggles if eye contact is possible. Wash unintentional residues with soap and warm water.
-----	--------------------------	--

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-1-2020

7.2	Storage and Handling:	Use and store in a cool, dry, well-ventilated location (e.g., local exhaust ventilation, fans) away from heat and direct sunlight. Avoid temperatures above 120 °F (48°C). Keep away from incompatible substances. Protect containers from physical damage. To avoid unintentional spraying, keep cap in place when not in use. Storage level 1.
7.3	Special Precautions:	Spilled material may present a slipping hazard if left unattended. Clean all spills promptly.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1	Exposure Limits: Ppm (mg/m ³)		ACGIH		NOHSC			OSHA			OTHER
		Chemical Name(s)	TLV	STEL	ES-TWA	ES-STEL	ES-PEAK	PEL	STEL	IDLH	
		Ethanol (SD Alcohol 40B)	1000	3000	1000	1800	NF	1000	1900	3300	
		DIFLUOROETHANE (R-152a)	1000	NA	1000	NA	NA	NE	NA	NA	
		Isobutane	600	750	NF	NF	NA	NA	NA		
8.2	Ventilation & Engineering Controls	General mechanical (e.g., fans) or natural ventilation is sufficient when this product is in use. Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product.									
8.3	Respiratory Protection:	No special respiratory protection is required under typical circumstances of use or handling. In instances where dusts of this product are generated, and respiratory protection is needed, use only protection authorized by 29 CFR §1910.134, applicable U.S. State regulations, or the Canadian CAS Standard Z94.4-93 and applicable standards of Canadian Provinces, EC member States, or Australia.									
8.4	Eye Protection:	None required under normal conditions of use. Avoid eye contact. Safety glasses should be used when handling or using large quantities of this product (e.g., ≥ 1 gallon (3.8 L)).									
8.5	Hand Protection:	None required under normal conditions of use. However, may cause skin irritation in some sensitive individuals. When handling large quantities (e.g., ≥ 1 gallon (3.8 L)), wear rubber, nitrile or impervious plastic gloves.									
8.6	Body Protection:	No apron required when handling small quantities. When handling large quantities (e.g., ≥ 5 lbs.), eye wash station and deluge showers should be available. Upon completion of work activities involving large quantities of this product, wash any exposed areas thoroughly with soap and water.									

9. PHYSICAL & CHEMICAL PROPERTIES

9.1	Appearance:	Aerosol, Foam/Mousse
9.2	Odor:	Fresh Clean odor
9.3	Odor Threshold	NA
9.4	pH:	NA
9.5	Melting/Freezing Point	NA
9.6	Initial Boiling Point/ Boiling Range:	NA
9.7	Flashpoint:	-30 °F (-34 °C) TCC for propellant only; 35.6 °F (2 °C) EPA method 1010 Concentrate only
9.8	Upper/Lower Flammability limits	NA
9.9	Vapor Pressure:	@ 20 °C (68° F) – Can pressure not to exceed 180 psig @ 55 °C (131 °F) 12.4 bar
9.10	Vapor Density	>1
9.11	Relative Density:	0.85 – 0.95
9.12	Solubility:	Soluble
9.13	Partition Coefficient (log P _{ow}):	NA
9.14	Autoignition Temperature:	NA
9.15	Decomposition Temperature.	NA
9.16	Viscosity:	Aerosol at ambient temperature
9.17	Other Information:	Evaporation Rate >1

10. STABILITY & REACTIVITY

10.1	Stability:	Stable at normal temperatures.
10.2	Hazardous Decomposition Products:	Oxides of carbon (CO, CO ₂) and sulfur (SO ₂)
10.3	Hazardous Polymerization:	Will not occur.
10.4	Conditions to Avoid	Excessive heat, direct sunlight, flames, heat sources and incompatible substances.
10.5	Incompatible Substances	Mixture with strong acids, alkalis or oxidizers.

11. TOXICOLOGICAL INFORMATION

11.1	Routes of Entry:	Inhalation: YES	Absorption: YES	Ingestion: YES
11.2	Toxicity Data:	This product was not tested on animals.		
11.3	Acute Toxicity:	See Section 4.4		
11.4	Chronic Toxicity:	See Section 4.5		
11.5	Suspected Carcinogen:	NA		
11.6	Reproductive Toxicity:	This product is not reported to cause reproductive toxicity in humans.		
	Mutagenicity:	This product is not reported to produce mutagenic effects in humans.		
	Embryotoxicity:	This product is not reported to produce embryotoxic effects in humans.		
	Teratogenicity:	This product is not report to cause teratogenic effects in humans.		
	Reproductive Toxicity:	This product is not report to cause reproductive effects in humans.		
11.7	Irritancy of Product:	See Section 4.3		
11.8	Biological Exposure Indices:	NA		
11.9	Physician Recommendations:	Treat symptomatically.		

12. ECOLOGICAL INFORMATION

12.1	Environmental Stability:	There is no specific data available for this product.
12.2	Effects on Plants & Animals	There is no specific data available for this product.
12.3	Effects on Aquatic Life:	The product itself has not been tested as a whole. There is no specific data available for this product.

13. DISPOSAL CONSIDERATIONS

13.1	Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state and federal laws and regulations. Contact the appropriate agency for specific information. A licensed facility or waste hauler must provide treatment, transport, storage and disposal of hazardous waste.
13.2	Special Considerations:	U.S. EPA Hazardous Waste – Characteristic – Ignitable (D001)

14. TRANSPORTATION INFORMATION

14.1	49 CFR (GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or CONSUMER COMMODITY, ORM-D (IP VOL ≤ 1.0 L) – until 12/31/2020	
14.2	IATA (AIR)	UN1950, AEROSOLS, FLAMMABLE, 2.1 (LTD QTY, IP VOL ≤ 0.5 L); or ID8000, CONSUMER COMMODITY, ORM-D (IP VOL ≤ 0.5 L)	
14.3	IMDG (OCN):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.4	TDGR (Canadian GND):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L); or MARK PACKAGE "LIMITED QUANTITY", "LTD QTY", OR "QUANT LTÉE" OR "QUANTITÉ LIMITÉE"	
14.5	ADR/RID (EU):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	
14.6	SCT (MEXICO):	UN1950, AEROSOLS, 2.1 (CANTIDAD LIMITADA, IP VOL ≤ 1.0 L)	
14.7	ADGR (AUS):	UN1950, AEROSOLS, 2.1 (LTD QTY, IP VOL ≤ 1.0 L)	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards SDS Revision: 1.0 SDS Revision Date: 4-1-2020

15. REGULATORY INFORMATION

15.1	SARA Reporting Requirements:	This product does not contain any substance subject to SATA Title III, section 313 reporting requirements.	
15.2	SARA Threshold Planning Quantity:	There are no specific Threshold Planning Quantities for the components of this product.	
15.3	TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.	
15.4	CERCLA Reportable Quantity (RQ):	Ethanol: 2270 kg; 5000 lbs	
15.5	Other Federal Requirements:	This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR Subchapter G. (Cosmetics)	
15.6	Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of the product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substance List. WHMIS Class B5 (Flammable Aerosol)	
15.7	State Regulatory Information:	<u>Ethanol</u> : is found on the following state criteria lists FL, MA, MN, NJ, PA, and WA <u>Isobutane</u> can be found on the following state criteria lists: MA, NJ, and PA. Difluoroethane can be found on the following state criteria lists: MA and NJ No other ingredients of this product, present in a concentration of 1.0% or greater, are listed on any of the following state criteria lists: California Proposition 65 (CA65), Delaware Air Quality Management List (DE), Florida Toxic Substances List (FL), Massachusetts Hazardous Substances List (MA), Michigan Critical Substances List (MI), Minnesota Hazardous Substances List (MN), New Jersey Right-to-Know List (NJ), New York Hazardous Substances List (NY), Pennsylvania Right-to-Know List (PA), Washington Permissible Exposures List (WA), Wisconsin Hazardous Substances List (WI).	
15.8	Other Requirements:	The primary components of this product are listed in Annex I of EU Directive 67/548/EEC: <u>Isobutane</u> : Flammable (F+). <u>Risk Phrases</u> (R): 12 – Highly Flammable. <u>Safety Phrases</u> (S): 2-9-16 – Keep out of reach of children. Keep container in a well-ventilated place. Keep away from sources of ignition – No smoking. <u>Ethanol</u> : Flammable (F). Risk Phrases (R): 11 – Flammable. Safety Phrase (S): 2-7-16 – Keep out of reach of children. Keep container tightly closed. Keep away from sources of ignition – No smoking	 

16. OTHER INFORMATION

16.1	Other Information:	<p>WARNING! FLAMMABLE AEROSOL. PRESSURIZED CONTAINER: MAY BURST IF HEATED, HIGHLY FLAMMABLE LIQUID AND VAPORS. CAUSES EYE IRRITATION. Keep away from heat, hot surfaces, sparks open flames and other ignition sources. No Smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing vapor/spray. Wash thoroughly with soap and water after handling. Use only in a well ventilated area. Wear eye protection. Protect from sunlight. Do not expose to temperature exceeding 48°C (120°F). IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. KEEP PRODUCT LOCKED-UP AND OUT OF REACH OF CHILDREN.</p>	
16.2	Terms & Definitions:	See last page of this Safety Data Sheet.	
16.3	Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the base of KIK Custom Product's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or complete-ness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.	
16.4	Prepared By:	KIK Custom Products 2730 Middlebury Road Elkhart, Indiana 46515 USA http://www.kikcorp.com	

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4-1-2020



Flammable



Explosive



Oxidizer



Pressurized



Corrosive



Toxic



Harmful/Irritating



Health Hazard



Environment



Face Shield and Protective Eyewear



Apron



Dust Mask



Scuba



Protective Clothing



Full Suit



Boots



Safety Glasses



Gloves

Prepared to OSHA, ACC, ANSI, NOHSC, WHMIS, 2001/58 & 1272/2008/EC Standards

SDS Revision: 1.0

SDS Revision Date: 4-1-2020



Full Face Respirator



Reactive



Irritant / Harmful



Biohazard



Oxidizing



Flammable



Infectious



Corrosive



Compressed



Toxic



Irritation