

RADIANT CUSTOM DELUXE WINTER COVERS



**DESIGNED EXCLUSIVELY
FOR METRIC SERIES POOLS!**



Finally, a winter cover designed exclusively to fit into both the 2" standard and 4" premium coping of Radiant Metric Series Pools! The custom fit provides perfect coverage for winterizing your Radiant Metric Series Pool.


This deluxe winter cover is the ultimate in tear and puncture resistance strength! Made from Tough Triple-laminated NO-RIP polyethylene fabric & Triple edge reinforced perimeter, this swimming pool winter cover is 30% lighter than other winter covers, yet is 40% stronger than any other swimming pool winter cover!

**This incredible winter cover comes
with a 10 year prorated Warranty
with the first 2 years FULL!**



If your cover should experience a puncture, this tough cover will not rip, fray or come apart!


2" Coping



**Custom designed to
snap into the Metric
pool's patented dual
bead receiver coping!**



4" Coping



**WHEN IT COMES TIME TO WINTERIZE
YOUR RADIANT METRIC SERIES POOL,
WE'VE GOT YOU COVERED!**





WINTERIZING YOUR METRIC POOL

Your Radiant Metric Series pool is to be winterized in the same manner as other pools. With a Metric Series pool there are some specific steps you should follow:

1. Make sure all ladders, pool cleaners, toys, floats are out of the water and stored.
2. Make sure the water is clean, balanced, free of algae, and winter chemicals are added.
3. Water is generally lowered to just below the skimmer to ease the plugging and draining of the hoses, pipes and skimmer.
4. Return Inlet: Remove directional (eyeball) and insert winterizing plug from the inside of the pool. We recommend a #10 rubber plug or a Hayward SP1022C plug.
5. Make sure the filter and pump pipes, hoses are drained of water. Please follow pump and filter manufacturers specific instructions for winterizing.
6. Skimmer: Remove basket and weir. Insert Gizzmo or styrofoam and/or winterizing plate to prevent ice from forming a solid block that could damage your skimmer. If using a gizzmo, the standard size is recommended for aboveground skimmers. For inground skimmers, the super Gizzmo will work best.
7. To winterize the Radiant LED light in your Metric pool, it is our recommendation that you the remove lens cap from light to prevent ice from catching and causing damage.
8. Install aboveground winter cover by inserting beading on cover into bead track of your Metric coping. The cover bead track on the standard 2" coping is located on the exterior of the pool. The cover bead on the 4" coping is located on the interior of the pool, above the liner track. Excess cover material should be inside the pool and resting on the water. Add a little water on the cover in windy areas to hold the cover down. No air pillow or flotation is required in the middle of the pool.
9. Check the level of the water under the cover after about one week, a good test for a slow leak in your liner.

For some of the specific "how to's" it may be necessary to contact your local pool professional.

If you have any questions about specific instructions for winterizing your Metric Pool, contact our offices Monday - Friday, 8AM to 5PM eastern time via phone or fax and by e-mail at info@radiantpools.com.



www.radiantpools.com