



# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Date of Issue: 07/06/2020

Version: 1.0

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** SPECTRALOCK® PRO Premium Translucent Grout Part A

### 1.2. Intended Use of the Product

Grout.

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

LATICRETE International

1 Laticrete Park, N

Bethany, CT 06524

T (203)-393-0010

[www.laticrete.com](http://www.laticrete.com)

#### Company

LATICRETE Canada ULC

PO Box 129, Emeryville, Ontario, Canada

N0R-1A0

(833)-254-9255

### 1.4. Emergency Telephone Number

**Emergency Number** : For Chemical Emergency call ChemTel Inc. day or night:

(800)255-3924 (North America)

(800)-099-0731 (Mexico)

+1 (813)248-0585 (International - collect calls accepted)

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### GHS-US/CA Classification

Flam. Liq. 4 H227

Acute Tox. 4 (Oral) H302

Acute Tox. 4 H332

(Inhalation:dust,mist)

Skin Corr. 1B H314

Eye Dam. 1 H318

Skin Sens. 1 H317

Muta. 1B H340

Carc. 1B H350

Repr. 1B H360

Asp. Tox. 1 H304

Aquatic Acute 2 H401

Aquatic Chronic 2 H411

Full text of hazard classes and H-statements : see section 16

### 2.2. Label Elements

#### GHS-US/CA Labeling

#### Hazard Pictograms (GHS-US/CA)

:



GHS05



GHS07



GHS08



GHS09

#### Signal Word (GHS-US/CA)

: Danger

#### Hazard Statements (GHS-US/CA)

: H227 - Combustible liquid.

H302+H332 - Harmful if swallowed or if inhaled.

H304 - May be fatal if swallowed and enters airways.

H314 - Causes severe skin burns and eye damage.

H317 - May cause an allergic skin reaction.

H318 - Causes serious eye damage.

H340 - May cause genetic defects.

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

H350 - May cause cancer.  
H360 - May damage fertility or the unborn child.  
H401 - Toxic to aquatic life.  
H411 - Toxic to aquatic life with long lasting effects.

**Precautionary Statements (GHS-US/CA) :** P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P260 - Do not breathe mist, spray, vapors.  
P264 - Wash hands, forearms, and other exposed areas thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P271 - Use only outdoors or in a well-ventilated area.  
P272 - Contaminated work clothing should not be allowed out of the workplace.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves, protective clothing, and eye protection.  
P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.  
P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.  
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313 - If exposed or concerned: Get medical advice/attention.  
P310 - Immediately call a POISON CENTER or doctor.  
P321 - Specific treatment (see section 4 on this SDS).  
P330 - Rinse mouth.  
P331 - Do NOT induce vomiting.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P370+P378 - In case of fire: Use appropriate media (see section 5) to extinguish.  
P391 - Collect spillage.  
P403 - Store in a well-ventilated place.  
P405 - Store locked up.  
P501 - Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

### 2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

### 2.4. Unknown Acute Toxicity (GHS-US/CA)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product Identifier	% *	GHS Ingredient Classification
Benzyl alcohol	(CAS-No.) 100-51-6	16 - 33	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Inhalation:dust,mist), H332 Eye Irrit. 2A, H319 Aquatic Acute 2, H401
Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products	(CAS-No.) 68609-08-5	13 - 26	Aquatic Acute 2, H401

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

with bisphenol A diglycidyl ether homopolymer			
Phenol, 4-nonyl-, branched	(CAS-No.) 84852-15-3	12 - 21	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Repr. 2, H361 Aquatic Acute 1, H400 Aquatic Chronic 1, H410
1-Piperazineethanamine	(CAS-No.) 140-31-8	12 - 21	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Trimethylhexamethylenediamine	(CAS-No.) 25620-58-0	7 - 16	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)- .omega.-(2-aminomethylethoxy)-	(CAS-No.) 9046-10-0	7 - 16	Skin Corr. 1C, H314 Eye Dam. 1, H318 Asp. Tox. 1, H304 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Cyclohexanemethanamine, 5-amino- 1,3,3-trimethyl-	(CAS-No.) 2855-13-2	3 - 7	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Urea, N,N'-bis[3-( dimethylamino)propyl]-	(CAS-No.) 52338-87-1	1 - 5	Skin Irrit. 2, H315 Eye Irrit. 2A, H319
Ethanol, 2-[(2-aminoethyl)amino]-	(CAS-No.) 111-41-1	< 1	Acute Tox. 4 (Oral), H302 Skin Corr. 1B, H314 Skin Sens. 1, H317 Repr. 1B, H360 STOT SE 3, H335 Aquatic Acute 3, H402 Aquatic Chronic 3, H412
Stoddard solvent	(CAS-No.) 8052-41-3	0.5 - 0.6	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Propylene glycol monomethyl ether acetate	(CAS-No.) 108-65-6	0.09 - 0.1	Flam. Liq. 3, H226 STOT SE 3, H336
Isopropylbenzene	(CAS-No.) 98-82-8	0.01 - 0.02	Flam. Liq. 3, H226

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

			Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Acute 2, H401 Aquatic Chronic 2, H411
--	--	--	---

Full text of H-phrases: see section 16

\*Percentages are listed in weight by weight percentage (w/w%) for liquid and solid ingredients. Gas ingredients are listed in volume by volume percentage (v/v%).

\*\* The actual concentration of ingredient(s) is withheld as a trade secret in accordance with the Hazardous Products Regulations (HPR) SOR/2015-17 and 29 CFR 1910.1200.

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First-aid Measures

**General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**Inhalation:** Remove to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention. Immediately call a poison center or doctor/physician.

**Skin Contact:** Immediately remove contaminated clothing. Immediately flush skin with plenty of water for at least 30 minutes. Get immediate medical advice/attention.

**Eye Contact:** Immediately rinse with water for at least 30 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice/attention.

**Ingestion:** Obtain emergency medical attention. Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most Important Symptoms and Effects Both Acute and Delayed

**General:** May cause cancer. Skin sensitization. May cause genetic defects. May damage fertility. May damage the unborn child. Harmful if swallowed. Harmful if inhaled. Causes severe skin burns and eye damage. May be fatal if swallowed and enters airways.

**Inhalation:** Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

**Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. May damage fertility or the unborn child.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention. If medical advice is needed, have product container or label at hand.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>). Water may be ineffective but water should be used to keep fire-exposed container cool.

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. A heavy water stream may spread burning liquid.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Combustible liquid.

**Explosion Hazard:** May form flammable or explosive vapor-air mixture.

**Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction. Prolonged storage: may form peroxides.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: Evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

**Hazardous Combustion Products:** Carbon oxides (CO, CO<sub>2</sub>). Nitrous fumes. Unidentified hydrocarbons. Nitrogen oxides. Silica compounds.

**Other Information:** Do not allow run-off from fire fighting to enter drains or water courses.

### 5.4. Reference to Other Sections

Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Do not get in eyes, on skin, or on clothing. Do not breathe vapor, mist or spray. Keep away from heat, hot surfaces, sparks, open flames, and other ignition sources. No smoking. Use special care to avoid static electric charges.

#### 6.1.1. For Non-Emergency Personnel

**Protective Equipment:** Use appropriate personal protective equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Stop leak if safe to do so.

#### 6.1.2. For Emergency Personnel

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Upon arrival at the scene, a first responder is expected to recognize the presence of dangerous goods, protect oneself and the public, secure the area, and call for the assistance of trained personnel as soon as conditions permit.

Ventilate area. Eliminate ignition sources.

### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment. Collect spillage.

### 6.3. Methods and Materials for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. As an immediate precautionary measure, isolate spill or leak area in all directions. Ventilate area.

**Methods for Cleaning Up:** Clean up spills immediately and dispose of waste safely. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill. Absorb and/or contain spill with inert material. Do not take up in combustible material such as: saw dust or cellulosic material. Use only non-sparking tools. Cautiously neutralize spilled liquid.

### 6.4. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Additional Hazards When Processed:** Handle empty containers with care because residual vapors are flammable. May release corrosive vapors.

**Precautions for Safe Handling:** Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Do not handle until all safety precautions have been read and understood. Do not breathe mist, spray, vapors. Take precautionary measures against static discharge. Use only non-sparking tools. Obtain special instructions before use. Do not get in eyes, on skin, or on clothing. Handle empty containers with care because they may still present a hazard. Use only outdoors or in a well-ventilated area.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Take action to prevent static discharges. Ground and bond container and receiving equipment. Use explosion-proof electrical, ventilating, and lighting equipment.

**Storage Conditions:** Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Store locked up/in a secure area. Store in a well-ventilated place. Keep container tightly closed. Keep in fireproof place. Store in original container or corrosive resistant and/or lined container.

**Incompatible Materials:** Oxidizing agent. Acids. Amines. alcohols, ketones, aldehydes, hydrocarbons.

### 7.3. Specific End Use(s)

Grout.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), OSHA (PEL), or Canadian provincial governments.

**Benzyl alcohol (100-51-6)**

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>USA AIHA</b>	<b>WEEL TWA (ppm)</b>	<b>10 ppm</b>
<b>Isopropylbenzene (98-82-8)</b>		
<b>USA ACGIH</b>	<b>ACGIH TWA (ppm)</b>	<b>50 ppm</b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (mg/m³)</b>	<b>245 mg/m³</b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (ppm)</b>	<b>50 ppm</b>
<b>USA OSHA</b>	<b>Limit value category (OSHA)</b>	<b>prevent or reduce skin absorption</b>
<b>USA NIOSH</b>	<b>NIOSH REL (TWA) (mg/m³)</b>	<b>245 mg/m³</b>
<b>USA NIOSH</b>	<b>NIOSH REL (TWA) (ppm)</b>	<b>50 ppm</b>
<b>USA IDLH</b>	<b>US IDLH (ppm)</b>	<b>900 ppm (10% LEL)</b>
<b>Alberta</b>	<b>OEL TWA (mg/m³)</b>	<b>246 mg/m³</b>
<b>Alberta</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>British Columbia</b>	<b>OEL STEL (ppm)</b>	<b>75 ppm</b>
<b>British Columbia</b>	<b>OEL TWA (ppm)</b>	<b>25 ppm</b>
<b>Manitoba</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>New Brunswick</b>	<b>OEL TWA (mg/m³)</b>	<b>246 mg/m³</b>
<b>New Brunswick</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Newfoundland &amp; Labrador</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Nova Scotia</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Nunavut</b>	<b>OEL STEL (ppm)</b>	<b>74 ppm</b>
<b>Nunavut</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Northwest Territories</b>	<b>OEL STEL (ppm)</b>	<b>74 ppm</b>
<b>Northwest Territories</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Ontario</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Prince Edward Island</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Québec</b>	<b>VEMP (mg/m³)</b>	<b>246 mg/m³</b>
<b>Québec</b>	<b>VEMP (ppm)</b>	<b>50 ppm</b>
<b>Saskatchewan</b>	<b>OEL STEL (ppm)</b>	<b>74 ppm</b>
<b>Saskatchewan</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Yukon</b>	<b>OEL STEL (mg/m³)</b>	<b>365 mg/m³</b>
<b>Yukon</b>	<b>OEL STEL (ppm)</b>	<b>75 ppm</b>
<b>Yukon</b>	<b>OEL TWA (mg/m³)</b>	<b>245 mg/m³</b>
<b>Yukon</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>		
<b>USA AIHA</b>	<b>WEEL TWA (ppm)</b>	<b>50 ppm</b>
<b>British Columbia</b>	<b>OEL STEL (ppm)</b>	<b>75 ppm</b>
<b>British Columbia</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Ontario</b>	<b>OEL TWA (mg/m³)</b>	<b>270 mg/m³</b>
<b>Ontario</b>	<b>OEL TWA (ppm)</b>	<b>50 ppm</b>
<b>Stoddard solvent (8052-41-3)</b>		
<b>USA ACGIH</b>	<b>ACGIH TWA (ppm)</b>	<b>100 ppm</b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (mg/m³)</b>	<b>2900 mg/m³</b>
<b>USA OSHA</b>	<b>OSHA PEL (TWA) (ppm)</b>	<b>500 ppm</b>
<b>USA NIOSH</b>	<b>NIOSH REL (TWA) (mg/m³)</b>	<b>350 mg/m³</b>
<b>USA NIOSH</b>	<b>NIOSH REL (ceiling) (mg/m³)</b>	<b>1800 mg/m³</b>
<b>USA IDLH</b>	<b>US IDLH (mg/m³)</b>	<b>20000 mg/m³</b>
<b>Alberta</b>	<b>OEL TWA (mg/m³)</b>	<b>572 mg/m³</b>
<b>Alberta</b>	<b>OEL TWA (ppm)</b>	<b>100 ppm</b>
<b>British Columbia</b>	<b>OEL STEL (mg/m³)</b>	<b>580 mg/m³</b>
<b>British Columbia</b>	<b>OEL TWA (mg/m³)</b>	<b>290 mg/m³</b>
<b>Manitoba</b>	<b>OEL TWA (ppm)</b>	<b>100 ppm</b>
<b>New Brunswick</b>	<b>OEL TWA (mg/m³)</b>	<b>525 mg/m³</b>

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

New Brunswick	OEL TWA (ppm)	100 ppm
Newfoundland & Labrador	OEL TWA (ppm)	100 ppm
Nova Scotia	OEL TWA (ppm)	100 ppm
Nunavut	OEL STEL (ppm)	125 ppm
Nunavut	OEL TWA (ppm)	100 ppm
Northwest Territories	OEL STEL (ppm)	125 ppm
Northwest Territories	OEL TWA (ppm)	100 ppm
Ontario	OEL TWA (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup> (140°C Flash aliphatic solvent)
Prince Edward Island	OEL TWA (ppm)	100 ppm
Québec	VEMP (mg/m <sup>3</sup> )	525 mg/m <sup>3</sup>
Québec	VEMP (ppm)	100 ppm
Saskatchewan	OEL STEL (ppm)	125 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm
Yukon	OEL STEL (mg/m <sup>3</sup> )	720 mg/m <sup>3</sup>
Yukon	OEL STEL (ppm)	150 ppm
Yukon	OEL TWA (mg/m <sup>3</sup> )	575 mg/m <sup>3</sup>
Yukon	OEL TWA (ppm)	100 ppm

### 8.2. Exposure Controls

**Appropriate Engineering Controls:** Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases or vapors may be released. Proper grounding procedures to avoid static electricity should be followed. Use explosion-proof equipment. Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

**Personal Protective Equipment:** Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection. Face shield.



**Materials for Protective Clothing:** Chemically resistant materials and fabrics. Wear fire/flammable resistant/retardant clothing. Corrosion-proof clothing.

**Hand Protection:** Wear protective gloves.

**Eye and Face Protection:** Chemical safety goggles and face shield.

**Skin and Body Protection:** Wear suitable protective clothing.

**Respiratory Protection:** If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

**Other Information:** When using, do not eat, drink or smoke.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: White
Odor	: Ammonia
Odor Threshold	: Not available
pH	: Not available
Evaporation Rate	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: Not available
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Flammability (solid, gas)	: Not applicable
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 20°C	: Not available
Relative Density	: Not available
Density	: 8.09 lb/gal
Specific Gravity	: Not available
Solubility	: Water: Insoluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: Not available

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Reacts violently with strong oxidizers. Increased risk of fire or explosion. May react exothermically with water releasing heat. Adding an acid to a base or base to an acid may cause a violent reaction. Prolonged storage: may form peroxides.
- 10.2. Chemical Stability:** Combustible liquid. May form flammable or explosive vapor-air mixture.
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight, extremely high or low temperatures, heat, hot surfaces, sparks, open flames, incompatible materials, and other ignition sources.
- 10.5. Incompatible Materials:** Oxidizing agent. Acids. Amines. alcohols, ketones, aldehydes, hydrocarbons.
- 10.6. Hazardous Decomposition Products:** Thermal decomposition generates: Corrosive vapors.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on Toxicological Effects - Product

**Acute Toxicity (Oral):** Harmful if swallowed.

**Acute Toxicity (Dermal):** Not classified

**Acute Toxicity (Inhalation):** Harmful if inhaled.

**LD50 and LC50 Data:**

SPECTRALOCK® PRO Premium Translucent Grout Part A	
ATE US/CA (oral)	878.53 mg/kg body weight
ATE US/CA (dust, mist)	4.61 mg/l/4h

**Skin Corrosion/Irritation:** Causes severe skin burns and eye damage.

**Eye Damage/Irritation:** Causes serious eye damage.

**Respiratory or Skin Sensitization:** May cause an allergic skin reaction.

**Germ Cell Mutagenicity:** May cause genetic defects.

**Carcinogenicity:** May cause cancer.

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Reproductive Toxicity:** May damage fertility or the unborn child.

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Aspiration Hazard:** May be fatal if swallowed and enters airways.

**Symptoms/Injuries After Inhalation:** Inhalation is likely to cause adverse health effects including but not limited to: irritation, difficulty breathing, and unconsciousness. May be corrosive to the respiratory tract.

**Symptoms/Injuries After Skin Contact:** May cause an allergic skin reaction. Causes severe irritation which will progress to chemical burns.

**Symptoms/Injuries After Eye Contact:** Causes permanent damage to the cornea, iris, or conjunctiva.

**Symptoms/Injuries After Ingestion:** This material is harmful orally and can cause adverse health effects or death in significant amounts. May cause burns or irritation of the linings of the mouth, throat, and gastrointestinal tract. Aspiration into the lungs can occur during ingestion or vomiting and may cause lung injury.

**Chronic Symptoms:** May cause cancer. May cause genetic defects. May damage fertility or the unborn child.

### 11.2. Information on Toxicological Effects - Ingredient(s)

**LD50 and LC50 Data:**

Benzyl alcohol (100-51-6)
---------------------------



# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

LD50 Oral Rat	1230 mg/kg
LD50 Dermal Rabbit	> 2000 mg/kg
LD50 Intravenous Rat	53 mg/kg
LC50 Inhalation Rat	> 4.178 mg/l/4h
ATE US/CA (dust, mist)	1.50 mg/l/4h
<b>1-Piperazineethanamine (140-31-8)</b>	
LD50 Oral Rat	2140 µl/kg
LD50 Dermal Rabbit	880 µl/kg
ATE US/CA (oral)	500.00 mg/kg body weight
ATE US/CA (dermal)	1,100.00 mg/kg body weight
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
LD50 Oral Rat	1300 mg/kg
LD50 Dermal Rabbit	2000 mg/kg
<b>Trimethylhexamethylenediamine (25620-58-0)</b>	
LD50 Oral Rat	910 mg/kg
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
LD50 Oral Rat	2885 mg/kg (Specoes: Sprague-Dawley)
LD50 Dermal Rabbit	2980 mg/kg
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
LD50 Oral Rat	1030 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
ATE US/CA (dermal)	1,100.00 mg/kg body weight
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>	
LD50 Oral Rat	2000 mg/kg
LD50 Dermal Rabbit	3560 µl/kg
<b>Isopropylbenzene (98-82-8)</b>	
LD50 Oral Rat	2260 mg/kg
LD50 Dermal Rabbit	10000 mg/kg
LC50 Inhalation Rat	9.83 mg/l/4h
LC50 Inhalation Rat	> 3577 ppm (Exposure time: 6 h)
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>	
LD50 Oral Rat	8532 mg/kg
LD50 Dermal Rabbit	> 5 g/kg
<b>Stoddard solvent (8052-41-3)</b>	
LD50 Oral Rat	> 5 g/kg Behavioral somnolence
LD50 Dermal Rabbit	> 3 g/kg
LC50 Inhalation Rat	> 5500 mg/l/4h Behavioral somnolence
<b>Isopropylbenzene (98-82-8)</b>	
IARC Group	2B
National Toxicology Program (NTP) Status	Evidence of Carcinogenicity, Reasonably anticipated to be Human Carcinogen.
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

Ecology - General: Toxic to aquatic life with long lasting effects.

<b>Benzyl alcohol (100-51-6)</b>	
LC50 Fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
LC50 Fish 2	10 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])
ErC50 (algae)	770 mg/l

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)</b>	
LC50 Fish 1	1.62 mg/l
EC50 Daphnia 1	1.59 mg/l
ErC50 (algae)	3.3 mg/l
NOEC Chronic Algae	2.07 mg/l
<b>1-Piperazineethanamine (140-31-8)</b>	
LC50 Fish 1	1950 - 2460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	32 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	> 1000 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [semi-static])
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
LC50 Fish 1	0.135 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	0.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 Fish 2	0.1351 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
NOEC Chronic Fish	0.006
<b>Trimethylhexamethylenediamine (25620-58-0)</b>	
ErC50 (algae)	29.5 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
EC50 Daphnia 1	80 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC Chronic Crustacea	18 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
EC50 Daphnia 1	14.6 - 21.5 mg/l (Exposure time: 48 h - Species: Daphnia magna [semi-static])
NOEC Chronic Crustacea	3 mg/l
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>	
LC50 Fish 1	728 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
EC50 Daphnia 1	22 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Isopropylbenzene (98-82-8)</b>	
LC50 Fish 1	6.04 - 6.61 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
LC50 Fish 2	4.8 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [flow-through])
EC50 Daphnia 2	7.9 - 14.1 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
NOEC Chronic Crustacea	0.35 mg/l
NOEC Chronic Algae	0.22 mg/l
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>	
LC50 Fish 1	161 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	> 500 mg/l (Exposure time: 48 h - Species: Daphnia magna)
<b>Stoddard solvent (8052-41-3)</b>	
NOEC Chronic Algae	0.16 mg/l

### 12.2. Persistence and Degradability

<b>SPECTRALOCK® PRO Premium Translucent Grout Part A</b>	
Persistence and Degradability	May cause long-term adverse effects in the environment.

### 12.3. Bioaccumulative Potential

<b>SPECTRALOCK® PRO Premium Translucent Grout Part A</b>	
Bioaccumulative Potential	Not established.
<b>Benzyl alcohol (100-51-6)</b>	
Log Pow	1.1
<b>1-Piperazineethanamine (140-31-8)</b>	
BCF Fish 1	(no bioaccumulation expected)
Log Pow	-1.48
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
BCF Fish 1	271

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Trimethylhexamethylenediamine (25620-58-0)</b>	
<b>Log Pow</b>	0.77 (at 23 °C)
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
<b>Log Kow</b>	0
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
<b>Log Pow</b>	0.79 (at 23 °C)
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>	
<b>BCF Fish 1</b>	0.2 - 3.7
<b>Log Pow</b>	-1.46
<b>Isopropylbenzene (98-82-8)</b>	
<b>BCF Fish 1</b>	35.5
<b>Log Pow</b>	3.7
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>	
<b>Log Pow</b>	0.43
<b>Stoddard solvent (8052-41-3)</b>	
<b>Log Pow</b>	3.16 (Octanol/water partition coefficient 3.16/7.06)

**12.4. Mobility in Soil** Not available

### 12.5. Other Adverse Effects

**Other Information:** Avoid release to the environment.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of contents/container in accordance with local, regional, national, territorial, provincial, and international regulations.

**Additional Information:** Handle empty containers with care because residual vapors are flammable.

**Ecology - Waste Materials:** Avoid release to the environment. This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

## SECTION 14: TRANSPORT INFORMATION

The shipping description(s) stated herein were prepared in accordance with certain assumptions at the time the SDS was authored, and can vary based on a number of variables that may or may not have been known at the time the SDS was issued.

### 14.1. In Accordance with DOT

**Proper Shipping Name** : CORROSIVE LIQUIDS, N.O.S.(Phenol, 4-nonyl-, branched; 1-Piperazineethanamine)  
**Hazard Class** : 8  
**Identification Number** : UN1760  
**Label Codes** : 8  
**Packing Group** : III  
**Marine Pollutant** : Marine pollutant  
**ERG Number** : 154



### 14.2. In Accordance with IMDG

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S. (Phenol, 4-nonyl-, branched; 1-Piperazineethanamine)  
**Hazard Class** : 8  
**Identification Number** : UN1760  
**Label Codes** : 8  
**Packing Group** : III  
**EmS-No. (Fire)** : F-A  
**EmS-No. (Spillage)** : S-B  
**Marine pollutant** : Marine pollutant



### 14.3. In Accordance with IATA

**Proper Shipping Name** : CORROSIVE LIQUID, N.O.S. (Phenol, 4-nonyl-, branched; 1-Piperazineethanamine)  
**Hazard Class** : 8  
**Identification Number** : UN1760



# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Label Codes : 8  
Packing Group : III  
ERG Code (IATA) : 8L

### 14.4. In Accordance with TDG

Proper Shipping Name : CORROSIVE LIQUID, N.O.S.(Phenol, 4-nonyl-, branched; 1-Piperazineethanamine)  
Hazard Class : 8  
Identification Number : UN1760  
Label Codes : 8  
Packing Group : III  
Marine Pollutant (TDG) : Marine pollutant



## SECTION 15: REGULATORY INFORMATION

### 15.1. US Federal Regulations

<b>SPECTRALOCK® PRO Premium Translucent Grout Part A</b>	
<b>SARA Section 311/312 Hazard Classes</b>	Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Physical hazard - Flammable (gases, aerosols, liquids, or solids) Health hazard - Germ cell mutagenicity Health hazard - Reproductive toxicity Health hazard - Acute toxicity (any route of exposure) Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation Health hazard - Aspiration hazard
<b>Benzyl alcohol (100-51-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>1-Piperazineethanamine (140-31-8)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Subject to reporting requirements of United States SARA Section 313	
<b>EPA TSCA Regulatory Flag</b>	SP - SP - indicates a substance that is identified in a proposed Significant New Uses Rule.
<b>SARA Section 313 - Emission Reporting</b>	1 %
<b>Trimethylhexamethylenediamine (25620-58-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>EPA TSCA Regulatory Flag</b>	XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Urea, N,N'-bis[3-(dimethylamino)propyl]- (52338-87-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
<b>Isopropylbenzene (98-82-8)</b>	

# SPECTRALOCK® PRO Premium Translucent Grout Part A


## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Subject to reporting requirements of United States SARA Section 313	
CERCLA RQ	5000 lb
SARA Section 313 - Emission Reporting	0.1 %
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	PMN - PMN - indicates a commenced PMN substance.
<b>Stoddard solvent (8052-41-3)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

### 15.2. US State Regulations

#### California Proposition 65

 **WARNING:** This product can expose you to Isopropylbenzene, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Chemical Name (CAS No.)	Carcinogenicity	Developmental Toxicity	Female Reproductive Toxicity	Male Reproductive Toxicity
Isopropylbenzene (98-82-8)	X			
<b>Benzyl alcohol (100-51-6)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - Pennsylvania - RTK (Right to Know) List				
<b>1-Piperazineethanamine (140-31-8)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Trimethylhexamethylenediamine (25620-58-0)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List				
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>				
U.S. - New Jersey - Right to Know Hazardous Substance List				
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Isopropylbenzene (98-82-8)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List				
U.S. - Pennsylvania - RTK (Right to Know) List				
<b>Stoddard solvent (8052-41-3)</b>				
U.S. - Massachusetts - Right To Know List				
U.S. - New Jersey - Right to Know Hazardous Substance List				
U.S. - Pennsylvania - RTK (Right to Know) List				

### 15.3. Canadian Regulations

<b>Benzyl alcohol (100-51-6)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl-, reaction products with bisphenol A diglycidyl ether homopolymer (68609-08-5)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>1-Piperazineethanamine (140-31-8)</b>	
Listed on the Canadian DSL (Domestic Substances List)	
<b>Phenol, 4-nonyl-, branched (84852-15-3)</b>	
Listed on the Canadian DSL (Domestic Substances List)	

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

<b>Trimethylhexamethylenediamine (25620-58-0)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Poly[oxy(methyl-1,2-ethanediyl)], .alpha.-(2-aminomethylethyl)-.omega.-(2-aminomethylethoxy)- (9046-10-0)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Cyclohexanemethanamine, 5-amino-1,3,3-trimethyl- (2855-13-2)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Urea, N,N'-bis[3-(dimethylamino)propyl]- (52338-87-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Ethanol, 2-[(2-aminoethyl)amino]- (111-41-1)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Isopropylbenzene (98-82-8)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Propylene glycol monomethyl ether acetate (108-65-6)</b>
Listed on the Canadian DSL (Domestic Substances List)
<b>Stoddard solvent (8052-41-3)</b>
Listed on the Canadian DSL (Domestic Substances List)

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

**Date of Preparation or Latest Revision** : 07/06/2020

### Revision

**Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200 and Canada's Hazardous Products Regulations (HPR) SOR/2015-17.

### GHS Full Text Phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 2	Hazardous to the aquatic environment - Acute Hazard Category 2
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment - Chronic Hazard Category 3
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Repr. 1B	Reproductive toxicity Category 1B
Repr. 2	Reproductive toxicity Category 2
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Corr. 1C	Skin corrosion/irritation Category 1C
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization, Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1

# SPECTRALOCK® PRO Premium Translucent Grout Part A

## Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations And According To The Hazardous Products Regulation (February 11, 2015).

STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H401	Toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

NA GHS SDS 2015 (Can, US)