

DIRECT DRIVE PUMPS - WGP-SERIES

This efficient, dual discharge pump produces greater pressure, so each can serve two water features simultaneously. Installed either vertically or horizontally, the corrosion-resistant submersible body is designed for non-potable, continuous operation. Ideal for filtration, waterfalls, and streams.



WGP-95-PW



WGP-65-PW

OIL-FREE

FEATURES

- Dual discharge can serve two water features simultaneously
- Mount vertically or horizontally
- Removable pre-filter for easy cleaning
- Rated for continuous duty

SERIES SPECIFICATIONS

Item No.	Model	Volts	Amps	Watts	Discharge FNPT	Gallons per hour (Liters per hour) @ Height						Shut-off	Cord
						1'	5'	10'	15'	20'	25'		
566409	WGP-65-PW	115	2	230	1.25" (31.7 mm)	1900 (7192)	1250 (4732)	785 (2972)	325 (1230)	-	-	20' (6.1 m)	16' (4.8 m)
566417	WGP-80-PW	115	6.3	700	1.25" (31.7 mm)	3500 (13249)	3200 (12113)	2700 (10221)	2100 (7949)	1300 (4921)	695 (2631)	29.5' (8.9 m)	16' (4.8 m)
566407	WGP-95-PW	115	6.3	700	1.25" (31.7 mm)	4280 (16202)	4000 (15142)	3500 (13249)	2850 (10788)	2200 (8328)	1370 (5186)	30' (9.1 m)	16' (4.8 m)

DIMENSIONS

Dimensions (in)	A	B	C	Weight
WGP-65-PW	9.6	8.1	6.35	10.43 (4.73)
WGP-80-PW	11.0	8.1	6.35	14.68 (6.65)
WGP-95-PW	11.0	8.1	6.35	14.68 (6.65)

PERFORMANCE

