

3/16" x 3" Phillips/Slotted Mushroom Head Toggle Bolt

Part Number TBC363  
Category Number 4050  
UPC 781002168508



Toggle Bolts, or butterfly anchors, are a light to medium duty anchor intended to be used in hollow block, wallboard, plaster, plywood, and other hollow base materials. Once fully opened, Toggle Bolts significantly expand the surface area making contact with the back of the hollow wall. This spreads out the load of the fastened object, increasing the weight that can be secured. The maximum weight a Toggle Bolt supports, depends on the size of the bolt and the thickness of the substrate. To accommodate the Toggle, installation requires a relatively large hole compared to other types of hollow wall anchors.

Physical Characteristics

|                  |                  |
|------------------|------------------|
| Anchor Type      | Toggle Bolt      |
| Nut Type         | Spring Wing      |
| Drive Type       | Phillips/Slotted |
| Head Type        | Mushroom         |
| Thread Type      | UNC              |
| Size             | 3/16" x 3"       |
| Bit Size         | #2               |
| Dia./Thread Size | 3/16"-24         |
| Anchor Diameter  | 3/16"            |
| Length (in)      | 3"               |
| Thread Per Inch  | 24               |
| Material         | Carbon Steel     |
| Finish           | Zinc Plated      |

Packaging Details

|                |        |
|----------------|--------|
| Standard Qty   | 50     |
| Master Qty     | 500    |
| Price Per      | 100    |
| Package Length | 5.50   |
| Package Width  | 4.10   |
| Package Height | 2.70   |
| Net Weight     | 0.0353 |
| Package Weight | 1.77   |

Performance Data

|                  |                                                                                                                   |
|------------------|-------------------------------------------------------------------------------------------------------------------|
| Pre-Drill Size   | 1/2"                                                                                                              |
| Applications     | Hollow Block, Wallboard, Plaster, Plywood and other Hollow Base Materials                                         |
| Special Features | Adjustable for Various Thicknesses, Contractor Oriented Design, Easy to Use, Wings Open to Distribute Load Evenly |

Certifications

|                |          |
|----------------|----------|
| UNSPSC         | 31161609 |
| RoHS Compliant | Yes      |