

# **Product Description**

**Americrete Concrete Resurfacer** is a powdered proprietary co-polymer mix that is easy to install for large projects or small repairs. This product only needs water added. Designed as a micro topping, it can be used in virtually any climate due to its ability to resist freeze/thaw cycles, and is salt resistant. **Concrete Resurfacer** can be used as a feather edge product and is available in light gray.

## **Coverage Rate**

**Concrete Resurfacer** when applied by squeegee will cover 200 to 400 square feet per bag depending upon the application procedures and the porosity of the concrete surface. Mixing Ratio; one 50 lb. Bag of A-601 to 4 – 6.5 quarts of water.

## **Primary Use, Characteristics and Advantages**

**Concrete Resurfacer** eliminates concrete removal and is a single component mixture (add water only). It has superior bonding capabilities, tested at 5510 psi, while maintaining flexibility and weather resistance. **Concrete Resurfacer** has been designed for use as a micro topping that is water resistant and can not be re-emulsifiable. **Concrete Resurfacer** is environmentally friendly and ideal for vapor emission control.

# **Typical Applications**

Walkways, patios, casinos, airport hangers, restaurants, parking structures, pool decks, one step tile set, curbs and gutters, driveways, bridges and warehouse floors. Underlayment for carpet, tile, wood floors, etc... Ideal leveling agent.

## **Important Notice to Purchaser**

Please see Important Notice to Purchaser in the front of this Specification Book.