



LIFE PAINT

PRODUCT SPECIFICATIONS



CLEAR SEALERS

1325 SILICONE SEALER

Description

Life's Concrete Masonry Siliconate Sealer is a clear penetrating water repellent for use on porous concrete or other masonry surfaces. Contains no wax.

Use

This Concrete Sealer may be applied to above grade concrete and masonry blocks, cement block, stucco, walls, stones, grout, porous tiles, inside or outside, new or old unpainted surfaces.

Advantages

- * Fast Drying
- * Water Base
- * Penetrating
- * Invisible protection
- * Easy to use
- * Low Odor

Finish Natural Finish

Inspection

Surface to be protected must be porous enough to allow total penetration. Surface ponding may cause discoloration. Please test a small area before beginning your project. Painted or stained masonry and concrete surfaces could be discolored by the use of this product. Please test before using on such areas. Keep Concrete Sealer away from contact with aluminum and other light metallic alloys. Do not apply to wood surfaces.

IMPORTANT NOTE: Do not apply to wood surfaces or any sealed concrete or masonry surface. Not recommended for below grade waterproofing. New concrete and masonry should cure for 30 days.

Surface Preparation

Make sure your surface is clean, dry, dust free and prepared to accept the invisible penetrating protection of this Concrete Sealer. Moisture content of the surface should register no higher than 15% as measured with an electronic moisture meter.

Application Specifics You may apply this product with a brush, roller, spray equipment or even a synthetic fiber broom on horizontal surfaces. (See above warning regarding aluminum and light alloys.) Never apply more than one coat to pre-cast concrete, brick walls, stucco, concrete block, split face bloc, or masonry. Avoid puddling. The surface to be protected should absorb all the product applied.

Do not thin.

Coverage

Coverage will vary due to the porosities of cementitious and masonry surfaces.

Surface	Sq.Ft./Gallon
Masonry/Stucco	75-125
Concrete Block	50-80
Mammoth Block	70-100
Porous Tile	80-100
Clay Tile	100-150
Split Face Block	50-80

In many cases discoloration from over application may be removed by scrubbing with household detergent.

Drying Time

Do not apply this product when the ambient temperatures might drop below 40°F. Do not apply during rainy or foggy conditions. At 77°F and 50% relative humidity over a porous concrete surface your protected surface will be ready for use within 30 minutes.

Clean-up

Clean tools and hands with warm soapy water and rinse thoroughly.

CAUTION

Wear protective clothing, goggles and gloves to avoid contact with skin. If direct contact occurs, wash skin thoroughly. Avoid breathing vapors or spray mist. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area. Wash thoroughly after use. Close container after use. Avoid contact with food.

FIRST AID: Eye Contact: Flush thoroughly with water for at least 15 minutes. If irritation persists get medical attention.

If Inhaled: If affected by vapors or spray mist, move to fresh air. If breathing difficulty continues, get medical attention.

If Swallowed: Drink two glasses of water. Get medical attention immediately.

Technical Information

Type:	Silicone Masonry Water Repellants
Diluent:	Water
Solids Content:	7-8% by weight 5-6% by volume
Viscosity:	Like Water
Flash Point:	200°F plus
Maximum V.O.C.:	0 grams per liter