

FLOOR N DECK SANDY BEIGE

HMIS CODES: H F R P

Page: 1 1/26/2006

PRODUCT NAME: FLOOR N DECK SANDY BEIGE

PRODUCT CODE: 10-78/150 1 0 0 A

# **SECTION I - MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: LIFE PAINT COMPANY

ADDRESS : 12927 SUNSHINE AVENUE

SANTA FE SPRINGS, CA 90670-0488

EMERGENCY PHONE : (800) 424-9300 INFORMATION PHONE : (562) 944-6391

NAME OF PREPARER : MICHAEL DE LA VEGA DATE PRINTED : 1/26/2006

# SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

	VAPOR PRESSURE			WEIGHT	
REPORTABLE COMPONENTS	CAS NUMBER mm Hg @ TEMP		PER	PERCENT	
METHYL CARBITOL	111-77-3	.2	68	5	
OSHA PEL: NE, ACGIH TLV: NE, OTHER: NE					
PROPYLENE GLYCOL MONOBUTYL ETHER	5131-66-8	.6	68	5	
OSHA PEL: NA, ACGIH TLV: NA					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

WARNING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR REPRODUCTIVE HARM MAY BE PRESENT IN THIS PRODUCT.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.27

VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than ether

COATING V.O.C.: 1.65 lb/gl MATERIAL V.O.C.: 0.81 lb/gl

SOLUBILITY IN WATER: DILUTABLE

APPEARANCE AND ODOR: COLORED LIQUID WITH MILD ODOR

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 150 METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1 UPPER: 22.7

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, WATER FOG

### SPECIAL FIREFIGHTING PROCEDURES

IF WATER IS USED FOG NOZZLES ARE PREFERRABLE. USE WATER TO COOL CLOSED CONTAINERS

#### UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.



FLOOR N DECK SANDY BEIGE

Page: 2 1/26/2006

# **SECTION V - REACTIVITY DATA**

STABILITY: STABLE CONDITIONS TO AVOID

HIGH TEMPERATURES OR EXTREME HEAT

#### INCOMPATIBILITY (MATERIALS TO AVOID)

OXYGEN AND STRONG OXIDIZERS, SULFURIC ACID, AND OTHER DEHYDRATING AGENTS.

#### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

# **SECTION VI - HEALTH HAZARD DATA**

#### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OVEREXPOSURE MAY CAUSE DIZZINESS, HEADACHES, EVEN UNCONSCIOUSNESS.

#### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED SKIN CONTACT WILL CAUSE DRYING AND DEFATING OF SKIN TISSUE LEADING TO IRRITATION AND DERMATITIS.EYE CONTACT MAY CAUSE IRRITATION AND BLURRED VISION.

#### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DRYING AND DEFATTING OF SKIN

# INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTATION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING, AND DIARRHEA.

## HEALTH HAZARDS (ACUTE AND CHRONIC)

THE PROPER USE OF THIS PAINT PRODUCT DOES NOT PRESENT ANY SERIOUS HEALTH HAZARD KNOWN TO LIFE PAINT COMPANY.

#### CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:

No

N/A

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

# EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN. INGESTION: INDUCE VOMITTING IF VICTIM IS CONSCIOUS.CALL PHYSICIAN IMMEDIATELY SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH EYES WITH WATER.CALL PHYSICIAN IMMEDIATELY.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

# STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL IGNITION SOURCES. VENTILATE CONFINED SPACES. AVOD BREATHING VAPORS.RECOVER FREE LIQUID AND ABSORBENT MATERIAL

Life Paint Company 12927 Sunshine Ave Santa Fe Springs, CA 90670

FLOOR N DECK SANDY BEIGE

Page: 3 1/26/2006

FROM SPILL ARE. KEEP OUT OF SEWERS AND WATERWAYS.

#### WASTE DISPOSAL METHOD

DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, OR UNDERGROUND WATER SUPPLIES. INCINERATE OR BURY IN AN APPROVED LANDFILL.BE CERTAIN TO COMPLY WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS IN THE WASTE DISPOSAL METHOD THAT YOU CHOOSE.

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, OPEN FLAME, OR STRONG OXIDANTS.USE ONLY IN WELL VENTILATED AREAS.AVOID BREATHING VAPORS. AVOID CONTACT WITH SKIN. KEEP OUT OF THE REACH OF CHILDREN.

#### OTHER PRECAUTIONS

N/A

# **SECTION VIII - CONTROL MEASURES**

#### RESPIRATORY PROTECTION

USE APPROPRIATE NIOSH APPROVED RESPIRATORY EQUIPMENT WHEN OCCUPATIONAL EXPOSURE LIMITS ARE EXCEEDED.

#### **VENTILATION**

LOCAL EXHAUST AND MECHANICAL VENTILATION ARE RECOMMENDED.

### PROTECTIVE GLOVES

NEOPRENE OR NON SOLUBLE PLASTIC.

### EYE PROTECTION

GOGGLES.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

DI/A

# WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING OR SMOKING.

# **SECTION IX - DISCLAIMER**

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT SOURCES BELIEVED BY LIFE PAINT CORPORATION TO BE ACCURATE LIFE PAINT CORPORATION DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THE INFORMATION SUPPLIED HERE.



FLOOR N DECK SANDY BEIGE

Page: 1 1/26/2006

PRODUCT NAME: FLOOR N DECK SANDY BEIGE

PRODUCT CODE: 10-78/250

HMIS CODES: H F R P 1 0 0 A

# **SECTION I - MANUFACTURER IDENTIFICATION**

MANUFACTURER'S NAME: LIFE PAINT COMPANY

ADDRESS : 12927 SUNSHINE AVENUE

SANTA FE SPRINGS, CA 90670-0488

EMERGENCY PHONE : (800) 424-9300 INFORMATION PHONE : (562) 944-6391

NAME OF PREPARER : MICHAEL DE LA VEGA DATE PRINTED : 1/26/2006

# SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

	v	APOR PRESSUR	E	WEIGHT	
REPORTABLE COMPONENTS	CAS NUMBER	mm Hg @ TEMP		PERCENT	
METHYL CARBITOL	111-77-3	.2	68	5	
OSHA PEL: NE, ACGIH TLV: NE, OTHER: NE					
PROPYLENE GLYCOL MONOBUTYL ETHER	5131-66-8	.6	68	5	
OSHA PEL: NA, ACGIH TLV: NA					

\*\*\* No toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372 are present. \*\*\*

WARNING: DETECTABLE AMOUNTS OF A CHEMICAL KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND/OR BIRTH DEFECTS OR REPRODUCTIVE HARM MAY BE PRESENT IN THIS PRODUCT.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING RANGE: N/A SPECIFIC GRAVITY (H2O=1): 1.27

VAPOR DENSITY: Heavier than air EVAPORATION RATE: Slower than ether

COATING V.O.C.: 1.65 lb/gl MATERIAL V.O.C.: 0.81 lb/gl

SOLUBILITY IN WATER: DILUTABLE

APPEARANCE AND ODOR: COLORED LIQUID WITH MILD ODOR

### SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: 150 METHOD USED: N/A

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1 UPPER: 22.7

EXTINGUISHING MEDIA: CO2, DRY CHEMICAL, WATER FOG

# SPECIAL FIREFIGHTING PROCEDURES

IF WATER IS USED FOG NOZZLES ARE PREFERRABLE. USE WATER TO COOL CLOSED CONTAINERS

#### UNUSUAL FIRE AND EXPLOSION HAZARDS

CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.



FLOOR N DECK SANDY BEIGE

Page: 2 1/26/2006

# **SECTION V - REACTIVITY DATA**

STABILITY: STABLE CONDITIONS TO AVOID

HIGH TEMPERATURES OR EXTREME HEAT

#### INCOMPATIBILITY (MATERIALS TO AVOID)

OXYGEN AND STRONG OXIDIZERS, SULFURIC ACID, AND OTHER DEHYDRATING AGENTS.

#### HAZARDOUS DECOMPOSITION OR BYPRODUCTS

CARBON MONOXIDE AND CARBON DIOXIDE

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

# **SECTION VI - HEALTH HAZARD DATA**

#### INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INHALATION OVEREXPOSURE MAY CAUSE DIZZINESS, HEADACHES, EVEN UNCONSCIOUSNESS.

#### SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

PROLONGED SKIN CONTACT WILL CAUSE DRYING AND DEFATING OF SKIN TISSUE LEADING TO IRRITATION AND DERMATITIS.EYE CONTACT MAY CAUSE IRRITATION AND BLURRED VISION.

#### SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

DRYING AND DEFATTING OF SKIN

# INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTATION MAY CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITTING, AND DIARRHEA.

## HEALTH HAZARDS (ACUTE AND CHRONIC)

THE PROPER USE OF THIS PAINT PRODUCT DOES NOT PRESENT ANY SERIOUS HEALTH HAZARD KNOWN TO LIFE PAINT COMPANY.

#### CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED:

No

N/A

### MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

UNKNOWN

# EMERGENCY AND FIRST AID PROCEDURES

INHALATION: REMOVE TO FRESH AIR AND GIVE ARTIFICIAL RESPIRATION OR OXYGEN. INGESTION: INDUCE VOMITTING IF VICTIM IS CONSCIOUS.CALL PHYSICIAN IMMEDIATELY SKIN CONTACT: WASH WITH SOAP AND WATER. EYE CONTACT: FLUSH EYES WITH WATER.CALL PHYSICIAN IMMEDIATELY.

### SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

# STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

REMOVE ALL IGNITION SOURCES. VENTILATE CONFINED SPACES. AVOD BREATHING VAPORS.RECOVER FREE LIQUID AND ABSORBENT MATERIAL

Life Paint Company 12927 Sunshine Ave Santa Fe Springs, CA 90670

FLOOR N DECK SANDY BEIGE

Page: 3 1/26/2006

FROM SPILL ARE. KEEP OUT OF SEWERS AND WATERWAYS.

#### WASTE DISPOSAL METHOD

DO NOT CONTAMINATE ANY LAKES, STREAMS, PONDS, OR UNDERGROUND WATER SUPPLIES. INCINERATE OR BURY IN AN APPROVED LANDFILL.BE CERTAIN TO COMPLY WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS IN THE WASTE DISPOSAL METHOD THAT YOU CHOOSE.

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, OPEN FLAME, OR STRONG OXIDANTS.USE ONLY IN WELL VENTILATED AREAS.AVOID BREATHING VAPORS. AVOID CONTACT WITH SKIN. KEEP OUT OF THE REACH OF CHILDREN.

#### OTHER PRECAUTIONS

N/A

# **SECTION VIII - CONTROL MEASURES**

#### RESPIRATORY PROTECTION

USE APPROPRIATE NIOSH APPROVED RESPIRATORY EQUIPMENT WHEN OCCUPATIONAL EXPOSURE LIMITS ARE EXCEEDED.

#### **VENTILATION**

LOCAL EXHAUST AND MECHANICAL VENTILATION ARE RECOMMENDED.

### PROTECTIVE GLOVES

NEOPRENE OR NON SOLUBLE PLASTIC.

### EYE PROTECTION

GOGGLES.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

DI/A

# WORK/HYGIENIC PRACTICES

WASH HANDS BEFORE EATING OR SMOKING.

# **SECTION IX - DISCLAIMER**

THIS INFORMATION IS FURNISHED WITHOUT WARRANTY, REPRESENTATION, INDUCEMENT OR LICENSE OF ANY KIND, EXCEPT SOURCES BELIEVED BY LIFE PAINT CORPORATION TO BE ACCURATE LIFE PAINT CORPORATION DOES NOT ASSUME ANY LEGAL RESPONSIBILITY FOR USE OR RELIANCE ON THE INFORMATION SUPPLIED HERE.