

D6B2-5W-27K-A D6B2-5W-30K-A

D6B2-10W-27K-A

D6B2-10W-30K-A

Modular Light Source Spot Light Antique Brush Brass













| Fixture Type | Fixture Components | Fixture Material | Fixture Style | Watts | Color Temperature | Finish |
|-----------------|------------------------------------|------------------|---------------|-----------|----------------------------|--------------|
| D (Directional) | 6 (Integrated Modular Variable) | B (Brass) | 2 (Down) | 5W 10W | 27K (2700K) 30K (3000K) | A (Antiqued) |





Construction: Brass Finish: Antique Brush Lead Wire: 30ft long Mounting: LAP-002 Wattage: 5W or 10W Operating Voltage: 10-15V Lumens: 375LM or 600LM

Beam Spread: 15°, 38°, 60°

Color Temperature: 2700K or 3000K

Volt Amps: 6.99 - 14.11

RGB: NO CRI: 80+

Rated Life: 50,000 Hrs

Dimmable: Primary Dimming Capable

APPLICATION

Environment: Wet, Damp or Dry Area approved.

Included Optic Lenses (In The Box):

15* Lens

40* Lens

60* Lens

ACCESSORIES











Lifetime Warranty on the Housing, 10 Year Warranty on the LED Light Source

CERTIFICATION

UL Listed | File #E501872