


NAMEPLATE DATA

EXTERNAL CONNECTION DIAGRAM

NOTES

MODEL: F56AB31A01
CUST PN: BPA449V1
HP: 1.25 SF: 1.00
ROT: CCWPE
RPM: 3450
TYPE: CX CODE: L
FORM: FRAME: 56Y
VOLTS: 208-230/115
AMPS:
MAX AMPS:
SF AMPS: 7.0-6.4/12.8
PH: 1 HZ: 60
INS: F AMB: 50°C
DUTY: CONT
ENCLOSURE: ODP
THERMALLY PROTECTED



1. FOR THREADED SHAFT EXT. ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004[.10] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR.
2. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST.
3. ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS.
4. FINISH PAINT TO BE BEIGE.
5. 1.25 SF HP

PERFORMANCE CURVE

APPROVED SAMPLE

16380511

UL COMPONENT

CSA

FILE#

CCN#

PENDING

PENDING

CUSTOMER

DISTRIBUTION

DRAWING	REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY	REGAL
A	MEO		04/25/14	.X ±0.1 [±2.5] .05°	MEO	Regal Beloit America, Inc.
ECO	APPROVED BY		DATE		DATE:	
ECO-50130	SNELL		04/25/14		04/25/14	
ECO DESCRIPTION					APPROVED BY:	
NEW RELEASE					SNELL	
©2014 REGAL BELIOT AMERICA, INC. ALL RIGHTS RESERVED. PROPRIETARY AND CONFIDENTIAL INFORMATION - THIS DOCUMENT IS THE PROPERTY OF REGAL BELIOT AMERICA, INC. ("OWNER") AND CONTAINS OWNER'S PROPRIETARY INFORMATION. IT IS TO BE USED ONLY BY THE ADDRESSEE. IT IS TO BE KEPT BY RECEIVING IT, TO AGREE THAT IT, AND/OR ANY PART OF IT, SHALL NOT BE DISCLOSED TO ANY PERSON, CORPORATION OR OTHER ENTITY, DUPLICATED, AND/OR USED, EXCEPT AS EXPRESSLY APPROVED IN WRITING IN ADVANCE BY OWNER. THIS DOCUMENT SHALL NOT BE RETURNED TO OWNER UPON REQUEST, IF OWNER SELECTS CERTAIN RESTRICTIONS UNDER APPLICABLE EXPORT CONTROL LAWS AND REGULATIONS.						
PROCESS/FINISH					DESCRIPTION	MODEL-PFHP-56FR OUTLINE
MATERIAL						
THIRD ANGLE PROJECTION					SIZE	DWG NO
C						BPA449V1
						SHEET
						1