


NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
<p>MODEL: F56AA40A01 CUST PN: B2854 HP: 1.5 SF: 1.10 ROT: CCWPE RPM: 3450 TYPE: CX CODE: J FORM: - FRAME: Y56Y VOLTS: 230/115 AMPS: - MAX AMPS: - SF AMPS: 8.0/16.0 PH: 1 HZ: 60 INS: F AMB: 50°C DUTY: CONT ENCLOSURE: ODP THERMALLY-PROTECTED</p>		<p>B</p> <ol style="list-style-type: none"> 1. FOR THREADED SHAFT EXTENSION ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004[.01] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR. 2. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST. 3. FINISH PAINT TO BE BLACK. 4. CONNECTED FOR 230V. DUAL VOLTAGE MOTOR. SEE CONNECTION DIAGRAM TO CHANGE VOLTS TO 115V.

PERFORMANCE CURVE	APPROVED SAMPLE
16381811	B2848
UL COMPONENT	CSA
FILE#	CCN#
PENDING	PENDING
CUSTOMER	DISTRIBUTION

DRAWING	REVISION	REVISION BY	DATE				
G		F.NAVARRO	01-28-2015				
ECO	APPROVED BY		DATE				
0066231	G.ALVIDREZ		01-28-2015				
ECO DESCRIPTION SEE ECO				TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:	Regal Beloit America, Inc.	
				DEC. INCH mm	ANGLE	Regal	
				X ± 0.1 (± 2.5)	$\pm 0.5'$	J.LHESS	
				XX ± 0.02	(± 0.51)	DATE: 06-11-2009	
				XXX ± 0.005	(± 0.127)	APPROVED BY: D.FOX	
				XXXX ± 0.0005	(± 0.0127)	DATE: 06-11-2009	
				DESCRIPTION MODEL-CFHP-56FR			
				OUTLINE			
				REFERENCE	MATERIAL	PROCESS/FINISH	
				INCH mm			
				32/32 mm SHOWN IN [PARENTHESES]			
				THIRD ANGLE PROJECTION	SIZE DWG NO	SHEET 1	
					D2854		