



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 177897 CUST PN: B855 HP: 2.0 SF: 1.10 ROT: CCWPE RPM: 3450 TYPE: CX CODE: F FORM: FRAME: Y 56 Y VOLTS: 230 AMPS: SF 10.0 MAX AMPS: SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 50°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		<ol style="list-style-type: none"> FOR THREADED SHAFT EXT. MATING PARTS SHOULD BE RELIEVED ONE THREAD TO CLEAR FILLET END PLAY NOT TO EXCEED .010 [.25] MEASURED WITH NO THRUST ALL DIMENSIONS SHOWN IN PARENTHESIS ARE REFERENCE DIMENSIONS.

PERFORMANCE CURVE	APPROVED SAMPLE		
18014311			
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E14663	XEWR2	LR4642	4211-01
CUSTOMER	DISTRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
C	F. RAMIREZ	12-02-2014	DEC. INCH mm ANGLE
ECO	APPROVED BY	DATE	.XX ±0.02 [±0.51] ±0.5°
ECO-0066229	J.RUIZ	12-02-2014	.XX ±0.02 [±0.51]
ECO DESCRIPTION			.XXX ±0.005 [±0.127]
SEE ECO			.XXXX ±0.0005 [±0.0127]
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/3.81]
			CORNER FILLETS .02 [1.51]
			MACHINED SURFACES INCH/mm 3/2
			mm SHOWN IN [BRACKETS]

DRAWN BY:	DATE:	DESCRIPTION
D.SCHUBERT		MODEL-CFHP-56FR OUTLINE
APPROVED BY:		
DATE:		
REFERENCE	MATERIAL	PROCESS/FINISH
THIRD ANGLE PROJECTION	SIZE DWG NO	SHEET
	C B855	1

