

## SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTIFICATION

**PRODUCT NAME:** MULTICOAT SPEEDBOND PART A  
**PRODUCT CLASS:** Polymeric Diisocyanate (MDI)  
**COMPANY NAME:** ACCUMETRIC  
350 Ring Road  
Elizabethown, KY 42701  
800-928-2677

**PRODUCT CODE:** MultiCoat SpeedBond-A  
**CAS NUMBER:** None

**FOR EMERGENCY ASSISTANCE**  
**CONTACT CHEMTREC**  
**AT 1-800-424-9300**

### SECTION II - HAZARDS IDENTIFICATION

#### Information in accordance with 29 CFR 1910.1200

##### GHS Classification:

Acute Toxicity Inhalation Category 4  
Skin Irritation Category 2  
Eye Irritation Category 2A  
Respiratory Sensitization Category 1  
Skin Sensitization Category 1

##### GHS Label elements

Pictograms



Signal Word : Danger

##### Hazard Statements:

H315: Causes Skin Irritation  
H317: May cause Allergic skin reaction  
H320: Causes eye irritation  
H332: Harmful if inhaled  
H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled

##### Precautionary Statements:

P261: Do not breathe vapors, mist or spray  
P264: Wash thoroughly hands after handling  
P270: Do not eat drink or smoke when using this product.  
P271: Use only outdoors or in well-ventilated area.  
P280: Wear eye and face protection. Wear protective gloves  
P285: In case of inadequate ventilation wear respiratory protection.  
P302+P352: If on Skin: wash with plenty of soap and water  
P304+P340: If inhaled: Remove person to fresh air and keep comfortable for breathing  
P305+P351+P338: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.  
P333+P313: If skin irritation or rash occurs: Get medical attention  
P337+P313: If eye irritation persists: Get medical attention  
P342+P311: If experiencing respiratory symptoms: Call a poison center or physician  
P362: Take off contaminated clothing and wash before reuse.  
P403: Store in a well-ventilated place  
P232: Protect from moisture  
P233: Keep container tightly closed  
P501: Dispose of contents and /or container according to Federal State/Provincial and local governmental regulations.

---

### SECTION III - COMPOSITION / INFORMATION ON INGREDIENTS

---

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>Weight</u>	<u>ACGIH TWA</u>	<u>OSHA PEL</u>
Diphenylmethane Diisocyanate (MDI)	25686-28-6	>50	0.005 ppm	0.02 ppm

---

---

### SECTION IV - FIRST AID MEASURES

---

<b>SKIN CONTACT :</b>	Remove contaminated clothing or shoes, wipe excess from skin. Wash with soap and plenty of water (warm water is preferable if readily available).
<b>EYE CONTACT :</b>	Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open and seek medical attention.
<b>INHALATION :</b>	Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing and seek medical help immediately. Asthmatic- type symptoms may develop and may be immediate or delayed up to several hours.
<b>INGESTION :</b>	Do not give any liquids (do not induce vomiting). Get medical help immediately.

---

---

### SECTION V - FIRE FIGHTING MEASURES

---

#### EXTINGUISHING MEDIA:

Use Dry Chemical, Carbon Dioxide, Foam or Water Fog. For large fires, alcohol resistant foams (ATC type) are preferred if available. General purpose synthetic foams (including AFFF) or protein foams may function but much less effectively. Water is not recommended but may be applied in very large quantities as a fine spray when other extinguishing media are not available.

#### SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS :

Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. Do not enter a confined space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus. During fire, irritating and toxic gases may be generated by thermal decomposition or combustion. Product reacts with water. Reaction may produce heat and / or gases.

---

### SECTION VI - ACCIDENTAL RELEASE MEASURES

---

#### SPILL OR LEAK PROCEDURES:

Remove all sources of ignition and ventilate the area. Dike and contain spilled material and control further spillage if feasible. Cover spill with clay, sand, saw dust, vermiculite, Fuller's earth or other suitable absorbent.

Collect material in non-leaking containers and seal tightly for disposal. Attempt to neutralize by adding a mixture of : water (80%) with non-ionic surfactant Tergitol TMN-10 (20%), OR water (90%), concentrated ammonia (3-8%) and detergent (2%). Add about 10 parts of neutralizer per part of Isocyanate while mixing, Allow to stand uncovered for 48 hours to let CO2 escape. If ammonia is used, use good ventilation to prevent vapor exposure. Large quantities may be pumped into closed , but not sealed containers. Refer to section 13 for disposal information.

---

---

## SECTION VII - HANDLING AND STORAGE

---

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Employee education and training in the safe use and handling of this material are required under the OSHA Hazard communication standard. Use with adequate ventilation.

**STORAGE:** Store indoors in a dry place away from heat between 65 to 85 °F. Keep containers tightly closed when not in use. Keep product from exposing to atmospheric moisture and maintain a nitrogen atmosphere in the containers at all times. Do not store product contaminated with water to prevent potential hazardous reaction. Refer to Section X of the MSDS for Reactivity and Stability data.

---

## SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**EYE PROTECTION:** Safety glasses, Chemical / splash goggles.

**SKIN PROTECTION:** Avoid contact with skin and clothing. Use permeation resistant gloves such as Butyl rubber, nitrile rubber or polyvinyl alcohol. However, please note that PVA degrades with water.

**RESPIRATORY PROTECTION:** Atmospheric levels should be maintained below the exposure guidelines. When respiratory protection is required for certain operations, use an approved positive pressure supplied - air respirator. Avoid breathing vapors which may be produced under some conditions such as heating or applications. Avoid breathing aerosols and mists. Use NIOSH / MSHA approved respiratory protection equipment when airborne exposure is excessive.

**VENTILATION :** Hazard control from vapor or spray mist is ideally performed by the use of engineering controls. MDI levels must be monitored.

---

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

---

**PHYSICAL FORM:** Liquid  
**COLOR:** light Amber  
**BOILING POINT:** 302 °F @ 5 mm Hg for MDI  
**WEIGHT PER GALLON:** 9.68 pounds  
**VAPOR PRESSURE:** < 10-5 mm Hg @ 77°F  
**VAPOR DENSITY:** 8.5 (MDI) (Air =1)  
**EVAPORATION RATE :** Not available  
(N-Butyl Acetate)  
**FLASH POINT :** >350°F (PMCC)  
**FLAMMABILITY LIMITS:** UEL % Not established  
LEL % Not established

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guarantee analysis of any specific lot or as specifications for the product.

---

## SECTION X - STABILITY AND REACTIVITY

---

**STABILITY:** Product is stable under normal conditions of storage and handling. Product is very Unstable when contaminated with water.

### CONDITIONS TO AVOID:

Avoid temperatures above 90°F. Avoid temperatures below 64°F. Avoid moisture. Product can decompose at Elevated temperature..

### MATERIALS TO AVOID:

Avoid contact with metals such as aluminum, brass, copper, galvanized metals, zinc. Reaction with water can generate carbon dioxide. Generation of gas can cause pressure build up in closed systems. Avoid contact with acids, alcohol, amines, ammonia, bases, metal compounds, moist air, strong oxidizers, and water. Avoid unintended contact with polyols.

**HAZARDOUS POLYMERIZATION :** Polymerization can occur which could be catalyzed by strong bases and water.

---

**DECOMPOSITION PRODUCTS :** By heat and fire: Carbon dioxide, carbon monoxide, Aldehydes, acids and other organic substances may be formed.

---

## SECTION XI - TOXICOLOGICAL INFORMATION

---

### ACUTE TOXICITY:

Oral LD50 : > 15,800 mg/Kg (Rat)  
Dermal LD50: > 5010 but < 7,940 mg/Kg (Rabbit)

Inhalation LC50: The 4 hour LC50 for polymeric MDI in rats ranges from 370 to 490 mg/m<sup>3</sup>. The LC50 For monomeric MDI was estimated to be between 172 and 187 mg/m<sup>3</sup>.

### MUTAGENICITY:

Positive (Salmonella micro some test with metabolic activation; cell transformation assay). As well as negative (mouse lymphoma specific locus mutation test with or without metabolic activation) results have been observed "in vitro". However, MDI was negative in an "in vivo" (mouse micronucleus) assay.

---

## SECTION XII - ECOLOGICAL INFORMATION

---

Data not available.

---

## SECTION XIII - DISPOSAL CONSIDERATIONS

---

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

---

## SECTION XIV - TRANSPORTATION INFORMATION

---

### DOMESTIC SURFACE (USA / DOT)

**PROPER SHIPPING NAME :** Not Regulated  
**HAZARD CLASS or DIVISION:** Not Applicable  
**UN / NA Number :** Not Applicable  
**PACKING GROUP :** PG III  
**DOT PRODUCT RQ, Lb.** 25000 lbs  
**HAZARD LABEL(S) :** Not Applicable  
**HAZARD PLACARD(S) :** Not Applicable

---

## SECTION XV - REGULATORY INFORMATION

---

**TSCA STATUS:** All ingredients in this products are listed in the T.S.C.A. inventory.

### CERCLA REPORTABLE QUANTITY:

5000 lbs for 4,4'-Diphenylmethane Diisocyanate , CAS # 101-68-8

### SARA TITLE III:

**SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE :** None

### SECTION 311 and 312 HAZARD CATEGORIES:

Under applicable definitions, the product is considered to meet following categories: An immediate health hazard, A delayed health hazard and a reactive hazard.

---

**SECTION 313 TOXIC CHEMICALS :**

4,4' -Diphenylmethane Diisocyanate  
Diphenylmethane Diisocyanate

CAS #: 101-68-8  
CAS #: 26447-40-5

< 99 % by weight  
< 10 % by weight

**RCRA :** If discarded in its purchased form, this product would not be a hazardous waste by listing. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste.

**CALIFORNIA PROPOSITION 65:** To the best of our knowledge this product does not contain any list of chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.

---

**SECTION XVI - OTHER INFORMATION**

---

**HMIS RATINGS:**

Health  
3

Flammability  
1

Reactivity  
1

**REASON FOR ISSUE :** Initial issuance of new document

## SAFETY DATA SHEET

### SECTION I - PRODUCT IDENTIFICATION

<b>PRODUCT NAME:</b>	MULTICOAT SPEEDBOND PART B	<b>PRODUCT CODE:</b>	MultiCoat SpeedBond-B
<b>PRODUCT CLASS:</b>	Polymeric Diisocyanate (MDI)	<b>CAS NUMBER:</b>	None
<b>COMPANY NAME:</b>	<b>ACCUMETRIC</b> 350 Ring Road <b>Elizabethown, KY 42701</b> 800-928-2677	<b>FOR EMERGENCY ASSISTANCE</b> <b>CONTACT CHEMTREC</b> <b>AT 1-800-424-9300</b>	

### SECTION II - HAZARDS IDENTIFICATION

Information In accordance with 29 CFR 1910.1200

**GHS Classification:**

Skin Irritation Category 2  
Eye irritation Category 2A  
Acute Toxicity Inhalation Category 3

**GHS Label elements:**  
Pictograms



Signal Word: Warning

**Hazard Statements:**

H315: Causes Skin Irritation  
H320: Causes eye irritation  
H335: May cause respiratory Irritation

**Precautionary Statements:**

P261: Do not breathe vapors, mist or spray  
P264: Wash thoroughly hands after handling  
P280: Wear eye and face protection. Wear protective gloves  
P301+P330+P331: If swallowed: Rinse mouth. Do not induce vomiting.  
P302+P352: If on Skin: Wash with plenty of soap and water  
P305+P351+P388: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do so. Continue rinsing.  
P332+P313: If skin irritation occurs :Get medical attention  
P337+P313: If eye irritation persists: Get medical attention  
P342+P311: If experiencing respiratory symptoms: Call a poison center or physician  
P404: Store in a well-ventilated place  
P232: Protect from moisture  
P233: Keep container tightly closed  
P501: Dispose of contents and /or container according to Federal State/Provincial and local governmental regulations.

### SECTION III - COMPOSITION / INFORMATION ON INGREDIENTS

<u>COMPONENT</u>	<u>CAS NO.</u>	<u>Weight</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>
NJTSRN-MULTICOAT SPEEDBOND-B	--	--	--	--

---

## SECTION IV - FIRST AID MEASURES

---

- SKIN CONTACT :** Remove contaminated clothing or shoes, wipe excess from skin and flush with plenty of water for at least 15 minutes. Use soap if available or follow by washing with soap and water. Do not reuse clothing until thoroughly cleaned.
- EYE CONTACT :** Flush eyes with plenty of water for at least 15 minutes while holding eyelids open and seek medical attention.
- INHALATION :** Remove victim to fresh air and provide oxygen if breathing is difficult. Give artificial respiration if not breathing and seek medical help immediately.
- INGESTION :** Do not give any liquids (do not induce vomiting) if victim is unconscious or very drowsy. Get medical help immediately.

---

## SECTION V - FIRE FIGHTING MEASURES

---

**EXTINGUISHING MEDIA:** Use Dry Chemical, Carbon Dioxide, Foam or Water Fog

**SPECIAL FIRE FIGHTING PROCEDURES AND PRECAUTIONS :**

Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. Do not enter a confined space without full bunker gear, including a positive pressure NIOSH approved self-contained breathing apparatus. During fire, irritating and toxic gases may be generated by thermal decomposition or combustion.

---

## SECTION VI - ACCIDENTAL RELEASE MEASURES

---

**SPILL OR LEAK PROCEDURES:**

Remove all sources of ignition and ventilate the area. Dike and contain spilled material and control further spillage if feasible. Cover spill with clay, sand, saw dust, vermiculite, Fuller's earth or other suitable absorbent. Collect material in non-leaking containers and seal tightly for disposal. Refer to section 13 for disposal information.

---

## SECTION VII - HANDLING AND STORAGE

---

Handle in accordance with good industrial hygiene and safety practices. These practices include avoiding unnecessary exposure and removal of the material from eyes, skin and clothing. Employee education and training in the safe use and handling of this material are required under the OSHA Hazard communication standard. Use with adequate ventilation.

**STORAGE:** Store indoors in a dry place away from heat, sparks and flame. Keep containers tightly closed when not in use.

---

## SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

---

**EYE PROTECTION:** Safety glasses, splash goggles

**SKIN PROTECTION:** Avoid contact with skin and clothing. Use chemical resistant protective gloves.

**RESPIRATORY PROTECTION:** Avoid breathing vapors which may be produced under some conditions such as heating. Avoid breathing aerosols and mists. Use NIOSH / MSHA approved respiratory protection equipment when airborne exposure is excessive.

**VENTILATION :** Hazard control from vapor or spray mist is ideally performed by the use of engineering controls. General or local ventilation or isolation may prove adequate to keep airborne exposures below exposure limits.

---

## SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

---

**PHYSICAL FORM:** Liquid  
**COLOR:** Gray  
**BOILING POINT:** Not available  
**SOLUBILITY:** Negligible (in water)  
**WEIGHT PER GALLON:** 8.73 pounds  
**VAPOR DENSITY:** Heavier than air  
**EVAPORATION RATE :** Not available  
(N-Butyl Acetate)  
**LIQUID DENSITY:** Higher than water  
**FLASH POINT :** >250 °F (PMCC)  
**FLAMMABILITY LIMITS:** UEL % Not established  
LEL % Not established  
**AUTO IGNITION TEMP.** Not established

Note: These physical data are typical values based on material tested but may vary from sample to sample. Typical values should not be construed as a guarantee analysis of any specific lot or as specifications for the product.

---

## SECTION X - STABILITY AND REACTIVITY

---

**STABILITY:** Product is stable under normal conditions of storage and handling.  
**CONDITIONS TO AVOID :** Moisture and high temperature  
**HAZARDOUS POLYMERIZATION :** Will not occur under normal storage conditions.  
**DECOMPOSITION PRODUCTS :** By heat and fire: Carbon dioxide, carbon monoxide, Aldehydes, acids and other organic substances may be formed.

---

## SECTION XI - TOXICOLOGICAL INFORMATION

---

Product is not toxic

---

## SECTION XII - ECOLOGICAL INFORMATION

---

Data not available.

---

## SECTION XIII - DISPOSAL CONSIDERATIONS

---

Waste must be disposed of in accordance with federal, state and local environmental control regulations. Incineration is the preferred method. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.

---

## SECTION XIV - TRANSPORTATION INFORMATION

---

**PROPER SHIPPING NAME :** Not Regulated by D.O.T.  
**HAZARD CLASS or DIVISION:** None  
**UN / NA Number :** N/A  
**PACKING GROUP :** PG III  
**DOT PRODUCT RQ, Lb.** None  
**HAZARD LABEL(S) :** None  
**HAZARD PLACARD(S) :** None

---



---

## SECTION XV - REGULATORY INFORMATION

---

**TSCA STATUS:** All ingredients in this products are listed in the T.S.C.A. inventory.

**CERCLA REPORTABLE QUANTITY:** None

**SARA TITLE III:**

<b>SECTION 302 EXTREMELY HAZARDOUS SUBSTANCE :</b>	None
<b>SECTION 311/312 HAZARD CATEGORIES:</b>	None
<b>SECTION 313 TOXIC CHEMICALS :</b>	None

**RCRA :**

If discarded in its purchased form, this product would not be a hazardous waste by listing. However, under RCRA, it is the responsibility of the product user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste. ( 40 CFR 261.20-24).

**CALIFORNIA PROPOSITION 65:** To the best of our knowledge this product does not contain any list of chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.

---

## SECTION XVI - OTHER INFORMATION

---

<b>HMIS RATINGS:</b>	Health	Flammability	Reactivity
	1	1	0

**REASON FOR ISSUE :** Initial Issuance of new product.