



A Fast Setting Hydraulic Cement for Repairing Cracks, Holes, and Other Damaged Concrete Surfaces.

DESCRIPTION & BASIC USE

Multicoat® SPEED MIX 2000 is a fast setting, resin modified, hydraulic cement. It is used by itself for most types of concrete repair such as leveling, filling cavities and cracks. Can be used interior or exterior, vertical, horizontal or overhead. It is also a specified component of other Multicoat® Systems.

COVERAGE:

One 50-lb pail will yield approximately 1/2 of a cubic foot. (996 cubic inches). Equates to an area 12" wide, x 12" long x 6.9" deep.

ADDITIONS:

Clean pea gravel can be added when filling deep (3" or greater) horizontal areas. Total volume of pea gravel can not exceed 25% of Speed Mix being used.

LIMITATIONS:

Do not apply if substrate temperature is below 40°F or above 100°F, or if ambient temperature below 40°F above 100°F.

Do not apply if precipitation is expected within a twenty four (24) hour period.

PACKAGING AND STORAGE:

SPEED MIX 2000 is packaged in 25-lb and 65-lb poly-lined bags, 50-lb pails, and 10-lb cans. Shelf life is approximately 24 months in unopened bags. Store in a dry environment.

WARRANTY:

Materials are guaranteed with respect to uniformity and quality within manufacturer's specifications. Seller makes no other warranty, expressed or implied, regarding the use of its products. Since use of the product is beyond seller's control, the buyer assumes all risks of use. Seller's sole obligation shall be to replace the material if found to be defective. Seller shall not be liable for any damages, injury, loss, direct or consequential, resulting from use of its products.



MIX SPEED MIX WITH WATER.

TEST DATA - SPEED MIX 2000

TEST	METHOD	RESULTS
Compressive Strength, PSI.....	1 Day	4400 psi
	28 Day	6300 psi
Flexural Strength, PSI	28 Day	1525 psi
Tensile Strength, PSI	28 Day	700 psi
Density, g/cc		1.97
Set Time (minutes).....	Initial	16
	Final	18
Shrinkage %	28 Day075%



MULTICOAT® CORPORATION

West Coast

Toll Free: (877) 685-8426
(949) 888-7100 Fax (949) 888-2555
Website: www.multicoat.com
E-mail: info@multicoat.com

MC311

MULTICOAT® PRODUCTS, INC.

East Coast

Toll Free: (800) 660-6729
(304) 586-0616 Fax (304) 586-0620
Website: www.multicoat.com
E-mail: info@multicoat.com

AVAILABLE THROUGH



SPEED MIX 2000

Polymer Modified Repair Mortar