



# A Polymer Modified Cementitious, Stampable Overlay Coating

# OVERLAY STAMP MIX

## DESCRIPTION & USE

Multicoat's OVERLAY STAMP MIX is a polymer modified cementitious coating used as an overlay on existing concrete surfaces to achieve a decorative stamp appearance

## ADVANTAGES:

- Single Component Packaging
- Easy to Apply
- Bonding Agent in the Bag
- Just Add Water
- High Compressive & Flexural Strength
- Superior Impact and Abrasion Resistance
- Weather and Freeze-Thaw Resistant
- Low Cost
- Environmentally Friendly
- Long Working Time
- Non Shrinking

## SEE TEST DATA

## BASIC USE:

OVERLAY STAMP MIX is a dry mix bagged material mixed with clean potable water on the jobsite, then spread to a consistent thickness to be stamped.

## COLOR:

OVERLAY STAMP MIX is white. Other colors available with custom orders.

## PACKAGING:

OVERLAY STAMP MIX is packaged in 65-lb bags.

## COVERAGE:

OVERLAY STAMP MIX will cover approximately 30 to 35 sq. ft. when spread to a thickness of 1/4", depending upon application, method of application, and substrate condition.

## SURFACE PREPARATION:

Substrate must be structurally sound, free from grease, oil, paint, dirt, dust, sealers. Laitance, curing compounds, and any other foreign material which may prevent proper bonding. A layer of Multicoat's SCRATCH KOTE 2000 must be applied to the substrate and allowed to dry prior to OVERLAY STAMP MIX application.



APPLY BASE COAT OF SCRATCH KOTE 2000 AS A BONDING AGENT.



MIX STAMP MIX WITH WATER, APPLY TO 1/4" THICK WITH GAUGE RAKE.



PLACE STAMPS INTO POSITION, MOVING AROUND THE AREA AS NEEDED.



APPLY MULTI-STAIN VIA PUMP UP SPRAYER, ALLOW TO DRY, THEN ROLL ON CLEAR SEAL TO PROTECT THE FINISH.



FINISHED OVERLAY STAMP SURFACE.

