

A Waterbase Below Grade Elastomeric Seamless Waterproofing Membrane.

GREEN
FRIENDLY
PRODUCTS!

DESCRIPTION & USE

BG 2000 is a unique Acrylic Waterbased coating which forms an elastomeric waterproofing membrane with excellent bonding characteristics to most building materials. Specifically designed for BELOW GRADE AND UNDERLAYMENT applications.

ADVANTAGES

- Low Cost - Minimum Down Time
- Ease of Application
- Superior Waterproofing
- Excellent Bond Strength
- High Tensile Strength and Elastomeric Properties
- Freeze-Thaw Resistant
- Waterbased - Environmentally Safe to Use and Apply

SEE TEST DATA

SURFACE PREPARATION

Substrate must be structurally sound and free from grease, oil, dirt, dust, sealers, water repellents and other foreign materials which may interfere with proper bonding. Shot blasting, sand blasting, or water sand blasting with minimum 3500 psi may be necessary over some surfaces to achieve proper bonding. On concrete block or slumpstone walls, all head and bed joints must be free of holes and finished flush with block substrate. For poured in place walls, a waterbase form release must be used. If an oil base release is used, it can be completely removed with trisodium phosphate (TSP), power washed and rinsed.

APPLICATION

Spray one (1) heavy coat or roll two (2) coats of MULASTICOAT® BG 2000 over area to be waterproofed at a coverage rate of 35-45 sq. ft. per gallon. Allow to dry, then backfill. Always use a drainage system at bottom of footing of retaining wall. MULTICOAT'S LASTO DRAIN or equivalent is recommended.

**FOR BELOW GRADE AND UNDERLAYMENT
WATERPROOFING USE ONLY**

LIMITATIONS

Do not apply if substrate temperature is below 40°F and falling, above 100°F and rising, or if precipitation is expected within a twenty four (24) hour period after each coat.

Do not use if substrate is subject to negative side water or water vapor pressure.

COVERAGE

35-45 sq. ft. per gallon, one coat. (Coverage may vary due to application method and/or substrate condition.)



5 GALLON BUCKET



55 GALLON DRUM



275 GALLON TOTE

ENVIRONMENTALLY SAFE, WATERBASE
AVAILABLE IN 5 GALLON BUCKETS, 55
GALLON DRUMS & 275 GALLON TOTES



BG 2000 CAN BE APPLIED BY SPRAYER,
HOPPER GUN, ROLLER OR BRUSH



READY FOR BACKFILL

BG 2000
Below Grade Waterproofing

