

CITRIC Acid

- Removes metal stains from pool liners and finishes
- Works great on steps



WARNING:

HARMFUL IF SWALLOWED. SKIN AND EYE IRRITANT. KEEP OUT OF REACH OF CHILDREN. READ CAREFULLY OTHER CAUTIONS ON THE REVERSE PANEL.

NET CONTENTS: 1.75 LBS

STAINfree[™]

Directions for use:

Note: Operating the pool for a couple of days without chlorine can create an algae concern. Follow pool dealer's recommendations on steps to take to protect the pool from algae during this metal stain removal process.

- 1. Balance pool water chemistry before using **STAINfree**: pH: 7.2-7.6, Alkalinity: 80-120ppm, Calcium Hardness: 200-400ppm, CYA: below 50ppm, Phosphates: below 100ppb.
 - Note: Stain removal products work best when the pH is on the lower side of acceptable range (7.2)
- 2. **IMPORTANT:** Before starting the metal stain removal or water discoloration process (step 4), a pulp based filter aid must be added to cartridge and sand filters. DE filters must be properly charged.
- 3. Lower chlorine level to 1ppm or less (a high chlorine level or adding oxidizing agents during the process will prevent **STAINfree** from working as designed).
- 4. For Surface Staining: If the surface is stained, add 1lb of **STAINfree** per 10,000 gallons as close to the stained area(s) as possible with the pump off overnight.

For Water Discoloration: If the entire body of water is discolored, put the pool on recirculate, add 1lb of **STAINfree** per 10,000 gallons to the pool evenly around the edge. Let the circulation run for one hour. After one hour, shut the pump off and let sit overnight.

Note: For use in swimming

pools only.

- 5. Before turning the pump back on, brush the pool walls and floor thoroughly.
- 6. Turn the pump back on and add **METALfree**™ to the pool water evenly around the edge at a rate of 33.9oz per 20,000 gallons.
- 7. With the pump still on, vacuum the pool walls and floor very thoroughly.
- 8. After vacuuming, clean filters: Sand filter- backwash for at least 3 minutes and then rinse for 2 minutes. Cartridge filter- clean filter and filter tank thoroughly. DE filterbackwash and recharge with DE.
- 9. Test and rebalance water. DO NOT SHOCK THE POOL FOR AT LEAST 1 WEEK.

Note: If chlorine level is low after the STAINfree treatment. add small amounts of chlorine. Do not exceed 2ppm.

For salt generator pools: a granular shock is recommended instead of turning the generator to its boost (superchlorinate) function after the recommended 1 week.

10. Use **METALfree**™ as a weekly maintenance to control future metal staining. Apply 4oz per 10,000 gallons once a week.

Do not swim until stain procedure is complete and normal chlorine residual is established.

WARNING: Avoid contact with eyes and skin. Do not swallow. Wear rubber gloves and safety glasses. Keep out of reach of children. Contains: Citric acid. **FIRST AID:**

If ingested: Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately. If in eyes: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists. If on skin: Wash with plenty of water. If skin irritation occurs, get medical advice/attention. Take off contaminated clothing and wash it before reuse. If breathing is difficult: Remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

NC Brands L.P.

40 Richards Ave. Norwalk, CT 06854 800-753-1233 www.naturalchemistry.com A North American Company

07400111601

