



Size (in)	Part Numbers	
	Stainless Steel Disc	Nylon Coated Disc
2	518020RO37	516020R037
2 1/2	518025RO37	516025R037
3	518030RO37	516030R037
4	518040RO37	516040R037
5	N/A	516050R037
6	518060RO37	516060R037
8	518080RO37	516080R037

Size		Dimensions with hand lever – All dimensions are in inches							
in	mm	A	B	C	D	Ø E	F	G	H
2	50	12 5/8	3 1/4	5 1/2	3 7/8	4	1 3/4	8 11/16	1 3/4
2 1/2	65	13 9/16	3 5/8	6	3 7/8	4 13/16	1 3/4	8 11/16	1 7/8
3	80	14 1/8	3 7/8	6 1/4	3 7/8	5 1/2	1 3/4	8 11/16	1 7/8
4	100	15 1/2	4 3/8	7	3 7/8	6 1/4	1 3/4	12 5/8	2 1/16
5	125	16 5/8	5	7 1/2	3 7/8	7 7/16	1 3/4	12 5/8	2 1/4
6	150	17 7/8	5 5/8	8	3 7/8	8 7/16	1 3/4	12 5/8	2 1/4
8	200	20 1/4	6 3/4	9 5/8	3 7/8	10 5/8	1 3/4	16 9/16	2 3/8

R-5/5/11

## **VALVES - GENERAL - DOMINION**

- A. All valves 3”–12” shall be constructed with cast aluminum ASTM S12A housing and fully coated with Rilsan on all interior and exterior surfaces. Internal components include EPDM resilient lining, Rilsan coated ductile iron disc and T304 stainless steel shaft. Valves 14” and larger shall be constructed with cast iron housing epoxy coated and with nylon coated ductile iron disc.
- B. Valves shall be Dominion butterfly valves and shall be provided for strainer isolation, filter bypass, backwash throttling, filtered water return and balance tank connections.
- C. Valves shall be suitable for freshwater, saltwater and submerged applications.