

SAFETY DATA SHEET

1. Product and Company Identification

| | |
|--------------------------------------|---|
| Product identifier | Pump Protector 4299-T8 |
| Other means of identification | Not available |
| Recommended use | Protectant |
| Recommended restrictions | None known. |
| Manufacturer | Nu-Calgon 2008 Altom Court St. Louis, MO 63146 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC) |

2. Hazards Identification

| | | |
|------------------------------|-----------------------------------|---------------|
| Physical hazards | Flammable aerosols | Category 2 |
| | Gases under pressure | Liquefied gas |
| Health hazards | Serious eye damage/eye irritation | Category 1 |
| Environmental hazards | Not classified. | |
| OSHA defined hazards | Not classified. | |

Label elements



Signal word Danger

Hazard statement Flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes serious eye damage.

Precautionary statement

- Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wear eye/face protection.
- Response** If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor.
- Storage** Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.
- Disposal** Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 53% of the mixture consists of component(s) of unknown acute inhalation toxicity. 17% of the mixture consists of component(s) of unknown acute oral toxicity.

3. Composition/Information on Ingredients

Mixture

| Chemical name | Common name and synonyms | CAS number | % |
|---|--------------------------|------------|-------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin | | 64742-65-0 | 10-30 |
| Propane | | 74-98-6 | 10-30 |
| Residual oils (Petroleum), solvent-dewaxed | | 64742-62-7 | 10-30 |
| 1,2-Propanediol | | 57-55-6 | 1-5 |
| Alcohols, C12-14-secondary, ethoxylated | | 84133-50-6 | 1-5 |
| Ethanol, 2,2",2'''-nitrotris- | | 102-71-6 | 1-5 |
| Isobutane | | 75-28-5 | 1-5 |

| Chemical name | Common name and synonyms | CAS number | % |
|-----------------------------|--------------------------|------------|---------|
| Octadecanoic acid | | 57-11-4 | 1-5 |
| Alcohols C12-14 ethoxylated | | 68439-50-9 | 0.1-1.5 |

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.

4. First Aid Measures

| | |
|---|---|
| Inhalation | If symptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. If breathing has stopped, trained personnel should administer CPR immediately. |
| Skin contact | Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists. |
| Eye contact | If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. |
| Ingestion | In the unlikely event of swallowing contact a physician or poison control center. Rinse mouth. Do not induce vomiting. Never give anything by mouth if victim is unconscious, or is convulsing. Obtain medical attention. |
| Most important symptoms/effects, acute and delayed | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. If you feel unwell, seek medical advice (show the label where possible). Show this safety data sheet to the doctor in attendance. Do not puncture or incinerate container. Do not store at temperatures above 49°C. Keep away from sources of ignition. No smoking. Avoid contact with eyes and skin. Keep out of reach of children. |

5. Fire Fighting Measures

| | |
|--|--|
| Suitable extinguishing media | Carbon dioxide. Dry chemical. Foam. |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. Cool containers with flooding quantities of water until well after fire is out. |
| Special protective equipment and precautions for firefighters | Firefighters should wear full protective clothing including self contained breathing apparatus. |
| Fire-fighting equipment/instructions | In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Flammable aerosol. |
| Hazardous combustion products | May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. |
| Explosion data | |
| Sensitivity to mechanical impact | Not available. |
| Sensitivity to static discharge | Not available. |

6. Accidental Release Measures

| | |
|--|--|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep out of low areas. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
|--|--|

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. Prevent entry into waterways, sewers, basements or confined areas.

Environmental precautions

Prevent further leakage or spillage if safe to do so.
Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

7. Handling and Storage

Precautions for safe handling

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using do not eat or drink. Wash hands before breaks and immediately after handling the product.

Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

| Components | Type | Value | Form |
|--|------|-----------------------------------|-------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | PEL | 5 mg/m ³ | Mist. |
| | | 2000 mg/m ³ 500 ppm | |
| Propane (CAS 74-98-6) | PEL | 1800 mg/m ³ | |
| | | 1000 ppm | |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|--|------|----------------------|---------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | TWA | 5 mg/m ³ | Inhalable fraction. |
| Ethanol, 2,2",2'''-nitrilotris- (CAS 102-71-6) | TWA | 5 mg/m ³ | |
| Isobutane (CAS 75-28-5) | STEL | 1000 ppm | |
| Octadecanoic acid (CAS 57-11-4) | TWA | 10 mg/m ³ | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value | Form |
|--|------|-----------------------------------|-------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | STEL | 10 mg/m ³ | Mist. |
| | | | |
| Isobutane (CAS 75-28-5) | TWA | 5 mg/m ³ | Mist. |
| | | 1900 mg/m ³ 800 ppm | |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m ³ | |
| | | 1000 ppm | |

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value | Form |
|-------------------------------|------|----------------------|----------|
| 1,2-Propanediol (CAS 57-55-6) | TWA | 10 mg/m ³ | Aerosol. |

| | |
|--|---|
| Biological limit values | No biological exposure limits noted for the ingredient(s). |
| Exposure guidelines | Chemicals listed in section 3 that are not listed here do not have established limit values for ACGIH. |
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| Hand protection | Rubber gloves. Confirm with a reputable supplier first. |
| Other | As required by employer code. Wear appropriate chemical resistant clothing. |
| Respiratory protection | Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. |
| Thermal hazards | Not applicable. |
| General hygiene considerations | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Handle in accordance with good industrial hygiene and safety practice. |

9. Physical and Chemical Properties

| | |
|---|--|
| Appearance | Clear |
| Physical state | Gas. |
| Form | Foam Aerosol |
| Color | Colorless |
| Odor | Characteristic |
| Odor threshold | Not available. |
| pH | 8.5 - 9.5 |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | 212 °F (100 °C) |
| Pour point | Not available. |
| Specific gravity | 0.96 - 1 |
| Partition coefficient (n-octanol/water) | Not available. |
| Flash point | Not available. |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not applicable. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | Not available. |
| Flammability limit - upper (%) | Not available. |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 30 - 40 psig @ 20°C |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | Not available. |
| Auto-ignition temperature | Not available. |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Flammability | Flame Height: 13cm, Duration 4-5 seconds |
| Heat of combustion | Level 1 |
| Percent volatile | 95 |

10. Stability and Reactivity

| | |
|---|--|
| Reactivity | This product may react with strong oxidizing agents. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Chemical stability | Stable under recommended storage conditions. |
| Conditions to avoid | Do not mix with other chemicals. Aerosol containers are unstable at temperatures above 49°C (120.2°F). |
| Incompatible materials | Strong oxidizing agents. Oxidizers. |
| Hazardous decomposition products | May include and are not limited to: Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. |

11. Toxicological Information

| | |
|---|---|
| Routes of exposure | Eye, Skin contact, Inhalation, Ingestion. |
| Information on likely routes of exposure | |
| Ingestion | Expected to be a low ingestion hazard. |
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans. |
| Eye contact | Causes serious eye damage. |
| Symptoms related to the physical, chemical and toxicological characteristics | Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. |

Information on toxicological effects

Acute toxicity

| Components | Species | Test Results |
|--|---------------|--------------|
| 1,2-Propanediol (CAS 57-55-6) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 20800 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Dog | 19000 mg/kg |
| | Guinea pig | 184000 mg/kg |
| | Mouse | 23900 mg/kg |
| | Rabbit | 14800 mg/kg |
| | Rat | 20000 mg/kg |
| Alcohols C12-14 ethoxylated (CAS 68439-50-9) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 2700 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Rat | 9800 mg/kg |
| Alcohols, C12-14-secondary, ethoxylated (CAS 84133-50-6) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 3177 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Rat | 3250 mg/kg |

| Components | Species | Test Results |
|--|---------------|---------------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | >= 5000 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Rat | 2.2 mg/l/4h |
| <i>Oral</i> | | |
| LD50 | Rat | >= 5000 mg/kg |
| Ethanol, 2,2',2'''-nitrotris- (CAS 102-71-6) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | >= 2000 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Not available | |
| <i>Oral</i> | | |
| LD50 | Guinea pig | 2200 mg/kg |
| | Mouse | 5846 mg/kg |
| | Rabbit | 2200 mg/kg |
| | Rat | 5530 mg/kg |
| Isobutane (CAS 75-28-5) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Not available | |
| <i>Inhalation</i> | | |
| LC50 | Rat | 658 mg/l/4h |
| <i>Oral</i> | | |
| LD50 | Not available | |
| Octadecanoic acid (CAS 57-11-4) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rabbit | 5000 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | | |
| <i>Oral</i> | | |
| LD50 | Rat | 5000 mg/kg |
| | | 4.6 g/kg |
| <i>Other</i> | | |
| LD50 | Mouse | 23 mg/kg |
| | Rat | 21.5 mg/kg |
| Propane (CAS 74-98-6) | | |
| Acute | | |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 1442.8 mg/l, 15 Minutes |
| <i>Oral</i> | | |
| LD50 | Not available | |
| Residual oils (Petroleum), solvent-dewaxed (CAS 64742-62-7) | | |
| Acute | | |
| <i>Dermal</i> | | |
| LD50 | Rat | > 2000 mg/kg |
| <i>Inhalation</i> | | |
| LC50 | Rat | > 2180 mg/m3, 4 hours |

| Components | Species | Test Results |
|--|--|---------------------------|
| <i>Oral</i> LD50 | Rat | 2 mg/l/4h > 5000 mg/kg |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. | |
| Exposure minutes | Not available. | |
| Erythema value | Not available. | |
| Oedema value | Not available. | |
| Serious eye damage/eye irritation | Causes serious eye damage. | |
| Corneal opacity value | Not available. | |
| Iris lesion value | Not available. | |
| Conjunctival reddening value | Not available. | |
| Conjunctival oedema value | Not available. | |
| Recover days | Not available. | |
| Respiratory or skin sensitization | | |
| Respiratory sensitization | Not available. | |
| Skin sensitization | This product is not expected to cause skin sensitization. | |
| Germ cell mutagenicity | Non-hazardous by WHMIS/OSHA criteria. | |
| Mutagenicity | Non-hazardous by WHMIS/OSHA criteria. | |
| Carcinogenicity | See below. Contains < 3% (w/w) DMSO-extract | |
| ACGIH Carcinogens | | |
| Octadecanoic acid (CAS 57-11-4) | A4 Not classifiable as a human carcinogen. | |
| IARC Monographs. Overall Evaluation of Carcinogenicity | | |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | Volume 33, Supplement 7, Volume 100F 1 Carcinogenic to humans. | |
| Ethanol, 2,2",2""-nitritoltris- (CAS 102-71-6) | Volume 77 - 3 Not classifiable as to carcinogenicity to humans. | |
| US NTP Report on Carcinogens: Known carcinogen | | |
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | Known To Be Human Carcinogen. | |
| Reproductive toxicity | Non-hazardous by WHMIS/OSHA criteria. | |
| Teratogenicity | Non-hazardous by WHMIS/OSHA criteria. | |
| Specific target organ toxicity - single exposure | Not classified. | |
| Specific target organ toxicity - repeated exposure | Not classified. | |
| Aspiration hazard | Not likely, due to the form of the product. | |
| Chronic effects | Prolonged inhalation may be harmful. May be harmful if absorbed through skin. Prolonged exposure may cause chronic effects. Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans. | |
| Further information | Not available. | |
| Name of Toxicologically Synergistic Products | Not available. | |

12. Ecological Information

| Components | Species | Test Results |
|--------------------------------------|---------|--|
| Ecotoxicity See below | | |
| 1,2-Propanediol (CAS 57-55-6) | | |
| Crustacea | EC50 | Daphnia 10000 mg/L, 48 Hours |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Daphnia magna) > 10000 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) 710 mg/l, 96 hours |

| Components | Species | Test Results |
|--|----------------|--------------------------------------|
| Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) | | |
| Crustacea | EC50 | Daphnia |
| | | 1000 mg/L, 48 Hours |
| Ethanol, 2,2',2'''-nitrotris- | (CAS 102-71-6) | |
| Algae | IC50 | Algae |
| | | 216 mg/L, 72 Hours |
| Aquatic | | |
| Crustacea | EC50 | Water flea (Ceriodaphnia dubia) |
| | | 565.2 - 658.3 mg/l, 48 hours |
| Fish | LC50 | Fathead minnow (Pimephales promelas) |
| | | 10610 - 13010 mg/l, 96 hours |
| Residual oils (Petroleum), solvent-dewaxed (CAS 64742-62-7) | | |
| Crustacea | EC50 | Daphnia |
| | | 1000 mg/L, 48 Hours |

| | |
|--------------------------------------|---|
| Persistence and degradability | No data is available on the degradability of this product. |
| Bioaccumulative potential | No data available. |
| Mobility in soil | No data available. |
| Mobility in general | Not available. |
| Other adverse effects | No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component. |

13. Disposal Considerations

| | |
|--|---|
| Disposal instructions | Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Local disposal regulations | Dispose in accordance with all applicable regulations. |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers. |

14. Transport Information

U.S. Department of Transportation (DOT)

Basic shipping requirements:


| | |
|-----------------------------|--|
| UN number | UN1950 |
| Proper shipping name | Aerosols, flammable, (each not exceeding 1 L capacity) |
| Hazard class | Limited Quantity - US |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

| | |
|-----------------------------|---------------------------|
| UN number | UN1950 |
| Proper shipping name | AEROSOLS, flammable |
| Hazard class | Limited Quantity - Canada |
| Special provisions | 80, 107 |
| Packaging exceptions | <1L - Limited Quantity |

DOT; TDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the SDS contains all the information required by the Controlled Products Regulations.

Canada DSL Challenge Substances: Listed substance

Isobutane (CAS 75-28-5) Listed.

Canada NPRI VOCs with Additional Reporting Requirements: Mass reporting threshold/Identification Number

Isobutane (CAS 75-28-5) 1 TONNES
Propane (CAS 74-98-6) 1 TONNES

Canada WHMIS Ingredient Disclosure: Threshold limits

1,2-Propanediol (CAS 57-55-6) 1 %
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) 1 %
Ethanol, 2,2",2""-nitrilotris- (CAS 102-71-6) 1 %
Octadecanoic acid (CAS 57-11-4) 1 %

WHMIS status Controlled

WHMIS classification Class A - Compressed Gas, Class B - Division 5 - Flammable Aerosol, Class D - Division 2B

WHMIS labeling



US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US CAA Section 111 Volatile Organic Compounds: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.

US CAA Section 112(r) Accidental Release Prevention - Regulated Flammable Substance: Listed substance

Isobutane (CAS 75-28-5) Regulated flammable substance.
Propane (CAS 74-98-6) Regulated flammable substance.

US CAA Section 112(r) Accidental Release Prevention: Threshold quantity

Isobutane (CAS 75-28-5) 10000 LBS
Propane (CAS 74-98-6) 10000 LBS

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

US CAA Section 612 SNAP Program: Listed substance

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Propane (CAS 74-98-6) Listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Safe Drinking Water Act (SDWA) Not regulated.

Food and Drug Administration (FDA)

Not regulated.

US state regulations

This product does not contain a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Not listed.

US - Illinois Chemical Safety Act: Listed substance

Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US - Louisiana Spill Reporting: Listed substance

Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Ethanol, 2,2',2'''-nitritoltris- (CAS 102-71-6) Listed.
Isobutane (CAS 75-28-5) Listed.
Octadecanoic acid (CAS 57-11-4) Listed.
Propane (CAS 74-98-6) Listed.

US - New Jersey RTK - Substances: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
Ethanol, 2,2',2'''-nitritoltris- (CAS 102-71-6) Listed.
Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US - Texas Effects Screening Levels: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
Alcohols, C12-14-secondary, ethoxylated (CAS 84133-50-6) Listed.
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Ethanol, 2,2',2'''-nitritoltris- (CAS 102-71-6) Listed.
Isobutane (CAS 75-28-5) Listed.
Octadecanoic acid (CAS 57-11-4) Listed.
Propane (CAS 74-98-6) Listed.
Residual oils (Petroleum), solvent-dewaxed (CAS 64742-62-7) Listed.

US. Massachusetts RTK - Substance List

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
Ethanol, 2,2',2'''-nitritoltris- (CAS 102-71-6) Listed.
Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US. Pennsylvania RTK - Hazardous Substances

1,2-Propanediol (CAS 57-55-6) Listed.
Ethanol, 2,2',2'''-nitritoltris- (CAS 102-71-6) Listed.
Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

US. Rhode Island RTK

Isobutane (CAS 75-28-5) Listed.
Propane (CAS 74-98-6) Listed.

Inventory status


| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---|------------------------|
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

| LEGEND | |
|----------|---|
| Severe | 4 |
| Serious | 3 |
| Moderate | 2 |
| Slight | 1 |
| Minimal | 0 |

| | | |
|---------------------|---|---|
| HEALTH | / | 2 |
| FLAMMABILITY | | 1 |
| PHYSICAL HAZARD | | 0 |
| PERSONAL PROTECTION | | X |



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

01-June-2015

Effective date

01-June-2015

Expiry date

01-June-2018

Further information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

This SDS conforms to the ANSI Z400.1/Z129.1-2010 Standard. This Safety Data Sheet was prepared to comply with the current OSHA Hazard Communication Standard (HCS) adoption of the Globally Harmonized System of Classification and Labeling of Chemicals (GHS).