



DEVELOPED BY
ANCHOR
DIAMOND
WALL INDUSTRY EXPERTS



DIAMOND PRO[®]

RETAINING WALL STRAIGHT SPLIT FACE

A PROVEN BLOCK FOR LARGE
SCALE PROJECTS IN SERVICE
SINCE 1999.

✓ FEATURES & BENEFITS

- Walls in excess of 50 feet high have been built with the Diamond Pro system when combined with geosynthetic reinforcement*
- ASTM C1372 – compliant
- ICC evaluated
- Supported by Anchorwall[®] design software and estimating tools
- Large open cores for ease of handling and drainage aggregate placement during installation
- Compatible fittings/accessories

H X W X D**	8" X 18" X 12"
WEIGHT*	74 LBS.
COVERAGE	1 SQ. FT.
SETBACK & BATTER	1" PER COURSE; 7.1°
MAX. GRAVITY WALL HT.**	4 FT.
MIN. OUTSIDE RADIUS†	4 FT.
MIN. INSIDE RADIUS††	6 FT.

* See Installation Guide. Reinforced walls, and other critical walls, must be designed by qualified engineers

**Dimensions and Weights may differ slightly from manufacturer to manufacturer

‡The maximum gravity wall height is project specific and may be lower than this height

†Measured on the top course to the front of the wall

††Measured on the base course to the front of the wall



ANCHOR
DIAMOND

ANCHOR DIAMOND Group
5909 Baker Rd. Suite 550
Minnetonka, MN 55345
📞 1-952-933-8855

For more info visit
anchordiamond.com



©2023 ANCHOR DIAMOND Group. All rights reserved.
AD23-001-DIAMOND PRO STRAIGHT FACE