# DIAMOND PRO® AIR SMOOTH



## RETAINING

A smooth face and crisp edges offer a clean, eye-catching look for contemporary retaining and terraced walls.







SCANDINA GRAY

ANTHRACITE









## PALLET INFORMATION

	DIAMOND PRO® AIR SMOOTH	SQFT/ PALLET	SQFT/ LAYER	LAYER/ PALLET	UNITS/ Pallet	WEIGHT/ Pallet
ВГОСК	8 x 18 x 11½	36	1	-	36	2004
CORNER	8 x 18 x 9	-	-	-	24	2080
CAP	4 x 18/12 x 13	-	-	-	54	3260

Downloadable professional resources available at **Belgard.com/Resources** 

#### **QUALITY FOR LIFE**

Every step of our manufacturing process incorporates rigorous research, testing and quality assurance. We demand the highest quality from each of our facilities across North America. We believe in creating world class building products that stand the test of time. See our lifetime warranty at **Belgard.com/Warranty** 

## FEATURES & BENEFITS

- Can be installed as a gravity wall or geogrid-reinforced wall.
- Weighing only 54 lbs., this 1 square foot block maximizes installation and shipping efficiencies
- Front lug design produces a 9/16" per unit setback for a 4° system batter
- · Cores align for easy filling
- Top course is placed upside down in order to increase capping efficiency
- Ideally situated for retaining walls up to 12 feet tall
- Can be used to build gravity walls up to 3'
  4" high\*, including the buried course
- Minimum outside radius, measured on the top course to the front of the units: 4 feet
- Minimum inside radius, measured on the base course to the front of the units: 6 feet

\*Gravity wall heights are based on project specific conditions and may be lower than this value.

### SHAPES & SIZES

BLOCK



8 x 18 x 11½

CORNER



8 x 18 x 9

4" CAP



4 x 18/12 x 13

View the product page on **Belgard.com** for more information

