



RUBBER TILE SPACERS

UPDATE

February 28, 2023

Make sure that you have an up-to-date technical data sheet in hand by consulting our website: techniseal.com

U.S.A. and Canada: dial 1 800 465-7325

Others: dial (514) 523-8324 (Canada)

APPLICATIONS

- Patios, walkways and pool decks.
- Perfect for porcelain tiles
- Ideal for use over NextBase™ panel base system
- Can be used both indoor and outdoor

PROPERTIES

- Noise reduction properties
- Guarantees even space gaps between tiles
- 3" (7,62 cm) diameter
- Spacing width: 3/16" (5 mm)
- Save time & effort on tile installations
- Provides added stability
- Made of superior quality rubber material

DESCRIPTION

Made of superior quality materials, Techniseal's professional grade tile rubber spacers will guarantee even-leveled installations and uniform space gaps between each tile. Providing optimal stability, their high-quality rubber confection also grants them noise reduction properties. Contractors can now save time and effort while delivering the same high-quality results.

DIRECTIONS

BEFORE YOU BEGIN

Before proceeding with the installation, make sure you have an up-to-date technical data sheet in hand visiting techniseal.com.

- Install tiles on spacers.
- Make sure the edges of each tile are well positioned against the tab of each spacer to ensure equal joint width.



NECESSARY TOOLS:

- Utility knife

STORAGE

Store in a cool, dry place.

PACKAGING

Product Code	Diameter	Units per box	Boxes per pallet	Units per pallet
70971151	3" / 7,62 cm	100	168	16,800

WARNING

Wear appropriate safety gears. For more information and advice on the proper handling, storage, and disposal of this product, please refer to the latest version of its Safety Data Sheet (SDS). This official document contains physical, ecological, and other important information pertaining to the safe usage of this product. Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN

TRANSPORT

For more information and advice on the proper handling and transportation of this product, please refer to the latest version of its Safety Data Sheet (SDS). Visit www.techniseal.com or call 1-800-465-7325 to request or find an up-to-date version of this product's Safety Data Sheet (SDS).

LIMITED WARRANTY

Having no control over the use of the products, Techniseal® does not guarantee finished work. Replacement of any defective product shall be the buyer's sole remedy under this warranty. A proof of purchase will be required for any claim. Before using this product, user shall determine the suitability of the product for its intended use, and user alone assumes all risks and liability whatsoever in connection therewith. User shall test product in a small inconspicuous area (approx. 4 sq. ft.) under projected conditions of use. In the event that no test was carried out, the warranty will only apply to 4 sq. ft. This limited warranty excludes any liability for any consequential, incidental, indirect or special damages. Except for the limited warranty described above, manufacturer specifically disclaims and excludes any other express warranty, any implied warranty of merchantability of goods, and implied warranty of fitness of goods for any particular purpose.