



# Paint, Tar and Rubber Remover



(141-541 / 1L)

#### **UPDATE**

#### June 15, 2016

Make sure that you have an up-to-date technical data sheet in hand by consulting our Web site: techniseal.com Canada and U.S.A.: dial 1 800 465-7325 Others: dial (514) 523-8324 (Canada)

#### **APPLICATIONS**

• Pavers, slabs concrete and masonry.

#### **DESCRIPTION**

Techniseal® Paint, Tar and Rubber Remover for pavers effectively dissolves paint, tar or bitumen, rubber and chewing gum on pavers, slabs, concrete and masonry.

#### **DIRECTIONS**

#### **BEFORE YOU BEGIN**

• Wear adequate protective clothing. • **ALWAYS TEST** on a small hidden area to ensure that result meets your expectations. • Surface should, ideally, be warm to the touch.

#### **APPLICATION**

Cover stain generously with Remover and let work for 5 to 10 minutes. Reapply product and, using a small nylon scrub brush such as the Techniseal Stain remover brush (145-910), scrub until stain is dissolved. **DO NOT** let dry; rinse immediately.

NOTE: This product dissolves any sealant; apply a new coat of sealant on stripped surface.

## **PACKAGING**

| Product code | Size | Units per box | Units per pallet |
|--------------|------|---------------|------------------|
| 141-541      | 1 L  | 6             | 480              |

#### **WARNING**

**CONTENTS HARMFUL. MAY IRRITATE EYES. MAY IRRITATE SKIN.** Do not swallow. Do not get in eyes. Do not get on skin or clothing. Keep away from flames or sparks. **KEEP OUT OF REACH OF CHILDREN.** Wear protective gloves and eye/face protection. **FIRST AID TREATMENT Contains:** Solvent naphtha (petroleum), light arom.; 1,2,4-Trimethylbenzene; N-Methyl-2- pyrrolidone; Dimethyl glutarate; Dimethyl adipate; Acetone; Glycols, polyethylene, Mono(p- (1,1,3,3-tetramethylbutyl)phenyl) ether. If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water.

#### **SHIPPING**

### Land

Transported in limited quantity

## Sea

UN1993

Flammable liquid, n.o.s. (1,2,4-Trimethylbenzene)

Class: 3 PG: III

#### **LIMITED WARRANTY**

Techniseal® warranties this Remover against manufacturing defects. As Techniseal® has no control over surface preparation and product application, results cannot be guaranteed. The Techniseal® warranty is limited only to the replacement of a product proven to be defective, and will never cover the cost of labour. A proof of purchase will be required for any claim.