

CITYSTONE™ DEMI 60MM


PRODUCT NUMBER # 363



- Smooth surfaces and classical chamfers define each stone to create texture and visual structure with timeless appeal
- Designed to be installed in an efficient repeating runner or ashlar pattern, with equal numbers of 1/2, square, and 3/2 stones
- Light vehicular applications
- Demi and Supra can be combined to create a six-piece system with expansive, industry-leading scale
- Made of durable concrete with iron oxide pigments which helps prevent fading from extended UV exposure.

The CityStone series shares a generative architectural look in which pavement's scale is defined by the joint pattern. Joints and surfaces conform to US Access Board ADA surface requirements. The CityStone units yield unlimited creative control with access to other modulating CityStone shapes, color and textures to satisfy the architectural design intent. Made of durable concrete with iron oxide pigments which helps prevent fading from extended UV exposure. Meets or exceeds applicable requirements of ASTM C936 - Standard Specification for Solid Concrete Interlocking Paving Units and ASTM C1782 - Standard Specification for Segmental Concrete Paving Slabs. Smooth surfaces and classical chamfers define each stone to create texture and visual structure with timeless appeal. Square shapes easily form stacked and runner bond patterns.

STONE(S)



		4x8	8x8	8x12
Height	<i>in</i>	2.36	2.36	2.36
	<i>mm</i>	60	60	60
Length	<i>in</i>	3.94	7.87	11.81
	<i>mm</i>	100	200	300
Width	<i>in</i>	7.87	7.87	7.87
	<i>mm</i>	200	200	200
Units	<i>/pl</i>	80	80	80

PALLET INFO

Pallet Weight	2884 lbs
Sq Ft/Pallet	103 sq.ft.