

ONE COAT FIBERGLASS REINFORCED

An alkali resistant fiberglass reinforced stucco designed for use in one-coat stucco applications. Available in a sanded version requiring only the addition of water or a concentrated version which requires the addition of clean plaster sand and water.

Features& benefits include:

- · Crack resistant formula
- · Extended board life
- 1 hour fire rating over plywood or OSB & EPS foam when applied in accordance with ICC ESR-1240
- Superior workability

Package Size	Metric	Quantity
80 lb. bag	36.2 kg	42/pallet
80 lb. bag	36.2 kg	42/pallet
90 lb. bag	40.8 kg	35/pallet
	80 lb. bag 80 lb. bag	80 lb. bag 36.2 kg 80 lb. bag 36.2 kg

	BASE COAT British the Capp of Base Final Busine Capp		
BASE COM-	T 2113		

BASE COAT STUCCO

A Portland cement based stucco used for construction and repair of stucco walls. Available in Extended Board- Life formulation.

Use For:

- · Scratch and brown coat in a three coat stucco application
- Apply directly to masonry walls in a two coat stucco application
- · Superior workability

Meets the requirements of ASTM C 926 for cement based plaster

Item No.	Package Size	Metric	Quantity
1139-81	50 lb. bag	22.7 kg	56/pallet
1139-80	80 lb. bag	36.2 kg	42/pallet
Ext. Board			
1139-87	80 lb. bag	36.2 kg	42/pallet



BASE COAT STUCCO-PUMP GRADE

A fiber reinforced contractor grade pre-blended Portland cement based scratch and brown coat stucco mix.

Use For:

- · Scratch and brown coat in a three coat stucco application
- Apply directly to masonry walls in a two coat stucco application
- · May be spray or trowel applied

Exceeds the requirements of ASTM C 926 for Portland cement based plaster

Item No.	Package Size	Metric	Quantity
1139-86	80 lb. bag	36.2 kg	42/pallet



BASE COAT STUCCO with WATER-STOP

An exterior stucco with Water-Stop additive, used for the construction and repair of stucco walls. The Water-Stop, waterproofing additive prevents moisture penetration from wind driven rain.

Use For:

- Scratch and brown coat in a three coat stucco application
- Apply directly to masonry walls in a two coat stucco application

Meets the requirements of ASTM C 926 requirements for cement based plaster.

Item No.	Package Size	Metric	Quantity
1139-89	80 lb. bag	36.2 kg	42/pallet



FINISH COAT STUCCO

A stucco finishing plaster designed for use as a color and texture coat over Portland cement base coat or QUIKRETE® Fiberglass Reinforced Stucco. Requires only the addition of water. Available in white or gray. Color can be added using QUIKRETE® Stucco & Mortar Color.

Use For:

A decorative color and texture finish coat for stucco

90 lb. (40.5 kg) Finish Coat Stucco Available Regionally

Item No.	Package Size	Metric	Quantity
White			
1201-80	80 lb. bag	36.2 kg	42/pallet
1201-80	80 lb. bag	36.2 kg	24/mini pallet
1201-91	90 lb. bag	40.8 kg	35/pallet
Gray			
1202-80	80 lb. bag	36.2 kg	42/pallet
1202-80	80 lb. bag	36.2 kg	24/mini pallet
1201-92	90 lb. bag	40.8 kg	35/pallet



Item No.	Package Size	Metric	Quantity	
8650-32	1 qt. pail	.95 L	24/case	





QUIKWALL® SURFACE BONDING CEMENT

An alkali resistant fiberglass reinforced, Portland cement based surface bonding cement used for construction of drystack (without mortar) cement block walls. Add color with QUIKRETE® Stucco & Mortar Color. **Use For:**

- Waterproofing and strengthening block walls without mortan
- Rehabilitating existing walls with a water-resistant & decorative coating
- Construction of structural and non-structural walls

Meets the requirements of ASTM C 887

PRE-MIXED STUCCO PATCH

Ready-to-use acrylic latex formula for making repairs to cracks, breaks and holes up to 1/4" thick in stucco surfaces.

- Dries to a durable and flexible finish
- Sanded formula blends with the texture of surrounding stucco

January 2010 QUIKRETE® celebrates 70th Anniversary with Rose Parade Float





January 2011 Introduces
QR Codes & full-color project photos
featured on QUIKRETE® Repair Products

