

POLYURETHANE SEALANTS, ADHESIVES & ANCHORING EPOXIES



POLYURETHANE SELF-LEVELING SEALANT

High performance, commercial grade, polyurethane sealant, used for sealing cracks and joints in horizontal concrete surfaces. Self leveling formula provides superior adhesion, flexibility and durability. Meets ASTM C 920 Type S, Grade P, Class 25. Available in gray or sandstone.

Use For:

- Sealing expansion joints in concrete slabs
- Sealing cracks in concrete floors, driveways, patios, steps, basements and pool decks

Item No.	Package Size	Metric	Quantity
Gray			
8660-10	10.1 oz. tube	300 mL	12/case
8660-30	29 oz. tube	858 mL	6/case
Sandstone			
8660-31	29 oz. tube	858 mL	6/case



POLYURETHANE NON-SAG SEALANT

High performance, commercial grade polyurethane sealant designed for vertical and overhead surfaces. The non-sag formula provides superior adhesion and flexibility. Meets ASTM C 920, Type S, Grade NS.

Use For:

- Expansion joints in concrete wall panels and stucco walls
- Sealing around window and door openings
- Sealing cracks in concrete, stucco and masonry surfaces

Item No.	Package Size	Metric	Quantity
8660-11	10.1 oz. tube	300 mL	12/case



POLYURETHANE CONSTRUCTION ADHESIVE

High performance, commercial grade adhesive designed for permanently bonding concrete, brick, marble, stone, wood, glass, aluminum, steel, PVC and tile.

Use For:

- Repairing broken concrete
- Bonding retaining wall block and caps

Item No.	Package Size	Metric	Quantity
9902-10	10.1 oz. tube	300 mL	12/case
9902-11	29 oz. tube	858 mL	6/case



POLYURETHANE CONCRETE CRACK SEALANT

Commercial grade polyurethane sealant for permanently sealing and waterproofing cracks in concrete, masonry and stucco surfaces. The textured, non-sag formula blends with the surrounding surface. Dries to a firm, flexible consistency. Use on vertical and horizontal applications

Item No.	Package Size	Metric	Quantity
8620-17	10.1 oz. tube	300 mL	12/case



POLYURETHANE MORTAR JOINT SEALANT

Commercial grade polyurethane sealant for sealing, waterproofing and tuck-pointing damaged and deteriorating mortar joints. The textured, matte-finish non-sag formula blends with surrounding mortar joints. Dries to a firm, flexible consistency.

Item No.	Package Size	Metric	Quantity
8620-18	10.1 oz. tube	300 mL	12/case



ANCHORING EPOXY

A two component, high modulus, non-sag, gray, structural epoxy. Anchoring Epoxy is solvent free, low odor, high strength and moisture insensitive. FastSet Anchoring Epoxy is suitable for vertical or horizontal applications with a working time of 4-5 minutes. High Strength Anchoring Epoxy is suitable for horizontal applications with a working time of approximately 20 minutes.

Use For:

- Anchoring bolts, threaded rods, tie bars and rebar dowels into concrete and masonry substrates.
- Bonding raised reflective pavement markers to concrete or asphalt.

Item No.	Package Size	Metric	Quantity
FastSet			
8620-30	8.6 oz. tube	255 mL	12/case
High Strength			
8620-31	8.6 oz. tube	255 mL	12/case



BACKER ROD

Foam rope used to partially fill large cracks, gaps and joints before applying sealant. Use for horizontal and vertical applications. Available in 3/4" diameter in 20 foot lengths.

Item No.	Package Size	Metric	Quantity
6917-42	3/4" diameter 20' long	19.1 mm x 6 M	12/case

January 1994 Introduces
Liquid Cement Colors



1995



60th Plant

January 1995 Introduces
Acrylic Concrete Cure & Seal



January 1996
Introduces
bilingual packaging